

International Civil Aviation Organization

MID Region ATM Enhancement Programme Steering Committee

Second Meeting (MAEP SC/2) (Cairo, Egypt, 20-22 October 2015)

Agenda Item 2: MAEP Projects/Working Packages

MID IP NETWORK

(Presented by the Secretariat)

SUMMARY

This paper presents the MID IP Network project in order to explore scenarios including the funding options to be presented to the MAEP Board, which would expedite the establishment of the project.

Action by the meeting is at paragraph 3.

REFERENCES

MIDANPIRG/15 Report

1. INTRODUCTION

1.1 The IP network telecommunication service has been used worldwide to provide a private network for banking and oil industries and has proved its service is reliable and affordable. The IP network is the only economical means to provide a standard telecommunication interface between ANSPs to meet the challenge of supporting ever increasing demand in information exchange required by System Wide Information Management (SWIM) and other services.

2. DISCUSSION

2.1 The MIDANPIRG/15 meeting recognized the necessity for a Regional Telecommunication Network for all Aeronautical Fixed Services (AFTN, AMHS, AIDC/OLDI, surveillance data sharing, etc.). Furthermore, the meeting recalled that MIDANPRG/14 meeting reiterated that the MID ATN implementation and MID IP Network should take place on the basis of regionally agreed requirements, taking into consideration, the System Wide Information Management (SWIM) concept and any other new developments. It was further recognized that the current Point-to-Point circuit arrangement between States to support the Aeronautical Fixed Service (AFS) enhancement will not cope with the advanced technologies and has many limitations.

2.2 The meeting may wish to recall the current Point-to-Point circuit arrangement between States to support Aeronautical Fixed Service (AFS) enhancement has the following issues:

- Half circuit arrangement between States is increasingly difficult to order and time consuming.
- Circuit upgrade between States is also impacted due to variable pricing and bandwidth availability of the half circuit at each State.

- Dynamic routing is not supported due to limited bandwidth and no central administration of the network.
- Incompatible network protocol does not support Extended Service as specified in ICAO Doc. 9880 and IPv6 addressing as specified in ICAO Doc. 9896.
- New future Information Management as recommended by ICAO 12th Air Navigation Conference, such as System Wide Information Management (SWIM), is not supported.
- Network security measures cannot be implemented, which leads many States to implement their own security measures and policy, adding to overall costs.
- Different budget cycles and priorities between States make the synchronization of upgrades difficult and in turn limit the seamless distribution of Aeronautical Fixed Service (AFS) data.

2.3 The European Region has implemented the Pan-European Network Service (PENS) and North American Region has FAA Telecommunication Infrastructure (FTI) to support Canada and USA to distribute AFS data. Similarly, other ICAO Regions South America has REDDIG and Caribbean has MEVA and the APAC Region is planning for the implementation of Common Regional Virtual Private Network (CRV).

2.4 In the MID Region there was a proposal for the feasibility study for implementing a Middle East Network Services (MENS) concept by the IPS WG/2 meeting in October 2009; this was not mature enough at that time. However, the last three MIDANPIRG reports highlighted the need for a MID IP Network and it was clearly mentioned in several reports that the MID IP Network is to be established based on regional agreement and requirement.

2.5 Any MID IP Network establishment should consider the following:

- reduce telecommunication cost;
- enhance information security;
- support new enhancements;
- provide a dynamic network;
- minimize coordination for network management and enhancement; and
- respond to Air Traffic requirements in a timely manner.

2.6 In order to establish a private network, the following are required:

- the cost has to be equal or less than the current cost by utilizing existing commercially available infrastructure;
- a common telecommunication network provider; and
- a selected common telecommunication service provider will work with local provider for access.

2.7 It is to be noted that the network will be private network and not public internet. Any users of the network can be connected to one another as configured through the Network Administrator. The establishment of MID IP Networks is to be in line with ICAO SARPs and guidance material to ensure secured and efficient operation.

2.8 The MIDANPIRG/15 meeting agreed that a MID IP Network needs to be established to cope with the current and future requirements. In this respect, the meeting considered the following two options:

- a) Private Network MENS i.e. similar to the European Network (PENS); or
- b) join the APAC CRV Network.

2.9 Based on the CNS SG/6 meeting Draft Conclusion 6/2 a MID IP Network Action Group was established and developed the MID IP Network Project Proposal at **Appendix A**, which was reviewed by the MSG/4 meeting. Accordingly, the MID IP Network was endorsed as a priority project under MAEP.

2.10 The MIDANPIRG/15 meeting noted that the APAC States funded an ICAO TCB project for the evaluation of the CRV Network, and they are now in stage 2 (implementation) and they welcome interested MID States to join the project. The meeting agreed that the establishment of the MID IP Network needs to be expedited to cope with the current and future requirements.

3. ACTION BY THE MEETING

3.1 The meeting is invited to:

- a) review the project proposal at Appendix A; and
- b) recommend actions/scenarios including funding options to the MAEP Board, which would expedite the establishment process of the MID IP Network project.

APPENDIX A



MID IP Network

Project proposal

Submitted by

MID IP network Action group

Date Version 09/11/2014 0.1

MID IP Network Project



Change Control

Version	Change	Date
0.1	Initial draft	9/11/2014

MID IP Network Project



Table of contents

Content	Page Num.
Executive Summary	4
Problem Statement	4
Project Objectives	4
Scope	5
Implementation plan	9
Attachments A and B	11-35



Executive Summary

This document developed by the MID IP Action Group to justify the need to have an IP Network in the ICAO MID Region which will be an enabler for many performance improvement planned to be implemented. Accordingly, this is document is developed for consideration of this MID IP Network as a candidate project to be submitted to the MAEP Board. The Project aims to create a single IP Backbone for MID Region Air Traffic Management Community, and will be capable to respond to future Air Traffic requirements in a timely manner.

The proposed MID IP Network is in line with ICAO Global Air Navigation Plan (GANP), it will be an enabler for the successful implementation of many ASBU Modules like:

- 1- B0-FICE and B1-FICE Increased Interoperability, Efficiency & Capacity through FF-ICE/1 application before Departure
- 2- B1-SWIM Performance Improvement through the Application of System Wide Information Management (SWIM);
- 3- B1-DATM Service Improvement through Integration of all Digital ATM Information; and
- 4- B1-AMET Enhanced Operational Decisions through Integrated Weather Information

Problem Statement

States in the MID have multi point to point circuits, to ensure high service availability relying on bilateral connections. In addition to the high running cost the current infrastructure depending on obsolete technology which can be an obstacle to implement the latest CNS technologies.

An example for the Current Point-to-Point circuit arrangement between MID States to support only the Aeronautical Fixed Service (AFS) Enhancement has the following issues:



- Half circuit arrangement between States is increasingly difficult to order and time consuming.
- Circuit upgrade between States is also impacted due to variable pricing and bandwidth availability of the half circuit at each State.
- Dynamic routing is not supported due to limited bandwidth and no central administration of the network.
- Incompatible network protocol does not support Extended Service as specified in ICAO Doc. 9880 and IPv6 addressing as specified in ICAO Doc. 9896.
- New future Information Management as recommended by ICAO 12th Air Navigation Conference, such as System Wide Information Management (SWIM), is not supported.
- Network security measures cannot be implemented, which leads many States to implement their own security measures and policy, adding to overall costs.
- Different budget cycles and priorities between States make the synchronization of upgrades difficult and in turn limit the seamless distribution of Aeronautical Fixed Service (AFS) data.

Project Objectives

- 1- To create cost-effective, robust and secured network for all ground-to –ground ATM Application and capable to respond to future Air Traffic requirements in a timely manner
- 2- Ease Migration of ATM Application to the IP standard (IPv4 and IPv6)
- 3- Facilitate data sharing in a secured way
- 4- create a shared Network for all ATM stakeholders like Airport operators, Airline, ... etc
- 5- Minimize coordination for network management and enhancement;
- 6- provide a dynamic network and support new enhancements.



Scope

Instead of having several fragmented States Network, the MID IP network will be the common Network for Ground to Ground Application with interconnectivity with other ICAO Regions networks, mainly the European Network (PENS), the APAC CRV Network, the AFI network and the VSAT network currently in operation in MID and AFI.

1- ATS Message Handling System (AMHS):

The AMHS is an ICAO standard to exchange messages pertaining safety of Air Navigation services, and it should be implemented using Internet Protocol suite (IPS), the MID IP Network will foster the AMHS Implementation

2- Voice Communication:

The coordination between Air Traffic control centers is carried out by using Analog voice communication or the using the multiplexer; the MID IP Network will enable the Implementation of Voice over IP which can improve the quality and redundancy.

3- OLDI/AIDC

The implementation B0-FICE (Increased Interoperability, Efficiency and Capacity through Ground-Ground Integration), will improve coordination between Air Traffic Service Units (ATSUs) by using ATS Interfacility Data Communication (AIDC) and/or On-Line Data Interchange (OLDI). The transfer of communication in a data link environment improves the efficiency of this process. The standard messages for coordination between ATSUs centers can be easily implemented over the IP network, the capability to implement IPv6 enables running of the future services will further bring benefits. The implementation of Ground-Ground integration can bring immediate benefits on safety and reduce ATCO workload.



4- Surveillance Data Sharing

Exchanging the Radar and ADS-B data between States have a significant impact to improve the Situational awareness coverage and Availability in Flight Information Regions., this results in improved safety.

5- National IP Network

The National IP network could be prerequisite to become a User of the new one. Each State's Network should be connected the MID IP Network. The MID Regional IP addresses for States networks are at Attachments A and attachment B provide the current Status of the networks in MID States.

6- Future Services

Like trajectory based operations, connection with Airline Network, Airport Network and Meteorology and other enhanced services will become easier. All information contained in different systems could be exchanged.

No.	Task	Task Owner	Status	Duration
Proj	ect Initiation			
1	Earmark the MID IP Project in	ICAO MID	Done	1 day
	the MID region plans	Office		
2	Identify Stakeholder to propose	CNS SG/6	Done	1 day
	the project			
3	Initial Project requirement	MID IP	Done	1 month
	document proposal	Network AG		
4	Initial review of project	MSG/4		1 day
	proposal			
5	Guide the Project process and	MAEP Board		
	initial agreement on project			
6	Agree on project team leader	MAEP		

General Implementation tasks and phases



7	Nominate Expert as members	MAEP	
	of the project team		
Deve	elop Business Requirements		
8	Develop Concept of operation		
9	Update the result of the IP		
	Survey		
Sear	ch for the Best Technical		
Solu	tion		
10	Facilitate a workshop With		
	States and telecommunication		
	Industry		
11	Prepare Request for		
1.0	Information		
12	Publish RFI		
Con	duct Dialog with Vendors		
10			
13	Form Answer committee		
14	Receive Vendor Questions		
15	Post Answer to Vendors		
T 1	question		
Iden	tily viable Alternatives		
16	Receive Vendors approach in		
	response to the RFI		
17	Select and document Viable		
	alternatives		
18	Define and Finalize evaluation		
	Criteria and Statement of need		
19	Develop Evaluation Plan		
Req	uest for Proposals (RFP)		
20	Prepare RFP document		
21	Publish RFP		
22	Receive Vendors proposals		
Eval	uation of RFP proposals		
23	Evaluate proposals		
24	Award Contract		
Man	age performance-based		
		•	•



MID IP Network Project

Contract			
25	Designate Contract management committee		
26	Prepare contract management plan		
27	Facilitate contract management		



This is page is left blank intentionally

APPENDIX A

Attachment A

THE PROPOSED IPv4 ADDRESS PLAN for MID REGION

Introduction

The IPv4 address scheme is proposed by the Caribbean and South American Regional for its ATN/IPS Network. The MID Region's plan was also part of their global IPv4 addressing assignment. The MID Region is requested to review this proposed IP addressing assignment for consideration and adoption.

Objectives

This document is meant to describe the addressing plan for IPv4 addresses throughout the MID Region. This document defines the recommended address format for IPv4 addresses. The document lists the addresses allocated to States in the MID Region and the interstate connections IP's. The implementation of the proposed plan will go into stages and should be carefully coordinated between States.

ICAO	_	International Civil Aviation Organization			
AMHS	_	ATN Message Handling System			
ARP -		Address Resolution Protocol			
ATN	_	Aeronautical Telecommunications Network			
CNS		Communication Navigation Surveillance			
BGP	-	Border Gateway Protocol			
DNS	-	Domain Name Service			
IANA	-	Internet Assigned Numbers Authority			
ICS	-	ATN Internet Communication Service			
IP -		ATN Internet Communication Service			
IPV4 -		Internet Protocol Version 4			
IPV6 -		Internet Protocol Version 6			
IPS	-	Internet Protocol suite			
LACNIC	-	Latin American and Caribbean Internet Address			
		Registry			
LIR	-	Local Internet Registry			
OSPF	-	Open Shortest Path First			
RIR	-	Regional Internet Registry			
ANSP	-	Air Navigation Service Provider			
ISP	-	Internet Service Provider			
APAC	-	Asia and Pacific			
CAR	_	Caribbean			
SAM	- South America				

Acronyms



MID IP Network Project

MID	-	Middle east
WACAF	-	West And Central Africa
ESAF	- East And South Africa	
PDU	-	Packet Data Unit
MTA	-	Message Transfer Agent
UA	-	User Agent
ACP	-	Aeronautical Communication Panel
SWIM	-	System Wide Information Management
PENS	-	PAN European Network Service
IMS	-	Information Management Service

Global IPv4 assignments

	IPv4 Address																																
	10 Region State / Territory						Host's																										
0	0) (0	0	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0	0	0	1
			1	st.	By	te					2r	nd.	By	te					- 3	rd.	By	te						4	th.	By	te		

- ▶ 0000 => SAM: South American Office.
- ▶ 0001 => NACC: North American, American Power station and Caribbean Office.
- > 0010 => APAC: Asia and Pacific Office.
- ➢ 0011 => MID: Middle East Office.
- > 0100 => WACAF: Western and Central African Office.
 > 0101 => ESAF: Eastern and Southern African Office.
- => EUR/NAT: European and North Atlantic Office. ➢ 0110

IP address Scheme Characteristics:

The proposed IPv4 address allocation scheme will be able to cover:

- 128 States
- 8190 Hosts for each State.
- 2048 Point-to-Point links. •



Network Assignments

Issue	State	Network	Direction	Decimal Notation		Bin	ary Notation	
			Used		1 st Byte	Region	State	Host
1	Bahrain	10.48.0.0/19	First	10.48.0.1	00001010.	0011	000.000	00000.00000001
			Last	10.48.31.254	00001010.	0011	000.000	11111. 11111110
2	Egypt	10.48.32.0/19	First	10.48.32.1	00001010.	0011	0000.001	00000.00000001
			Last	10.48.63.254	00001010.	0011	0000.001	11111. 11111110
3	Iran	10.48.64.0/19	First	10.48.64.1	00001010.	0011	0000.010	00000.0000001
			Last	10.48.95.254	00001010.	0011	0000.010	11111. 11111110
4	Iraq	10.48.96.0/19	First	10.48.96.1	00001010.	0011	0000.011	00000.00000001
			Last	10.48.127.254	00001010.	0011	0000.011	11111. 11111110
5	Jordan	10.48.128.0/19	First	10.48.128.1	00001010.	0011	0000.100	00000.00000001
			Last	10.48.159.254	00001010.	0011	0000.100	11111.1 1111110
6	Kuwait	10.48.160.0/19	First	10.48.160.1	00001010.	0011	0000.101	00000.00000001
			Last	10.48.191.254	00001010.	0011	0000.101	11111.11111110
7	Lebanon	10.48.192.0/19	First	10.48.192.1	00001010.	0011	0000.110	00000.0000001
			Last	10.48.223.254	00001010.	0011	0000.110	11111.1 1111110
8	Libya	10.48.224.0/19	First	10.48.224.1	00001010.	0011	0000.111	00000.0000001
			Last	10.48.255.254	00001010.	0011	0000.111	11111.1 1111110
9	Oman	10.49.0.0/19	First	10.49.0.1	00001010.	0011	0001.000	00000.0000001
			Last	10.49.31.1	00001010.	0011	0001.000	11111. 11111110
10	Qatar	10.49.32.0/19	First	10.49.32.1	00001010.	0011	0001.001	00000.0000001
			Last	10.49.63.254	00001010.	0011	0001.001	11111. 11111110
11	Saudi Arabia	10.49.64.0/19	First	10.49.64.1	00001010.	0011	0001.010	00000.00000001
			Last	10.49.95.254	00001010.	0011	0001.010	11111. 11111110
12	Sudan	10.49.96.0/19	First	10.49.96.1	00001010.	0011	0001.011	00000.00000001
			Last	10.49.127.254	00001010.	0011	0001.011	11111. 11111110
13	Syria	10.49.128.0/19	First	10.49.128.1	00001010.	0011	0001.100	00000.0000001
			Last	10.49.159.254	00001010.	0011	0001.100	11111.1 1111110
14	UAE	10 .49 .160.0 /19	First	10.49.160.1	00001010.	0011	0001.101	00000.00000001
			Last	10 .49 .191.254	00001010.	0011	0001.101	11111. 11111110
15	Yemen	10 .49 .192.0 /19	First	10 .49 .192.1	00001010.	0011	0001.110	00000.00000001
			Last	10 .49 .223.254	00001010.	0011	0001.110	11111.11111110







Range 1	Range 2	Range 3	Range 4
10.48.0.0 - 10.48.31.255	10.49.0.0 - 10.49.31.255	10.50.0.0 - 10.51.31.255	10.51.0.0 - 10.51.31.255
10.48.32.0 - 10.48.63.255	10 .49 .32 .0 - 10 .49 .63 .255	10.50.32.0 - 10.51.63.255	10.51.32.0 - 10.51.63.255
10.48.64.0 - 10.48.95.255	10.49.64.0 - 10.49.95.255	10.50.64.0 - 10.51.95.255	10.51.64.0 - 10.51.95.255
10.48.96.0 - 10.48.127.255	10.49.96.0 - 10.49.127.255	10.50.96.0 - 10.51.127.255	10.51.96.0 - 10.51.127.255
10.48.128.0 - 10.48.159.255	10.49.128.0 - 10.49.159.255	10.50.128.0 - 10.51.159.255	10.51.128.0 - 10.51.159.255
10 .48 .160.0 - 10 .48 .191 .255	10 .49 .160.0 - 10 .49 .191 .255	10 .50 .160.0 - 10 .51 .191 .255	10 .51 .160.0 - 10 .51 .191 .255
10 .48 .192.0 - 10 .48 .223 .255	10 .49 .192.0 - 10 .49 .223 .255	10.50.192.0 - 10.51.223.255	10 .51 .192.0 - 10 .51 .223 .255
10.48.224.0 - 10.48.225.255	10.49.224.0 - 10.49.225.255	10.50.224.0 - 10.51.225.255	10.51.224.0 - 10.51.225.255
Range 5	Range 6	Range 7	Range 8
10.52.0.0 - 10.52.31.255	10.53.0.0 - 10.53.31.255	10.54.0.0 - 10.54.31.255	10.55.0.0 - 10.55.31.255
10.52.32.0 - 10.52.63.255	10.53.32.0 - 10.53.63.255	10.54.32.0 - 10.54.63.255	10.55.32.0 - 10.55.63.255
10.52.64.0 - 10.52.95.255	10.53.64.0 - 10.53.95.255	10.54.64.0 - 10.54.95.255	10.55.64.0 - 10.55.95.255
10.52.96.0 - 10.52.127.255	10.53.96.0 - 10.53.127.255	10.54.96.0 - 10.54.127.255	10.55.96.0 - 10.55.127.255
10.52.128.0 - 10.52.159.255	10.53.128.0 - 10.53.159.255	10.54.128.0 - 10.54.159.255	10.55.128.0 - 10.55.159.255
10 .52 .160.0 - 10 .52 .191 .255	10 .53 .160.0 - 10 .53 .191 .255	10.54.160.0 - 10.54.191.255	10 .55 .160.0 - 10 .55 .191 .255
10 .52 .192.0 - 10 .52 .223 .255	10 .53 .192.0 - 10 .53 .223 .255	10.54.192.0 - 10.54.223.255	10.55.192.0 - 10.55.223.255
10.52.224.0 - 10.52.225.255	10.53.224.0 - 10.53.225.255	10.54.224.0 - 10.54.225.255	10.55.224.0 - 10.55.225.255
Range 9	Range 10	Range 11	Range 12
10.56.0.0 - 10.56.31.255	10 .57 .0 .0 - 10 .57 .31 .255	10.58.0.0 - 10.58.31.255	10.59.0.0 - 10.59.31.255
10.56.32.0 - 10.56.63.255	10.57.32.0 - 10.57.63.255	10.58.32.0 - 10.58.63.255	10.59.32.0 - 10.59.63.255
10.56.64.0 - 10.56.95.255	10.57.64.0 - 10.57.95.255	10.58.64.0 - 10.58.95.255	10.59.64.0 - 10.59.95.255
10.56.96.0 - 10.56.127.255	10.57.96.0 - 10.57.127.255	10.58.96.0 - 10.58.127.255	10.59.96.0 - 10.59.127.255
10 .56 .128.0 - 10 .56 .159 .255	10 .57 .128.0 - 10 .57 .159 .255	10.58.128.0 - 10.58.159.255	10.59.128.0 - 10.59.159.255
10 .56 .160.0 - 10 .56 .191 .255	10 .57 .160.0 - 10 .57 .191 .255	10 .58 .160.0 - 10 .58 .191 .255	10 .59 .160.0 - 10 .59 .191 .255
10 .56 .192.0 - 10 .56 .223 .255	10 .57 .192.0 - 10 .57 .223 .255	10 .58 .192.0 - 10 .58 .223 .255	10 .59 .192.0 - 10 .59 .223 .255
10.56.224.0 - 10.56.225.255	10.57.224.0 - 10.57.225.255	10 .58.224 .0 - 10 .58 . 225.255	10.59.224.0 - 10.59.225.255
Range 13	Range 14	Range 15	Range 16
10.60.0 .0 - 10.60.31.255	10.61.0 .0 - 10.61.31.255	10.62.0 .0 - 10.62.31.255	10.63.0 .0 - 10.63.31.255
10.60.32.0 - 10.60.63.255			
	10 .61 .32 .0 - 10 .61 .63 .255	10.62.32.0 - 10.62.63.255	10 .63 .32 .0 - 10 .63 .63 .255
10.60.64.0 - 10.60.95.255	10.61.32.0-10.61.63.25510.61.64.0-10.61.95.255	10.62.32.0 - 10.62.63.255 10.62.64.0 - 10.62.95.255	10.63.32.0 - 10.63.63.255 10.63.64.0 - 10.63.95.255
10.60.64.0 - 10.60.95.255 10.60.96.0 - 10.60.127.255	10.61.32.0 - 10.61.63.255 10.61.64.0 - 10.61.95.255 10.61.96.0 - 10.61.127.255	10.62.32.0 - 10.62.63.255 10.62.64.0 - 10.62.95.255 10.62.96.0 - 10.62.127.255	10.63.32.0 - 10.63.63.255 10.63.64.0 - 10.63.95.255 10.63.96.0 - 10.63.127.255
10.60.64.0 - 10.60.95.255 10.60.96.0 - 10.60.127.255 10.60.128.0 - 10.60.159.255	10.61.32.0 - 10.61.63.255 10.61.64.0 - 10.61.95.255 10.61.96.0 - 10.61.127.255 10.61.128.0 - 10.61.159.255	10.62.32.0 - 10.62.63.255 10.62.64.0 - 10.62.95.255 10.62.96.0 - 10.62.127.255 10.62.128.0 - 10.62.159.255	10.63.32.0 - 10.63.63.255 10.63.64.0 - 10.63.95.255 10.63.96.0 - 10.63.127.255 10.63.128.0 - 10.63.159.255
10.60.64.0 - 10.60.95.255 10.60.96.0 - 10.60.127.255 10.60.128.0 - 10.60.159.255 10.60.160.0 - 10.60.191.255	10.61.32.0 - 10.61.63.255 10.61.64.0 - 10.61.95.255 10.61.96.0 - 10.61.127.255 10.61.128.0 - 10.61.159.255 10.61.160.0 - 10.61.191.255	10.62.32.0 - 10.62.63.255 10.62.64.0 - 10.62.95.255 10.62.96.0 - 10.62.127.255 10.62.128.0 - 10.62.159.255 10.62.160.0 - 10.62.191.255	10.63.32.0 - 10.63.63.255 10.63.64.0 - 10.63.95.255 10.63.96.0 - 10.63.127.255 10.63.128.0 - 10.63.159.255 10.63.160.0 - 10.63.191.255
10.60.64.0 - 10.60.95.255 10.60.96.0 - 10.60.127.255 10.60.128.0 - 10.60.159.255 10.60.160.0 - 10.60.191.255 10.60.192.0 - 10.60.223.255	10.61.32.0 - 10.61.63.255 10.61.64.0 - 10.61.95.255 10.61.96.0 - 10.61.127.255 10.61.128.0 - 10.61.159.255 10.61.160.0 - 10.61.191.255 10.61.192.0 - 10.61.223.255	10.62.32.0 - 10.62.63.255 10.62.64.0 - 10.62.95.255 10.62.96.0 - 10.62.127.255 10.62.128.0 - 10.62.159.255 10.62.160.0 - 10.62.191.255 10.62.192.0 - 10.62.223.255	10.63.32.0 - 10.63.63.255 10.63.64.0 - 10.63.95.255 10.63.96.0 - 10.63.127.255 10.63.128.0 - 10.63.159.255 10.63.160.0 - 10.63.191.255 10.63.192.0 - 10.63.223.255



MID REGION SUB-NETWORKS

(Orange=State Range Blue=Vacancy

Red= Reserved)

MID Region intra-Regional Links (Point to Point)

-	-		10.63.224.0
10.63.224. 0 /30	Bahrain - Riyadh	Bahrain	10.63.224.1
		Riyadh	10.63.224.2
			10.63.224.3
			10.63.224.4
10.63.224. 4 /30	Bahrain - Dammam	Bahrain	10.63.224.5
		Dammam	10.63.224.6
			10.63.224.7
			10.63.224.8
10.63.224. 8 /30	Bahrain - Jeddah	Bahrain	10.63.224.9
		Jeddah	10.63.224.10
			10.63.224.11
			10.63.224.12
10.63.224. 12 /30	Bahrain - Kuwait	Bahrain	10.63.224.13
		Kuwait	10.63.224.14
			10.63.224.15
			10.63.224.16
10.63.224. 16 /30	Bahrain – Doha1	Bahrain	10.63.224.17
		Doha1	10.63.224.18
			10.63.224.19
			10.63.224.20
10.63.224. 20 /30	Bahrain – Doha2	Bahrain	10.63.224.21
		Doha2	10.63.224.22
			10.63.224.23
			10.63.224.24
10.63.224. 24 /30	Bahrain – AbuDhabi1	Bahrain	10.63.224.25
		AbuDhabi1	10.63.224.26
			10.63.224.27



			10.63.224.28
10.63.224. 28 /30	Bahrain – AbuDhabi2	Bahrain	10.63.224.29
		AbuDhabi2	10.63.224.30
			10.63.224.31
Sub-Network	Connected Route	Host / State	IP Address
			10.63.224.32
10.63.224. 32 /30	Bahrain – Tehran	Bahrain	10.63.224.33
		Tehran	10.63.224.34
			10.63.224.35
			10.63.224.64
10.63.224. 64 /30	Egypt – Amman	Egypt	10.63.224.65
		Amman	10.63.224.66
			10.63.224.67
			10.63.224.68
10.63.224.68/30	Egypt – Jeddah1	Egypt	10.63.224.69
		Jeddah1	10.63.224.70
			10.63.224.71
			10.63.224.72
10.63.224. 72 /30	Egypt – Jeddah2	Egypt	10.63.224.73
		Jeddah2	10.63.224.74
			10.63.224.75
			10.63.224.76
10.63.224. 76 /30	Egypt – Riyadh	Egypt	10.63.224.77
		Riyadh	10.63.224.78
			10.63.224.79
	12Sub-Networks are reserved for	or future links (10.63.224.80/30 ·	- 10.63.224.127/30)
			10.63.224. 128
10.63.224. 128 /30	Iran - Iraq	Iran	10.63.224. 129
		Iraq	10.63.224.130
			10.63.224.131
			10.63.224.132
10.63.224. 132 /30	Iran - Kuwait	Iran	10.63.224. 133



		Kuwait	10.63.224. 134	
			10.63.224. 135	
	14 Sub-Networks are reserved for fut	ure links (10.63.224.136/30 -		
			10.63.224. 192	
10.63.224. 192 /30	Jordan - Jeddah	Jordan	10.63.224. 193	
		Jeddah	10.63.224. 194	
			10.63.224. 195	
Sub-Network	Connected Route	Host / State	IP Address	
			10.63.225.0	
10.63.225. 0 /30	Kuwait - Iraq	Kuwait	10.63.225.1	
		Iraq	10.63.225.2	
			10.63.225.3	
	15 Sub-Networks are reserved for f		10.63.225.63/30)	
			10.63.225.64	
10.63.225.64 /30	Qatar – Abu Dhabi	Qatar	10.63.225.65	
		Abu Dhabi	10.63.225.66	
			10.63.225.67	
	15 Sub-Networks are reserved for fu	ture links (10.63.225.68/30 –	10.63.225.127/30)	
			10.63.225.128	
10.63.225.128 /30	Saudi Arabia (Jeddah) -	Jeddah	10.63.225.129	
	Muscat	Muscat	10.63.225.130	
			10.63.225.131	
	15 Sub-Networks are reserved for fut	ure links (10.63.225.132/30 -	- 10.63.225.191/30)	
			10.63.225. 192	
10.63.225.192 /30	UAE (Abu Dhabi) -	Abu Dhabi	10.63.225. 193	
	Muscat	Muscat	10.63.225. 194	
			10.63.225. 195	
	15 Sub-Networks are reserved for fut	ure links (10.63.225.196/30 -	- 10.63.225.255/30)	
 10.64.226. 0/30	Lebanon			
	16 Sub-Networks are reserved for f	uture links (10.63.226.0/30 –	10.63.226.63/30)	
 10.63.226. 64 /30	Sudan			



6 Sub-Networks are reserved for future links (10.63.226.64/30 – 10.63.226.127/30)

Remark: In case of a new IP link between two states, both States will have to use the next available IP address range as specified in the above table.



MID Region intra-Regional Links (Per State)

No.	State	Connected Route	Local Interface	Next Hop Interface
1	Bahrain	Bahrain - Riyadh	10.63.224.1	10.63.224.2
		Bahrain - Dammam	10.63.224.5	10.63.224.6
		Bahrain - Jeddah	10.63.224.9	10.63.224.10
		Bahrain - Kuwait	10.63.224.13	10.63.224.14
		Bahrain – Doha1	10.63.224.17	10.63.224.18
		Bahrain – Doha2	10.63.224.21	10.63.224.22
		Bahrain – AbuDhabi1	10.63.224.25	10.63.224.26
		Bahrain – AbuDhabi2	10.63.224.29	10.63.224.30
		Bahrain – Tehran	10.63.224.33	10.63.224.34
_				
2	Egypt	Egypt-Amman	10.63.224.65	10.63.224.66
		Egypt-Jeddah1	10.63.224.69	10.63.224.70
		Egypt-Jeddah2	10.63.224.73	10.63.224.74
		Egypt-Riyadh	10.63.224.77	10.63.224.78
3	Iran	Iran-Irag	10.63.224.129	10 63 224 130
•	ITall	Iran-Kuwait	10.63.224 133	10.63.224.134
		Iran-Bahrain	10 63 224 34	10.63.224.33
			10:00:12 1:0 1	10100122 1100
4	Iraq	Iraq-iran	10.63.224.130	10.63.224. 129
	•			
5	Jordan	Jordan - Jeddah	10.63.224. 193	10.63.224. 194
		Jordan - Cairo	10.63.224.66	10.63.224.65
6	Kuwait	Kuwait-Bahrain	10.63.224.14	10.63.224.13
		Kuwait-Iraq	10.63.225.1	10.63.225.2
		Kuwait-Iran	10.63.224. 134	10.63.224. 133
7	Lebanon			
~				
8	Libya			



9	Oman			
No.		Connected Route	Local Interface	Next Hop Interface
10	Qatar	Qatar-AbuDhabi	10.63.225.65	10.63.225.66
		Qatar-Bahrain1	10.63.224.18	10.63.224.17
		Qatar-Bahrain2	10.63.224.22	10.63.224.21
11	Saudi Arabia	Jeddah - Muscat	10.63.225.129	10.63.225.130
		Jeddah - Cairo1	10.63.224.70	10.63.224.69
		Jeddah - Cairo2	10.63.224.74	10.63.224.73
		Jeddah - Amman	10.63.224. 194	10.63.224. 193
		Jeddah - Bahrain	10.63.224.10	10.63.224.9
12	Sudan			
13	Syria			
	-			
14	UAE	UAE - Muscat	10.63.225. 193	10.63.225. 194
		UAE - Bahrain1	10.63.224.26	10.63.224.25
		UAE - Bahrain2	10.63.224.30	10.63.224.29
		UAE - Qatar	10.63.225.66	10.63.225.65
15	Yemen			



Impact of Changing Point-to-Point Ip address

The corresponding point-to-point IP line will be down during IP replacement process

Tips to Replace IP address

- 1- Coordinate with the adjacent State to agree on IPs, Routing, etc.
- 2- Make a backup of current configuration of the network devices (Routers, Firewalls... etc.)
- 3- Simulate new configuration on test network devices if possible
- 4- Advise AFS operators about downtime duration & time (for data line) or the controller(for voice line), the AFS operator should direct TFC to alternative CCT, and controller to use alternative voice means(dialup, Backup voice line,...etc.)
- 5- Configure network device with new setting
- 6- Send test data and decide about its reliability
- 7- Advise about its availability.

IP Change Schedule

No	State	Old IP	New IP	Net Mask	Router Type	Target date to change	State to connect to	Circuit speed	Circuit number	Type of Circuit	ISP	State Contact
1	Bahrain											
2	Egypt											
3	Iran											
4	Iraq											
5	Jordan											
6	Kuwait											
7	Lebanon											



MID IP Network Project

8	Libya						
9	Oman						
10	Qatar						
11	Saudi Arabia						
12	Sudan						
13	Syria						
14	UAE						
15	Yemen						

Attachment B

State Bahrain (Manama)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end user interface	Applications in use
Riyadh	64k	Batelco	10.61.11.12	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice
Dammam	64k	Batelco	10.61.11.44	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice
						Serial	AFTN
Tehran	64k	Batelco	172.16.10.2	255.255.255.0	Cisco2800	FXO/FXS	Voice
						Serial	AFTN-Radar
Kuwait	128k	Batelco	10.61.11.8	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice
						Serial	CIDIN
Jeddah	64k	Batelco	10.61.11.48	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice
						Serial	Radar
Doha-1	64k	Batelco	10.61.11.32	255.255.255.252	Motorola Vangurd 6455	FXO/FXS	Voice
						Serial	AFTN
Doha-2	64k	Batelco	10.61.11.56	255.255.255.252	Motorola Vangurd 6455	FXO/FXS	Voice
						Serial	Radar
AbuDhabi-1	64k	Batelco	10.61.11.12	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice
						Serial	CIDIN
AbuDhabi-2	64k	Batelco	10.61.11.16	255.255.255.252	Motorola Vangurd 6435	FXO/FXS	Voice



Figure 1: Bahrain Circuit Diagram

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end	Applications
						user interface	in use
•	CAL	T . 1	10.10.10.2	255 255 255 0		IP	AMHS
Amman	64K	Egypt (ATM)	10.10.10.2 192.168.12.7	255.255.255.0	Motorola Vangurd 6800	FXO/FXS	Voice
		Telecom				FXO/FXS	Voice
Jeddah1	64k	Egypt (ATM)	192.168.80.2	255.255.255.0	Cisco2800	IP	OLDI, Radar
		Telecom				IP	AMHS
Jeddah2	128k	Egypt (ATM)	10.10.10.1	255.255.255.0	Motorola Vangurd 6455	FXO/FXS	Voice
Riyadh	64k	Telecom Egypt (ATM)	192.168.80.2	255.255.255.0	Cisco2800	FXO/FXS	Voice
Tripoli	64k	Telecom Egypt (ATM)	10.10.10.1	255.255.255.0	Cisco1700	Serial	AFTN



Figure 2: Cairo Circuit Diagram

State Egypt (Cairo)

State Saudi Arabia (Jeddah)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end user interface	Applications in use
Cairo1	128k	N/A	192.168.12.0	255.255.255.0	Motorola Vangurd 6455	IP	AHHS
						FXO/FXS	Voice
Cairo2	64k	N/A	N/A	N/A	Motorola Vangurd 6455	IP	AMHS
					Motorola Vangurd 6455	FXO/FXS	Voice
		N/A	192.168.12.0	255.255.255.0	Motorola Vangurd 6455	IP	AHHS
Amman	64k					FXO/FXS	Voice
Muscat	64k	N/A	192.168.12.0	255.255.255.0	Cisco 2811	IP	AHHS
						FXO/FXS	Voice
Manama	64k	N/A	TBD	TBD	Motorola Vangurd 6435	Serial	CIDIN
						FXO/FXS	Voice



Figure 3: Jeddah Circuit Diagram

State IRAN(Tehran)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end	Applications
						user	in use
						interface	
						Serial	AFTN
Bahrain	64k	Iran PPT	172.16.10.2	255.255.255.0	Cisco2811	FXO/FXS	Voice
Baghdad	32k	Iran PPT	192.168.191.14	255.255.255.0	Cisco2811	FXO/FXS	Voice
						Serial	AFTN
Kuwait	64k	Iran PPT	172.16.12.0	255.255.255.0	Cisco2811	FXO/FXS	Voice
Abu Dhahi			172 16 15 0		Cisco 2811	Serial	AFTN
	64k	Iran PPT	172.10.13.0	233.233.233.0	615002811	FXO/FXS	Voice
			172 16 14 0		Cisco 2811	Serial	AFTN
Muscat	64k	Iran PPT	172.10.14.0	255.255.255.0		FXO/FXS	Voice



Figure 4: Tehran Circuit diagram

State UAE (Abu Dhabi)

MID IP Network AG

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end	Application
						user	s in use
						Interface	
	64K	Etisalat	N/A	N/A	Motorola Vangurd 6455	Serial	Radar
Bahrain1 ¹						FXO/FXS	Voice
	64K	Etisalat	N/A	N/A	Motorola Vangurd 6455	Serial	AFTN/CIDI
Bahrain2 ¹							Ν
						FXO/FXS	Voice
	64K	Etisalat	192.168.130.0	255.255.255.0	Motorola Vangurd 6455	Ethernet	AMHS
Oman						FXO/FXS	Voice
	128K	Etisalat	192.168.131.0	255.255.255.0	Motorola Vangurd 6435	Ethernet	AMHS/OLD
Qatar							Ι
						FXO/FXS	Voice
Qatar ²	256K	Etisalat	84.255.163.140	255.255.255.252	Motorola Vanguard 6840	Ethernet	AMHS
Qatar ²	256K	Etisalat	192.168.10.0	255.255.255.252	Cisco 1921	FXS	Voice
						Ethernet	Radar
Amman ³	2Mb	Etisalat	94.56.192.202	255.255.255.0	Fortigate 110C firewall	Ethernet	AMHS
Iran	64K	Etisalat	N/A	N/A	Cisco 2811	Ethernet	AMHS
Irall	041	Lusalat			01500/2011	FXS	Voice

Remarks: ¹ 2

3

The IP addresses for Bahrain links is configured by ISP and not identified on UAE side.

These are planned circuits still under test

The link type between Jordan and Abu Dhabi is over an IPSec connection over the public internet (VPN)



Figure 5: Abu Dhabi Circuit Diagram

State Kuwait (Kuwait)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end user interface	Applications in use
Beirut	64K	Qualitynet			Motorola Modem 3460	N/A	AFTN
Doha	64K	Qualitynet			Motorola Modem 3460	N/A	AFTN
Tehran	64K	Qualitynet	172.16.12.2	255.255.255.252	Cisco 2800	N/A	AFTN-Voice
Damascus	64K	Qualitynet			Motorola Modem 3460	N/A	AFTN
Bahrain	128K	Qualitynet			Motorola Vanguard 6455	N/A	AFTN, Radar
							Voice
Baghdad	64K	Qualitynet	192.1680.160	255.255.255.0	Motorola Modem 3460	N/A	AFTN-Voice

Remarks:

- The connectivity for circuits (Beirut, Doha, Damascus, Karachi and Bahrain) is pure layer 2 there is no IP configuration on these circuits.
- For Tehran circuit there is IP configuration on the WAN side 172.16.12.2/30 (between Quality net and Tehran provider), but there is no IP configuration between Quality net and DGCA Kuwait.



State Jordan (Amman)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end user interface	Applications in use
Cairo	64k	N/A	10.10.10.1	255.255.255.0	Vanguard	N/A	AMHS
						FXO/FXS	Voice
Jeddah	64k	N/A	10.10.10.1	255.255.255.0	Vanguard	N/A	AMHS
						FXO/FXS	Voice
Abu Dhabi*	2M	NITC	193.188.93.19	255.255.255.0	Cisco 5510	N/A	AMHS

* *The* link type between Jordan and Abu Dhabi is over public internet (VPN)



State Iraq (Baghdad)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end user interface	Applications in use
Iran	32k	Passcom	192.168.191.10	255.255.255.0	NDsatcom SkyWan 5000	FXS	Voice
			192.168.191.2	255.255.255.0	NDsatcom SkyWan 5000	FXS	Voice
Kuwait	64k	Passcom	192.168.0.60	255.255.255.0		Ethernet	AFTN



State QATAR (Doha)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end	Applications
						user	in use
						interface	
Abu Dhabi	128k	QTEL	200.200.200.x	255.255.255.252	Motorola Vanguard 6455	serial	AFTN, Radar
						FXO/FXS	Voice
Kuwait	64 k	QTEL	N/A	N/A	New Bridge Modem 2602	Serial	AFTN
Bahrain	64 k	QTEL	N/A	N/A	Motorola Vanguard 6840	serial	AFTN, Radar
						FXO/FXS	AFTN, Radar
Bahrain	64 k	QTEL	N/A	N/A	Motorola Vanguard 6840	FXO/FXS	Voice



Figure 9: Qatar Circuit Diagram

ATT B

State OMAN (Muscat)

State	Speed	ISP	IP Address	Net Mask	Router Type	Data end	Applications
						user	in use
						interface	
Abu Dhabi 6	64 k	OMANTEL	192.168.12.142	255.255.255.0	Motorola Vanguard 6455	serial	AFTN, AMHS
						FXO/FXS	Voice
JEDDAH	64 k	OMANTEL	10.10.10.1	255.255.255.0	Cisco 2800	serial	AFTN, AMHS
						FXO/FXS	Voice
Bahrain	64 k	OMANTEL	192.168.30.1	255.255.255.0	Cisco 2800	serial	AFTN, Radar
						FXO/FXS	AFTN, Radar
Iran	64 k	OMANTEL	172.16.14.0	255.255.255.252	Cisco 2800	FXO/FXS	Voice



Figure 10: Oman Circuit Diagram

Remark:

After conducting the IP network Survey, *Common infrastructure characteristics in all states have been found as follows:*

- Lebanon is in process of migration three circuits to IP networks (Kuwait, Bahrain, and Jeddah).
- Libya, Sudan, Syria and Yemen do not have IP circuits implemented
- Security Measure: Not implemented*
- Voice interfaces: FXO/FXS
- Voice Protocol Supported: SIP,H.323
- All IP circuits is using IPv4
- Link Type: Leased Line.
- Router interfaces: Async Serial, Sync Serial, Ethernet
- * Jordan has a firewall device CISCO ASA5510 for Abu Dhabi link (VPN)

- END --