



Airport - Collaborative Decision Making Information sharing

Dave Booth

A-CDM Implementation Manager



Challenges










- No complete & common picture on the flight progress
- Partners are dealing with the flight independently from each other
- Conflicting decisions





Airport-CDM is...





Airport CDM







- Improve predictability
- Reduce ground movement costs
- Optimise use of infrastructure & reduce congestion
- Reduce ATFM slot wastage
- Flexible pre-departure planning
- Reduce apron & taxiway congestion















Aim of A-CDM





A-CDM is about people working together, not technology!





Collaborative Management of Flight Updates

Variable Taxi
Time
Calculation

Collaborative Pre-Departure Sequencing

CDM in Adverse Conditions

Milestone Approach

Airport CDM Information Sharing

Information Sharing

















Foundation for Airport CDM



The **right** information


To the **right** people

At the **right** time



EUROCONTROL

If a realistic departure time is available...






...the information should be shared!





If an accurate take off time can be estimated...





...the network can benefit from it!

Requirement for Information Sharing



Airport Operator

- Airport slot data
- Stand & gate allocation
- Special events
- Reduction in airport capacity



ATC

- Real-time updates of LDG
- Taxi times & SIDs
- Runway operational capacity
- A-SMGCS data/radar information

Other service providers

- De-icing companies (de-icing times)
- Met office (met info)

Network Operations

- Flight plan data
- ATFM departure slots
- Arrival information (Flight Status/ELDT)


AO/GH

- Flight plans
- Turn-round times
- Priority of flights
- Aircraft registration
- Aircraft movement data

Single Platform





















Requirements A-CDM ISP HMI





Clearly link arrivals & departures

Avoid information overload

Create consistent look and feel

Avoid extra display

Tailor to each partner's needs

Airport database: the best platform to store, process and share Airport CDM information

Exercise



Explain the following term

EOBT

- What are the rules for updating this information?
- What does the NMOC use EOBT for?

Estimated off-block time. The estimated time at which the aircraft will commence movement associated with departure.

Field 13 of the ICAO FPL





Target Off-Block Time (TOBT):

The time that an **Aircraft Or** that an aircraft will be read removed, push back vehicl back immediately upon rec


r Ground Handler estimates closed, boarding bridge nd ready to start up / push earance from the Tower

Target Start Up Approval Time (TSAT):

The time provided by ATC tale the traffic situation that an approval account TOBT, CTOT and / or expect start up / push back
















Generic Processes and Output

- Processes are time information checks related to Milestone events
- Alerts are outcome of the processes, and trigger actions in case inconsistencies are detected
- DPI messages are an outcome of the processes and inform ATFM on predicted take-off time



Airport CDM Generic Procedures and Alerts

• **Example:** Milestone 1 process (ATC FPL activated)







- Example:
- Airport CDM Alert Message SOBT vs. EOBT Discrepancy (CDM01)



FLT ID/CDM02/Timestamp

ATC Flight Plan EOBT is not consistent with Airport Slot SOBT. Immediate update of Airport Slot or ATC Flight Plan EOBT needed.

Note: The Airport CDM process will be suspended until reception of your rectification.





Airport CDM Generic Procedures and Alerts

14. CDM14 Automatic TOBT Generation not Possible N/A

	ID	Code	Descrip	tion	Link with Network Management Operations DPI ERRor Reply Messages*	Applicable on Milestone Process	
	1.	CDM01	No Airport Slot Available, or Slot already correlated		N/A	1	
	0	001400	CODT	CODT diaments	NI/A	4	
Codes				Group Descr	ription		
1-14 Existing alloc					cated codes (basic + 7a, 11a, 12a)		
15-29 Flight phase					(Departure, Arrival, Diversion, etc.)		
30-39 Stand and G				Stand and Ga	ate Management		
40-49 De-icin				De-icing			
50+ Local airpo					codes		
	10.			ejected or Deleted	N/A	9-14	
	11.			Compliant with TOBT/TSAT	N/A	12-13	
	12.	12. CDM12 TSAT not respected by ATC			N/A	13	
	13. CDM13 No ATC		No ATC	Flight Plan Available	Not existing flight	1-14	

4-9

Information Sharing



- Benefits
- Bringing Partners together
- → Promotes trust
- Common situational awareness
- Enables monitoring of operations
- Optimises the use of resources
- Improved predictability
- Improves runway planning
- Maximises operational efficiency







- Key messages
- Information sharing through a transparent platform
- Link arrivals, turn-round and departures
- Monitor progress of a flight using adapted procedures and alerts – linked to Milestones
- Target times:
 - **TOBT** = flight ready to leave the block
 - **TSAT** = flight authorised to move by ATC





Thank you



david.booth@eurocontrol.int