



Doc 9284-AN/905
2009-2010 Edition
ADDENDUM NO. 5
8/12/10

INTERNATIONAL CIVIL AVIATION ORGANIZATION

**TECHNICAL INSTRUCTIONS FOR THE SAFE TRANSPORT
OF DANGEROUS GOODS BY AIR**

2009-2010 EDITION

ADDENDUM NO. 5

The attached addendum should be incorporated into the 2009-2010 Edition of the Technical Instructions (Doc 9284).

Note.— Addendum No. 1 did not affect the English version of the 2009-2010 Edition of the Technical Instructions.

(2 pages)

**TECHNICAL INSTRUCTIONS FOR THE SAFE TRANSPORT
OF DANGEROUS GOODS BY AIR**

The following amendments are approved and published by decision of the Council of ICAO and should be incorporated in the 2009-2010 Edition of the Technical Instructions (Doc 9284):

In Part 4, Chapter 7, page 4-7-19, Packing Instruction 523, paragraph b), *replace* with the following:

- b) when a generator is equipped with an actuating device, it must have at least two positive means of preventing unintentional actuation as follows:
 - 1) mechanically actuated devices:
 - i) two pins, installed so that each is independently capable of preventing the actuator from striking the primer;
 - ii) one pin and one retaining ring, each installed so that each is independently capable of preventing the actuator from striking the primer; or
 - iii) a cover securely installed over the primer and a pin installed so as to prevent the actuator from striking the primer and cover.
 - 2) electrically actuated devices: The electrical leads must be mechanically shorted and the mechanical short must be shielded in metal foil;
 - 3) for PBE:
 - i) a pin so as to prevent the actuator from striking the primer; and
 - ii) placed in protective packaging such as a vacuum-sealed bag;

— END —