



ICAO

International Civil Aviation Organization

**Twenty Fifth Meeting of the Communications/
Navigation and Surveillance Sub-group (CNS SG/25) of
APANPIRG**

Video Tele-Conference, 18 – 22 October 2021

Agenda Item 5: Navigation

5.4 Other navigation related issues

**UPDATE OF FLIGHT INSPECTION GUIDANCE MATERIAL (FIGM)
FOR APAC REGION**

(Presented by China and Hong Kong, China)

SUMMARY

This working paper is jointly prepared by China and Hong Kong, China to propose updates to the Flight Inspection Guidance Material (FIGM).

1. INTRODUCTION

1.1. The first edition of the Flight Inspection Guidance Material (FIGM) was adopted by the 24th Meeting of ICAO APAC CNS Sub-Group on 4 December 2020 to provide additional guidance on planning, execution and delivery of flight inspection services for States/Administrations in the APAC Region.

1.2. The FIGM is subject to regular review and update, in the light of on-going development of flight inspection standards and recommended practices. The Civil Aviation Administration of China (CAAC) Flight Inspection Center (FIC) and Hong Kong, China have volunteered to jointly conduct a review on the contents of the FIGM and propose updates in this paper.

1.3. In the Sixth Meeting of the Surveillance Implementation Coordination Group (SURICG/6), Civil Aviation Authority of Singapore presented an Information Paper (IP/12) (see **Appendix 1**) on “Resolution of Conflicting Text in Doc8071 Vol III Regarding Flight Inspections”, highlighting the conflicting provisions on the frequency of flight inspections stated in the “Manual on Testing of Radio Navigation Aids” (Doc 8071) Vol. III - Testing of Surveillance Radar Systems (Second Edition, 2020).

1.4. Appendix A of Doc 8071 Vol. III stated that flight inspection is required only during commissioning, unless there is specific problem investigation, or deemed necessary by the maintenance personnel. However, Appendix B of Doc 8071 Vol. III implied that there must be routine flight inspections every 120 days. The two provisions within Doc 8071 are conflicting.

Agenda Item 5.4

18-22/10/21

1.5. The SURICG/6 was informed that process had been underway for changes to be made to Appendix B of Doc 8071 Vol. III to remove reference to routine flight inspections, with the proposal to be accepted by the ICAO Surveillance Panel - Aeronautical Surveillance Working Group (SP-ASWG).

1.6. As it is anticipated to take time for the proposed changes to take effect in Doc 8071, it is proposed to provide additional guidance in FIGM on the frequency for flight inspections of surveillance radar systems, by supplementing the frequency for flight inspections of Primary Surveillance Radar and Secondary Surveillance Radar (PSR/SSR) in the document. Some other minor amendments, including the latest guidelines on Flight Inspection periodicity considerations for radio navigation aids and the glossary of FIGM are also proposed to be made. The details of updates are given in this paper for discussion.

2. DISCUSSION

2.1. To align with the amendments to be made to Doc 8071, the following two new paragraphs are proposed to be added in the FIGM to provide additional guidance on the frequency for flight inspections of surveillance radar systems.

3.1.5.3 According to Doc 8071, Civil ATC PSR and SSR facilities, after being commissioned and set into operational service, do not require a periodic flight inspection.

3.1.5.4 Special flight inspections may be conducted as part of a measurement campaign after major equipment modifications, or for specific problem investigation.

2.2. Some other abbreviations in the glossary of FIGM are proposed to be added/amended as follow: -

<u>FAA</u>	<u>Federal Aviation Administration of the United States of America</u>
<u>FL</u>	<u>Flight Level</u>
<u>MRVA</u>	<u>Minimum Radar Vectoring Altitude</u>
<u>PANS-Ops</u>	<u>Procedures for Air Navigation Services – Aircraft Operations</u>

2.3. Attachment C under Section 2 of the FIGM is removed to incorporate the latest guidelines on Flight Inspection periodicity considerations for radio navigation aids using web-link.

2.4 With the aforementioned, a draft conclusion is formulated and proposed for endorsement by the CNS Sub-group as follows:

Draft Conclusion CNS/SG/25/XX - Update of Flight Inspection Guidance Material (FIGM) for APAC Region	
What: That, the Edition 2.0 of the Flight Inspection Guidance Material (FIGM) provided in Appendix 3 to this paper be adopted.	Expected impact: <input type="checkbox"/> Political / Global <input type="checkbox"/> Inter-regional <input type="checkbox"/> Economic <input type="checkbox"/> Environmental <input checked="" type="checkbox"/> Ops/Technical
Why: The FIGM is subject to regular review and update, in the light of on-going development of flight inspection standards and recommended practices.	Follow-up: <input type="checkbox"/> Required from States
When: 22-Oct-21	Status: Draft to be adopted by Subgroup
Who: <input checked="" type="checkbox"/> Sub groups <input checked="" type="checkbox"/> APAC States <input checked="" type="checkbox"/> ICAO APAC RO <input type="checkbox"/> ICAO HQ <input type="checkbox"/> Other:	

3. ACTION BY THE MEETING

3.1 The meeting is invited to:

- a) note the information contained in this paper;
- b) review and comment the proposed updates to the first edition of FIGM in **Appendix 2**;
- c) endorse the Draft Conclusion in paragraph 2.4;
- d) encourage States/Administrations to join the regular review and update of FIGM, in the light of ongoing development of flight inspection standards and recommended practice; and
- e) discuss any relevant matter as appropriate.



ICAO

International Civil Aviation Organization

**Sixth Meeting of the Surveillance Implementation
Coordination Group (SURICG/6)**

Video Teleconference, 24 – 27 August 2021

Agenda Item 11: Next meeting & any other business

**RESOLUTION OF CONFLICTING TEXT IN DOC 8071 VOL III REGARDING
FLIGHT INSPECTIONS**

(Presented by Singapore)

SUMMARY

This working paper highlights conflicting provisions in the Doc 8071 Vol III regarding flight inspections and provides information on the status thus far.

1 Introduction

1.1 It came to the attention of the radar engineers at the Civil Aviation Authority of Singapore that there are conflicting provisions on the frequency of flight inspections in the Vol III of Manual on testing of Radio Navigation Aids (Doc 8071) Testing of Surveillance Radar Systems (Second Edition, 2020).

1.2 A proposal was then submitted to the Surveillance Panel – Aeronautical Surveillance Working Group (SP-ASWG) on 12-16 April 2021 and subsequently to the Aeronautical Surveillance Working Group – Technical Subgroup (ASWG-TSG) on 14-15 June 2021 for considerations.

2 Discussions

2.1 In Para 2.8 – 2.10 of Appendix A of Doc 8071 Vol III – Flight Testing Methods, there is the following text:

2.8 Civil ATC PSR and SSR facilities, after being commissioned and set into operational service, do not require a periodic flight inspection. Instead, the radar performance parameters described in this manual shall be re-assessed at regular intervals by RTQC or by preventive/corrective maintenance. Only in cases of specific problem investigation should it thus be necessary to perform measurement campaigns including flight checks.

2.9 Special inspections are conducted to fulfil a particular need and may be very limited in scope. The limited inspection may not require a formal written plan, but only a short report. Examples of testing events include: development of a starting baseline (as found), identification of problem areas (quantity, if possible), correction of the problem or recommendations for solutions, revision of performance, and generation of a new database.

2.10 If equipment changes/modifications to commissioned facilities change the coverage pattern, document the changes in the inspection report. The new coverage pattern will then

SURICG/6 – IP/12
Agenda Item 3
24-27/08/21

- 2 -

become the basis for comparison during subsequent inspections. Special inspections include the following:

a) engineering support. Engineering support is performed to help engineers and air traffic personnel determine whether the radar meets equipment certification requirements. This data may be used for commissioning purposes, provided that no major equipment modifications are made prior to the commissioning inspection. Requirements for specific checks will be determined by engineering personnel and need not conform to a specific format;

b) antenna change. The checklist, Table A-1, indicates the requirements for installation of a new antenna, a new generation dual beam antenna, or an antenna with a different radiation pattern. A flight inspection is not required following an antenna pedestal or rotary joint replacement if the ground measurements of the reflector position, feedhorn alignment, and antenna tilt of the replacement pedestal are satisfactory;

c) major modifications (other than antenna change). This inspection should be confined to the parameters necessary to confirm facility performance. The radar engineer shall determine the extent of a special inspection during preparation and coordination of the plan. Depending upon the extent of the modification, an inspection using radar evaluation tools and targets of opportunity may satisfy the requirements;

d) near-miss inspections. These inspections are conducted at the request of the air traffic manager of the facility involved, and are used to determine the radar coverage in the area in which the incident occurred. The flight inspection should be conducted as soon as possible following a near-miss, duplicating the manoeuvres, altitude, and direction of the aircraft incident. The flight inspector shall use an aircraft of the same type (or reflective surface) as the smaller aircraft involved. To the extent practicable, operate the radar in the same configuration as it was at the time of the incident. Accomplish flight inspection reports concerning near-miss collisions in the same manner as after-accident reports; and

e) future requirements. New PSR and SSR systems being developed may introduce features not common to existing radar, and may require techniques and procedures substantially different from those described below. Inspection procedures for future systems will be included as they become available.

2.2 In Para 2.4-2.6 of Appendix B of Doc 8071 Vol III – Flight Inspection Procedures For SSR, there is the following text:

2.4 *Commissioning flight inspections are conducted to supply engineering personnel with sufficient data to determine if the SSR meets operational requirements and/or equipment design specifications. These inspections will be extensive enough to provide required data and a basis for comparison of periodic data to detect future deterioration in the performance of the radar.*

2.5 *Routine flight inspections are conducted to determine that the facility performance continues to meet specifications and satisfies operational requirements. The recommended frequency for routine flight inspection is 120-day intervals, plus or minus 30 days, from the initial or annual inspection. In cases where there is a satisfactory record of performance of an equipment, an administration may extend the interval up to as much as 365 days. On the other hand, routine inspections at lesser intervals than 120 days may be needed if there are doubts about equipment performance at a given site.*

2.6 Special flight inspections are conducted after major equipment modifications, for reported or suspected mal functions, after an aircraft accident to determine if facility performance could have been a contributing factor to the accident and for other reasons. Usually a routine flight inspection is sufficient to restore a facility to operation after modification; however, engineering personnel should request checks in excess of routine requirements if additional performance data is required.

2.3 Appendix A of Doc 8071 Vol III stated that flight check is required only during commissioning, unless there is specific problem investigation, or deemed necessary by the maintenance personnel. Appendix B of Doc 8071 Vol III implied that there must be flight inspections every 120 days. There two provisions are in conflict and some States might be forced to adopt the more stringent requirement. It is noted that the proposed frequency of flight inspection is more frequent than the instrumental landing system.

2.4 Following checks among the Surveillance Panel members, their ANSPs perform flight checks based on the frequencies advised in Appendix A and not those in Appendix B.

2.5 It was thus proposed that some changed be made to Appendix B of Doc 8071 Vol III, essentially removing the reference to routine flight checks. The suggested changes are shown in **Appendix A** of this paper. The text will be subjected to acceptance by the SP-ASWG during its meeting on 1-5 Nov 2021.

3 Action by the meeting

3.1 The meeting is invited to note the progress of the works done thus far on the resolution of conflicting text in Doc 8071 Vol III regarding flight inspections.

—

SURICG/6 – IP/12
Agenda Item 3
24-27/08/21

- 4 -

Appendix A

INITIAL PROPOSAL 1

PROPOSED AMENDMENT TO

DOC 8071

MANUAL ON TESTING OF RADIO NAVIGATION AIDS

VOLUME III — TESTING OF SURVEILLANCE RADAR SYSTEMS

NOTES ON THE PRESENTATION OF THE PROPOSED AMENDMENT

1. The text of the amendment is arranged to show deleted text with a line through it and new text highlighted with grey shading, as shown below:
 - a) ~~Text to be deleted is shown with a line through it.~~ text to be deleted
 - b) **New text to be inserted is highlighted with grey shading.** new text to be inserted
 - c) ~~Text to be deleted is shown with a line through it followed~~ **by the replacement text which is highlighted with grey shading.** new text to replace existing text

Appendix B of Doc 8071 Vol III

2.4 Commissioning flight inspections are conducted to supply engineering personnel with sufficient data to determine if the SSR meets operational requirements and/or equipment design specifications. These inspections will be extensive enough to provide required data and a basis for comparison of periodic data to detect future deterioration in the performance of the radar.

~~2.5 Routine flight inspections are conducted to determine that the facility performance continues to meet specifications and satisfies operational requirements. The recommended frequency for routine flight inspection is 120 day intervals, plus or minus 30 days, from the initial or annual inspection. In cases where there is a satisfactory record of performance of an equipment, an administration may extend the interval up to as much as 365 days. On the other hand, routine inspections at lesser intervals than 120 days may be needed if there are doubts about equipment performance at a given site.~~

~~2.6~~ **2.5** Special flight inspections are **may be conducted as part of a measurement campaign** after major equipment modifications, **or for specific problem investigation.** ~~for reported or suspected malfunctions, after an aircraft accident to determine if facility performance could have been a contributing factor to the accident and for other reasons. Usually a routine flight inspection is sufficient to restore a facility to operation after modification; however, engineering personnel should request checks in excess of routine requirements if additional performance data is required.~~

[Subsequent paragraphs to be renumbered.]

**PROPOSED UPDATES TO
FLIGHT INSPECTION GUIDANCE MATERIAL
(FIRST EDITION)**

NOTES ON THE PRESENTATION OF THE PROPOSED AMENDMENT

1. The text of the amendment is arranged to show deleted text with a line through it and new text highlighted with grey shading, as shown below:

- | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| a) Text to be deleted is shown with a line through it. | text to be deleted |
| b) New text to be inserted is highlighted with grey shading. | new text to be inserted |
| c) Text to be deleted is shown with a line through it followed
by the replacement text which is highlighted with grey
shading. | new text to replace
existing text |

Page (vi) of Flight Inspection Guidance Material (First Edition)

ABBREVIATIONS

FAA	Federal Aviation Administration of the United States of America
FL	Flight Level
MRVA	Minimum Radar Vectoring Altitude
PANS-Ops	Procedures for Air Navigation Services – Aircraft Operations

Page 2-8 of Flight Inspection Guidance Material (First Edition)

2.3.4.3 ANSP Related – *The following is recommended to be provided by the ANSP prior to any night flight inspection operation:*

- (a) ATC are able to provide an Instrument Flight Rules (IFR) service;
- (b) ANSP should provide a full radar service within the area of operation;
- (c) Runway edge, centreline, approach lighting and PAPI's shall be serviceable and operating normally;
- (d) Any obstacle lighting shall be operational within the designated area of operation;
- (e) The weather conditions for the night inspection must be Visual Meteorological Conditions (VMC) below the 25/10 NM Minimum Sector Altitude (MSA) or Minimum Radar Vectoring Altitude (MRVA) / Radar Lower Safe Altitude (LSALT); and
- (f) ATC to provide any aerodrome QNH changes expeditiously.

Page 2-12 of Flight Inspection Guidance Material (First Edition)

~~2.5.2 ICAO has published a reference note on the considerations of radio navigation aids flight inspection periodicity during COVID-19 (at Attachment C to this chapter).~~

2.5.2 ICAO has published a reference note on the considerations of radio navigation aids flight inspection practices during the pandemic and restoration to service after temporary removal from service, details please refer to the following link:

<https://www.icao.int/safety/OPS/OPS-Normal/Pages/Flight-inspection-for-radio-aids.aspx>

Page 2-16 to 2-19 of Flight Inspection Guidance Material (First Edition)

~~Attachment C
Flight Inspection Periodicity Considerations for
Radio Navigation Aids during the COVID-19 Pandemic
and Related Recovery Phase~~

~~{Contents}~~

Page 3-5 of Flight Inspection Guidance Material (First Edition)

3.1.5.3 According to Doc 8071, Civil ATC PSR and SSR facilities, after being commissioned and set into operational service, do not require a periodic flight inspection.

3.1.5.4 Special flight inspections may be conducted as part of a measurement campaign after major equipment modifications, or for specific problem investigation.

App-1 Appendix 1

1. USEFUL REFERENCE

- Reference note from ICAO on the considerations of radio navigation aids flight inspection periodicity ~~during COVID-19~~
<https://www.icao.int/safety/COVID-19OPS/Pages/ANS.aspx>
<https://www.icao.int/safety/OPS/OPS-Normal/Pages/Flight-Inspection-for-radio-aids.aspx>



Asia and Pacific Office

ASIA PACIFIC FLIGHT INSPECTION GUIDANCE MATERIAL

~~First~~ Second Edition

PREFACE

This publication was prepared in response to a recommendation from the “Seminar on Flight Inspection and Procedure Validation (FIPV)” held in the ICAO Asia and Pacific (APAC) Regional Office, Bangkok, Thailand from 24 to 27 September 2019 with content contribution from volunteer States / Administrations and industry partners. It is decided to complement existing Standards and Recommended Practices (SARPs) to provide guidance on flight inspection and to serve as a reference upon which States / Administrations can develop their own specific practices and procedures.

The guidance material is developed with the experiences and knowledge among APAC States / Administrations and industry partners and includes recommendations of key activities and milestones in planning, execution, and delivery of a flight inspection. Useful materials, including sample flight inspection reports are also included for reference. This guidance material can hopefully facilitate and be useful to States / Administrations, especially for those without a national Flight Inspection Service Provider (FISP) and with difficulties when conducting flight inspection.

This guidance material is not intended to and shall not replace the relevant flight inspection requirements stipulated in Annex 10 and Doc 8071. In the event of any inconsistency or conflict between this document and Annex 10 and Doc 8071, Annex 10 and Doc 8071 shall take precedence.

The support from ICAO APAC Office and contributions from the following volunteer State/Administration and industry partner (in alphabetical order) in preparing the guidance material are acknowledged and highly appreciated: -

- AeroPearl, Australia
- Airways, New Zealand
- Civil Aviation Authority of Singapore
- FCS Flight Calibration Services GmbH, Germany
- Flight Inspection Center, Civil Aviation Administration of China, China
- Hong Kong Civil Aviation Department, China

TABLE OF CONTENTS

Page

Chapter 1	Introduction	1-1
1.1	Objectives	1-1
1.2	Scope	1-1
Chapter 2	Planning for Flight Inspection	2-1
2.1	General	2-1
2.2	Flight Inspection Coordination and Preparation	2-4
2.3	Flight Inspection at Night	2-7
2.4	Emergency Flight Inspection Arrangement	2-9
2.5	Considerations on Flight Inspection Periodicity during Pandemic	2-9
Attachment A	Example Flight Inspection Programme	2-13
Attachment B	Example Flight Inspection Profiles	2-14
Attachment C	Flight Inspection Periodicity Considerations for Radio Navigation Aids during the COVID-19 Pandemic and Related Recovery Phase	2-16
Chapter 3	Conducting Flight Inspection	3-1
3.1	Typical Flight Inspection Procedures	3-1
3.2	Other Types of Flight Inspection	3-5
3.3	Typical Flight Inspection System Performance Specifications and Associated Test Accuracy Ratios (TAR)	3-5
Chapter 4	Reporting of Flight Inspection Results	1
4.1	Typical Flight Inspection Reports	1
4.2	Typical Flight Inspection Records	1
Attachment A	Sample Flight Inspection Reports	4-2
Attachment B	Sample Flight Inspection Records	4-9
Appendix 1	Useful Reference	1
Appendix 2	Use of Emerging Technology to Supplement Flight Inspection	1

GLOSSARY

SYMBOLS AND UNITS

DDM	Difference in the depth of modulation
Ft	Feet
Kg	Kilogram
Km/h	Kilometers per hour
Kw	Kilowatt
M	Meter
NM	Nautical mile
QNH	Atmospheric pressure adjusted to mean sea level

ABBREVIATIONS

ADS-B	Automatic Dependent Surveillance – Broadcast
AI	Artificial Intelligence
AIP	Aeronautical Information Publication
ANSP	Air Navigation Service Provider
AOC	Air Operator's Certificate
APAC	Asia and Pacific
ATC	Air Traffic Control
ATM	Air Traffic Management
ATS	Air Traffic Service
CCC	Crew Coordination Concept
CNS	Communication, Navigation and Surveillance
COVID-19	Coronavirus Disease 2019
CRM	Crew Resource Management
DME	Distance Measuring Equipment
DVOR	Doppler VHF Omni-Directional Range
EASA	European Union Aviation Safety Agency
EFB	Electronic Flight Bag
FAA	Federal Aviation Administration of the United States of America
FIPV	Flight Inspection and Procedure Validation
FISP	Flight Inspection Service Provider
FL	Flight Level
FTL	Flight Time Limitation
GBAS	Ground Based Augmentation System
GLS	GNSS Landing System
GNSS	Global Navigation Satellite System
GP	Glidepath
ICAO	The International Civil Aviation Organization
ICASC	The International Committee for Airspace Standards and Calibration
IFR	Instrument Flight Rules
ILS	Instrument Landing System
LOC	Localizer
LSALT	Lowest Safe Altitude
MSA	Minimum Sector Altitude
MRVA	Minimum Radar Vectoring Altitude
NAVAID	Navigation Aid
NDB	Non Directional Beacon
NOTAM-	Notice to Airmen
PANS-Ops	Procedures for Air Navigation Services – Aircraft Operations
PAPI	Precision Approach Path Indicator
PSR	Primary Surveillance Radar
RNAV	Area Navigation
RNP	Required Navigation Performance
RPAS	Remotely Piloted Aircraft Systems
SARPs	Standards And Recommended Practices
SMS	Safety Management System
SOPs	Standard Operating Procedures
SORA	Specific Operations Risk Assessment

SSR	Secondary Surveillance Radar
TAR	Test Accuracy Ratios
TERPs	Terminal Instrument Procedures
TRM	Team Resource Management
TSO	Technical Standard Orders
UAV	Unmanned Aerial Vehicle
VASI	Visual Approach Slope Indicator
VHF	Very High Frequency
VMC	Visual Meteorological Conditions

Chapter 1

INTRODUCTION

This material was developed in response to the recommendation from the Seminar on Flight Inspection and Procedure Validation (FIPV) held in the ICAO APAC Regional Office, Bangkok, Thailand from 24 to 27 September 2019, considering the typical need of States / Administrations without a national FIS provider and some recommended measures necessary for conducting flight inspection at night.

1.1 OBJECTIVE

1.1.1 In accordance with the ICAO Annex 10 Volume I and Document 8071 requirements, flight inspection has to be conducted periodically to ensure accuracy, reliability and integrity of the signals-in-space from the air navigation facilities, and that the radio navigation systems meet the SARPs in Annex 10.

1.1.2 While flight inspection could also be conducted for surveillance facilities and/or other purposes such as flight procedure validation, VHF coverage checking, etc., this guidance material focuses on flight inspection for air navigation and surveillance facilities and is a sharing and representation of common practices existing in a number of States with considerable experiences in flight inspection.

1.1.3 This guidance material introduces and describes different stages in flight inspection for air navigation facilities, including planning, conducting and accepting the report that all tolerances are met. It is not intended to recommend specific FISP(s) or equipment to be used, but rather to provide general details and guidelines in the arrangement of flight inspection for States' own consideration.

1.2 SCOPE

1.2.1 This guidance material describes general reference in conducting flight inspection, including resources planning, roles and responsibilities of involving parties and identification of stakeholders. It also provides guideline in communication with stakeholders and criteria on planning and scheduling flight inspection.

1.2.2 This document introduces example flight inspection procedures for Instrument Landing System (ILS) including visual aids, Doppler Very High Frequency Omni-Directional Range (DVOR), Distance Measuring Equipment (DME), Primary Surveillance Radar and Secondary Surveillance Radar (PSR / SSR) and discusses about the arrangement for flight inspection at night and also emergency flight inspections.

1.2.3 Reference is also given on the example flight inspection system performance specifications and associated Test Accuracy Ratios (TAR) and the workflow on reporting of flight inspection results. Sample flight inspection records and reports are also shared in this document for States to make reference with.

Chapter 2

PLANNING FOR FLIGHT INSPECTION

2.1 GENERAL

2.1.1 General Setup and Resources Planning

- 2.1.1.1 General setup – there are 2 typical scenarios of flight inspection arrangements:
- (a) State has its own flight inspection unit; or
 - (b) Engagement of external FISP.
- 2.1.1.2 State's own flight inspection unit will be:
- (a) Able to activate within a short period of time during emergency (high flexibility);
 - (b) Particularly useful when State has large number of facilities / aerodromes to be flight inspected; and
 - (c) Likely regulated by State.
- 2.1.1.3 Engagement of external FISP will be:
- (a) More cost effective when State has small number of facilities to be flight inspected;
 - (b) More feasible when the State may not have the necessary expertise;
 - (c) More flexible to change FISP to meet the required service performance; and
 - (d) Little or no control when an emergency flight inspection is required.
- 2.1.1.4 General planning before flight inspection typically includes the following:
- (a) Determine types of flight inspection required (commissioning or routine) and periodicity for routine ones;
 - (b) Identify facilities to be flight inspected;
 - (c) Determine type of aircraft used for flight inspection, for example using jet aircraft for high level (i.e. FL350 and above) radar coverage check;
 - (d) Check with apron operations on where the inspection aircraft can park and identify any traffic/timing restrictions for its taking off and landing;
 - (e) Plan the time of flight inspection, after consulting operations;
 - (f) Develop draft flight inspection schedule and flight inspection profiles as well as proposed date for brief and debrief;
 - (g) Notify parties involved/affected by draft flight inspection schedule and flight inspection profiles. Parties involved/affected could be ATC, runway maintenance team, military, ground handlers, Nav aids & Surveillance facilities managers, Nav aids & Surveillance maintenance staff, airfield lighting / Precision Approach Path Indicator (PAPI) maintenance team;
 - (h) Conduct flight inspection briefing with involved / affected parties;

- (i) Issue Notices to Airmen (NOTAMs) for any change / cancellation of runway maintenance works; and
- (j) Develop list of contact details of parties involved in the flight inspection.

2.1.2 Roles and Responsibilities of the Flight Inspection Service Provider (FISP) Including Crew Resources Management

FISP is the main party to provide safe and reliable flight inspection services. Selection of an appropriate FISP is a key successful factor for flight inspection.

2.1.2.1 Roles

- (a) Assist Air Navigation Service Provider (ANSP) in planning, scheduling and conducting the flight inspection;
- (b) Be familiar with the airspace / airport to conduct safe and efficient flight inspection with minimum impact to normal traffic; and
- (c) Provide routine, commissioning or ad-hoc (special or urgent) flight inspection services.

2.1.2.2 Responsibilities

- (a) Assist ANSP to ensure no equipment (e.g. navigation aids) would expire the validity period as recommended by ICAO or State's regulatory requirement, or any validity period as confirmed by the ANSP, with proper planning and scheduling of flight inspection tasks;
- (b) Survey or assist to survey the reference point(s) for Global Navigation Satellite System (GNSS) for precision flight inspection on ILS;
- (c) Obtain all the necessary permits to fly over areas for its flight inspection;
- (d) Closely coordinate with ATC and ground technical personnel to prepare and conduct flight inspection including the provision of flight profiles for ATC assessment;
- (e) Implement Safety Management System (SMS) as appropriate to deliver safe flight inspection services;
- (f) Keep good archived records of flight inspection results of the equipment / system being inspected and provide advice if there was any anomaly trend or result observed;
- (g) Feedback to the ANSP on overall flight inspection arrangement, discuss and assist to resolve problems encountered; and
- (h) Desirable to have Crew Resource Management (CRM) to clearly define the roles and responsibilities of each crew member and to establish close collaboration among the crew members.

2.1.2.3 Crew Resource Management (CRM) System

Crew Resource Management (CRM) and Crew Coordination Concept (CCC) define how crews are to work together and the roles and responsibilities of each crew member. It clearly describes the communications involved in executing tasks and should be reinforced by Standard Operating Procedures (SOPs) and checklists. The CRM system, however, does not only define the cooperation among cockpit members, but also should encompass procedures and communication between cockpit and cabin, and it should define the interface between the flight crew and the rest of the organisation, like tasking / scheduling, management, maintenance, etc. This holistic approach in CRM is of great importance to create a working environment that takes into account all requirements to accomplish the organization's mission profile safely and reliably. It effectively translates into a Team Resource Management (TRM).

2.1.3 Roles and Responsibilities of the Flight Inspector

A flight inspector is the person who performs checking on equipment / system status. He / she must be proficient and have a good understanding on the characteristics of various equipment / systems to be flight inspected as well as familiarise himself / herself with relevant procedures to perform flight inspection on that equipment / system.

2.1.3.1 Roles

- (a) Contribute in early planning of the flight inspection;
- (b) Coordinator between ANSP and the flight inspection service provider;
- (c) Perform equipment checking in flight inspection and alert ANSP in real time of any out-of-tolerance conditions or anomaly observed during the flight inspection;
- (d) Assist ANSP to identify and analyse any anomaly / adverse trends observed; and
- (e) Prepare flight inspection records and reports.

2.1.3.2 Responsibilities

- (a) Provide advice to ANSP in planning the flight inspection tasks;
- (b) Assist in preparing flight inspection procedures for checking a specific equipment / system;
- (c) Coordinate with the rest of flight inspection team (e.g. pilots) for ad-hoc and flexible arrangement of flight inspection procedures (e.g. re-check on a specific run);
- (d) Observe the measured results of flight inspection and checks against the relevant tolerance limits;
- (e) Keep records of the measurement results and notifies ANSP for any trend/anomaly observed;
- (f) Assist ANSP from the flight inspection perspective for the rectification on any anomaly observed; and
- (g) Coordinate any real time changes to the flight inspection schedule due to unforeseen circumstances such as inclement weather, aircraft or aircrew problem.

2.1.4 Roles and Responsibilities of ANSP

The ANSP is ultimately responsible for management of the flight inspection. It is therefore vital that ANSP takes an active role throughout the flight inspection.

2.1.4.1 Roles

- (a) Types of ANSP Personnel
 - (i) Ground technical personnel maintaining navigational and landing aids, surveillance radars, airfield lighting and PAPIs, etc.; and
 - (ii) Air Traffic Controllers – En-route, Approach and Tower.

2.1.4.2 Responsibilities

- (a) Ensure that all systems and facilities to be flight inspected are operational and in a condition suitable for flight inspection on the scheduled dates;
- (b) Ensure all systems and facilities are regularly flight inspected, complying with the State's regulatory requirement on the periodicity of flight inspection;

- (c) Provide an annual draft schedule of systems and facilities to be flight inspected to the flight inspection service provider to facilitate early planning;
- (d) Assist in obtaining security clearance for flight inspection crew to access aircraft;
- (e) Provide necessary geographical information of systems & facilities under flight inspection, for example latitude and longitude co-ordinates of all navigation facilities;
- (f) Provide authorization for flight inspection aircraft to fly below established minimum altitudes, together with all other necessary air traffic authorizations to accomplish the flight inspection;
- (g) Provide qualified staff to be present during flight inspection;
- (h) Coordinate flight inspection briefing and debriefing;
- (i) Review flight inspection profiles with ATC and arrange discussion with FISP for any clarification, if required;
- (j) Ensure FISP obtain necessary permits to fly over areas for the planned flight inspection;
- (k) Issue necessary NOTAMs for flight inspection;
- (l) Review flight inspection reports;
- (m) Publish addition or / and amendments to AIP regarding systems / facilities after flight inspection;
- (n) Make arrangement for flight inspection crew to call ATC before the start of each sortie for co-ordination purposes;
- (o) ATC to facilitate flight inspection and accord it some priority, whenever possible; and
- (p) ATC to be conversant with flight inspection profiles.

2.2 FLIGHT INSPECTION COORDINATION AND PREPARATION

2.2.1 Identification of Stakeholders

The smooth conduct of flight inspection requires concerted efforts from all key stakeholders. Subject to the organization structure in the States, an example list of stakeholders related to flight inspection is provided below for reference:

2.2.1.1 Flight Inspection Service Provider (FISP)

- (a) FISP plays a vital role in flight inspection and is expected to be conversant with the relevant ICAO and local standards and requirements for flight inspection of various CNS equipment. FISP is also expected to be familiar with the flight profiles to be conducted and local airport / airspace environment in order to perform flight inspection in an efficient and effective manner. FISP should also be familiar with details of permits / approvals required for flying in airspace to ensure a successful and effective flight inspection.
- (b) The flight inspection team deployed by the FISP normally consists of three types of staff, namely pilots, flight inspectors and aircraft engineers.
 - (i) Pilots – mainly communicate with air traffic controllers to perform flight inspection profiles
 - (ii) Flight Inspector – mainly coordinate with ground maintenance personnel or systems supplier engineer to take, report and calibrate measurement reading to ensure the equipment under inspection performs within the relevant tolerance limits.

- (iii) Aircraft Engineer – support staff to deal with daily maintenance and problems encountered on the flight inspection aircraft, which would normally have been deployed at a far distance from the FISP's main base.

2.2.1.2 ANSP - Air Traffic Controller

- (a) States may consider, as far as practicable, to assign dedicated air traffic controller(s) in handling the flight inspection aircraft, in which the flight path might cross multiple sectors and affect normal traffic patterns. Experienced air traffic controllers could efficiently reduce the lead time to conduct flight inspection, while keeping the impact to normal traffic to a minimum.
- (b) Subject to different airport and airspace, temporary holding of ground and / or air traffic might be required to allow the flight inspection aircraft to conduct dedicated profiles unaffected.
- (c) Air traffic controller handling flight inspection aircraft has to work closely with the flight inspection pilot and keep a very close eye on the aircraft position to keep it clear from normal traffic.

2.2.1.3 Aerodrome Operator

- (a) Local aerodrome operator plays an important role in providing necessary logistics support to the flight inspection team, for example in the facilitation of access to airport restricted area, facilitate the conduct of flight profiles on ground or assist in handling the shipment of spare parts to address technical faults encountered by the flight inspection aircraft.

2.2.1.4 ANSP - Ground Maintenance Personnel

- (a) The ground maintenance personnel are responsible for equipment maintenance and adjustment during the flight inspection. They have to work closely with the flight inspector to ensure the measured reading is within tolerance limit and ensure the equipment is safe for operational use. Prior to the flight inspection, the ground maintenance personnel shall also ensure the equipment is operational and in a condition suitable for flight inspection.

2.2.1.5 Other Supporting Personnel

- (a) To facilitate daily flight inspection mission, there might be logistics support required for the flight and ground crews of the flight inspection team to travel between airport and their accommodation place. Immigration, Customs and Exercise clearance support might also be required to facilitate smooth operation of flight inspection activities.

2.2.1.6 Military, if applicable

- (a) The military shall be informed of the civilian flight inspection schedule to ensure military flights and civilian flight inspection aircraft routes are de-conflicted. The civilian flight inspection aircraft should take note of the military no fly zones.

2.2.2 Communication with Stakeholders

2.2.2.1 A thorough understanding of the details of flight inspection arrangements is crucial to the successful completion of a flight inspection. All stakeholders should know their roles and duties to render the best support to the flight inspection activities.

2.2.2.2 To facilitate clear communication among stakeholders, ANSP could consider preparing a comprehensive but concise daily programme for sharing among all stakeholders. The daily programme would typically include information on equipment / facility to be inspected, estimated start and end time, parties involved and their roles, useful contacts, etc. (see sample at Attachment A to this chapter).

2.2.2.3 In addition, the ANSP could also consider preparing a detailed flight inspection check sheet for each equipment / facility to document the planned flight inspection profiles to be conducted (preferably with diagrams for easy visualisation) and estimated duration for each run. This check sheet could greatly facilitate air traffic controllers and airport stakeholders to assess any potential impact to airport / airspace operations and to aid

communication during the flight inspection (see sample at Attachment B to this chapter). Appropriate NOTAM should also be issued to ensure airlines and pilots are kept informed of the flight inspection schedule and time.

2.2.2.4 Before the commencement of each round of flight inspection, an in-briefing involving all key stakeholders is recommended to ensure all are familiar with their roles and responsibilities in supporting the daily flight inspection as well as any issues requiring special attention. This also allows all stakeholders to exchange comments about the daily arrangement, for instance the flight profiles sequence, and helps to spot early issues that would potentially hinder normal ATC operations and flight inspection.

2.2.2.5 Contingency plan, including backup flight inspection date(s) due to unexpected ad-hoc event such as inclement weather or technical fault, could also be discussed with key stakeholders during the in-briefing.

2.2.2.6 During the flight inspection, it is essential that the ground maintenance personnel maintains direct communication with the on-board flight inspector so that any required adjustment of ground facilities or any recheck can be done expeditiously.

2.2.2.7 During the flight inspection period, daily de-briefing among flight inspection crews, ANSP, ATC and ground maintenance personnel would allow quick feedback on any issues encountered during the flight inspection so as to make timely fine-tuning when necessary for the subsequent flight inspection. This allows individual stakeholder to make adjustment / enhancement arrangement promptly such as issuance / cancellation of NOTAM, co-ordination / cancellation of runway closures, etc.

2.2.2.8 After the completion of each round of flight inspection, a de-briefing involving all stakeholders would help all to strive for continuous improvements on overall flight inspection arrangement, with parties sharing their views and suggestions as well as to share results and resulting actions of the flight inspection.

2.2.3 Consideration in the Planning and Scheduling of Flight Inspection

Flight inspection, depending on the exact flight profiles to be conducted, often causes some degrees of disruption to normal airport and airspace operations, especially at busy international airports during peak traffic hours. When planning and scheduling flight inspections, a number of key factors have to be considered so as to minimise potential interruptions to normal operations, for example:-

2.2.3.1 Traffic Volume

- (a) During day time when normal traffic is usually at its peak, the coordination of flight inspection by air traffic controllers will be complex and with great challenges which often results in undesirable disruption to normal air traffic. Hence, for busy airports, there is a trend to advance the flight inspection time to dawn or even earlier so as to avoid the busy day time traffic.
- (b) Some flight inspection profiles may require day-light conditions to perform. When scheduling the flight inspection, one possible way to take advantage of less busy early hours would be to perform those flight profiles that do not require day-light condition first, followed by those requiring day-light conditions. As the time of flight inspection is dependent on time of peak traffic volume, close co-ordination and early inputs from ATC and slot planner from the airport operator in the planning would be beneficial.

2.2.3.2 Holiday and Peak Travel Season

- (a) Long holidays and travel peak seasons would significantly increase the air traffic volume. In some ANSPs, there may also be a period of time in which equipment configuration or change is not allowed as this supports the heavy traffic in long holiday and peak season. Therefore, when planning and scheduling flight inspection programs, such long holiday and travelling peak seasons should be avoided as far as practicable.

2.2.3.3 Seasonal Weather Condition

- (a) In some States, there might be seasonal strong winds, typhoons or severe weather conditions in some parts of the year. Heavy rainfall, lightning and other severe weather conditions may impact or delay flight inspection activities. As such, the flight inspection program should be scheduled to avoid bad weather seasons as far as practicable.

2.2.3.4 Major Military Flying Exercises

- (a) Planning of flight inspection should avoid disruption with a period of major military flying exercises. This is because during the latter, many forbidden flying areas / zones may be activated and such activations could affect the normal flight inspection.

2.2.3.5 Types of Flight Inspections

- (a) Depending on type of flight inspections, some of them, such as some ILS commissioning checks, procedure validation, etc., may have to be carried out in the daytime with suitable visual conditions.

2.2.3.6 Contingency Arrangement

- (a) Back-up/contingency dates should be planned to cater for any unplanned cancellation or effect on flight inspection activities.
- (b) The back-up/contingency flight inspection date(s) could be inserted as buffer date(s) in between the planned flight inspection activities, or after all the planned flight inspection activities as an extended arrangement.

2.3 FLIGHT INSPECTION AT NIGHT

Flight inspection operations at night are becoming more popular and may inevitably be required at large and high traffic density airports so as to minimize potential impact to the normal air traffic flow. The possibility of reduced traffic flow densities at night may allow the necessary inspection profiles to be flown with minimal disruption to ATC. However, the potential risks for the FISP crews for performing such tasks at night need to be properly managed.

To reduce the risk in flight inspection at night, FISP crews should be familiar with the airspace and airport environment including the height of terrain and structures along and close to the flight inspection path. Air traffic controllers have to pay special attention to the altitude and flight path of the flight inspection aircraft to avoid any deviation from the planned safe flight path.

Night operations should be considered as any flight inspection being performed 30 minutes after sunset until 30 minutes before sunrise.

2.3.1 Flight Inspection Aircraft Type

2.3.1.1 The aircraft should be a multi-engine type capable of safe flight within the intended operational envelope with one engine inoperative, fully equipped and instrumented for night and instrument flight operations.

2.3.2 Crew Resource Management (CRM)

2.3.2.1 Flight inspection operations at night present additional risks that must be identified, assessed with necessary mitigations and documented. Night flying operations should only be conducted by experienced pilots that are current and proficient at night flying and who understand well the risks associated with night-time flight inspection.

2.3.2.2 A dual pilot operation should be considered for a normal night flight inspection operation to mitigate against the higher risks involved for night operations.

2.3.3 Night Duty Periods

2.3.3.1 FISPs operate under their own Air Operator's Certificate (AOC) and Flight Time Limitation (FTL) which would normally include duty periods for their specific night operations. Consideration should be given to the preceding duty period prior to any planned night duty to ensure the crew, including the flight inspector, have enough rest periods before and after the night duties.

2.3.3.2 Limitations should be provided for night duties worked in immediate succession, for example two consecutive nights, with a maximum duty period of 11 hours each.

2.3.3.3 Upon the conduction of a single night duty, or two consecutive night duties, there should be a minimum interval of rest time for the FISP crews before the commencement of the next duty time.

2.3.4 Operational Requirements

2.3.4.1 Where a requirement exists for flight inspection of ILS or other NAVAID installations at night, the following operational requirements should be met.

2.3.4.2 Aircraft Related - In addition to the normal equipment required for a night operation, the following equipment should be functioning normally:

- (a) Both aircraft altimeters;
- (b) Radar altitude indicators;
- (c) Auto-Pilot;
- (d) All flight instrument displays;
- (e) Up-to-date database for flight inspection equipment map display (If applicable);
- (f) Electronic Flight Bag (EFB), if applicable; and
- (g) Approach plate holders with adequate lighting.

2.3.4.3 ANSP Related – The following is recommended to be provided by the ANSP prior to any night flight inspection operation:

- (a) ATC are able to provide an Instrument Flight Rules (IFR) service;
- (b) ANSP should provide a full radar service within the area of operation;
- (c) Runway edge, centreline, approach lighting and PAPI's shall be serviceable and operating normally;
- (d) Any obstacle lighting shall be operational within the designated area of operation;
- (e) The weather conditions for the night inspection must be Visual Meteorological Conditions (VMC) below the 25/10 NM Minimum Sector Altitude (MSA) or Minimum Radar Vectoring Altitude (MRVA) / Radar Lower Safe Altitude (LSALT); and
- (f) ATC to provide any aerodrome QNH changes expeditiously.

2.3.4.4 Pilot Related - Prior to the commencement of any night inspection operation, a skyline plot of the obstructions in the approach path must be obtained from the aerodrome operating authority. The pilot should compare the intended inspection runs and adjustments made to the minimum operating altitude as necessary.

2.3.4.5 Where flight crews have not conducted a daylight operation into an aerodrome, then prior to conducting a night inspection task, the crew should first fly the approach in daylight conditions to assess the obstacle clearance within the approach area.

2.3.4.6 Areas surrounding the inspection runs shall be predominantly level, clear of terrain and obstacles.

2.3.4.7 For operations in certain States it may be compulsory for the crew to provide an alternate Aerodrome for recovery, these requirements must be determined prior to commencement of night operations. In addition, holding and alternate requirements always need to be borne in mind.

2.3.4.8 To raise the flight crew situational awareness and to reduce fatigue, the autopilot should be used whenever possible.

2.3.4.9 Flights should be conducted under the IFR.

2.3.4.10 Flight Inspection Profiles - Flight inspection at night should be conducted using the following minimum altitudes:

- (a) Level runs, Orbits and Part Orbits should not be conducted below the sector 25NM/10NM MSA or radar LSALT.
- (b) Not below SECTOR 25/10 NM MSA or radar LSALT until established on a flight inspection approach run, when established within full-scale deflection of the localiser descent may occur.

2.3.4.11 Localiser (LOC) offset approaches that involve flights more than half scale (5 Dots) indications should be flown during daylight.

2.3.4.12 Where a LOC part orbit altitude needs to be increased for a night operation, a range change may be required to ensure that the localiser coverage area correlates with the published GlidePath (GP) angle.

2.3.4.13 Cat III ILS approaches that include a fly through at 50ft along the runway to ILS Point 'E' should only be flown at night providing the following are met:

- (a) Runway centreline lights are serviceable; and
- (b) Pilots have conducted the relevant simulator training for such an operation.

An alternate method would be for the aircraft to perform a run along the runway centreline prior or post the inspection.

2.3.4.14 GP approach profiles that involve flight with more than half scale "FLY UP" indications should be flown during daylight e.g. GP lower edge (5 dots Fly Up) runs.

2.3.4.15 GP level runs need to encompass coverage and clearance at a minimum angle of 0.45θ , however, increasing the height to be at MSA for this measurement will inevitably mean an increase in the start range to achieve this, with the possibility that the GP coverage tolerance may not be met beyond 10NM. As an alternate solution, the GP level run profile could be flown with the addition of the night profile run during daylight and the measurements used as a reference transfer standard between the two profiles.

2.4 EMERGENCY FLIGHT INSPECTION ARRANGEMENT

2.4.1 Types of Flight Inspection

2.4.1.1 The various types and priorities of flight inspection are published within ICAO DOC 8071, Chapter 1 (Para.1.5). The following paragraphs discuss the requirements surrounding special inspections.

2.4.2 Priorities of Flight Inspection

2.4.2.1 If there are multiple flight inspection requests, the use of inspection priorities will determine the tasks to be supported first and make the most effective use of the resources in FISP. The following is an order of priorities that should be considered:

Priority	Type	Description
1	Accident/Incident	Accident or incident investigation requiring immediate response.
2	Restoration	Restore a commissioned facility after an unscheduled outage.
3	Periodic	A regularly scheduled inspection of a commissioned facility.
4	Commissioning	A comprehensive inspection of a newly installed facility.
5	Site Evaluation	An inspection to determine the environmental effects on the performance of a planned navigational aid.

Table 2-1. Flight Inspection Priority

2.4.3 Post-Accident Investigation

2.4.3.1 A flight inspection may be requested following an accident or incident by the investigating authority to verify the NAVAID system performance is satisfactory and able to continue to support the published instrument approach procedures and ANSP operations.

2.4.3.2 For a FISP, this type of inspection should be accorded highest priority and an appropriate response time should be contractually agreed between the ANSP and the service provider.

2.4.3.3 Pre-Flight Requirements – The flight inspector will be required to obtain the following information:

- (a) Equipment configuration at the time of the accident i.e. transmitter in operation;
- (b) Instrument approach procedures used; and
- (c) Any additional information required to support the investigation.

2.4.3.4 The flight inspector will need to coordinate the system configuration with the maintenance personnel and perform as a minimum, an inspection of the facility which may include the instrument procedure used if applicable. It is important to note that no equipment adjustments should be made during this inspection and if required, should be performed in a separate special inspection to facilitate investigation.

2.4.3.5 In the event of an accident or incident, ANSP should do all that is reasonably practicable to ascertain that a NAVAID is operating correctly. For this reason, ANSP should have equipment suitable for making field measurements available.

2.4.4 Post-Incident Investigation

2.4.4.1 Where a runway excursion by an aircraft has occurred and damage has been sustained to a NAVAID, the maintenance authority will determine the repairs required to the facility and whether a ground or flight inspection is required to return the facility back into service. However, the following considerations should be given when determining the need for a flight inspection:

- (a) Antenna array replacements that will affect the radiated pattern;
- (b) Cable replacements that affect transmission line lengths;
- (c) Replacement or re-positioning of an ILS near field monitor if the system does not contain integral course monitoring;
- (d) Major repair work to the LOC antenna distribution unit or when the center line phasor has been adjusted;
- (e) Adjustment or corrective maintenance on phasing or width controls that results in figures outside the monitor site acceptance figures;
- (f) Any work performed on the GP antenna distribution unit;
- (g) Adjusts to GP integral monitor probes, cables or monitor combiner unit; or
- (h) Damage to ILS critical areas ground in the beam forming areas that need re-grading.

2.4.4.2 In the event of an accident or incident, ANSP should do all that is reasonably practicable to ascertain that the facility is operating correctly. For this reason, all aerodromes should have equipment suitable for making field measurements available.

2.4.5 Flight Inspection Service Providers (FISP)

2.4.5.1 Information regarding FISP may be obtained from the appropriate ICAO Regional Office or online from the International Committee for Airspace Standards and Calibration (ICASC) at <http://www.icasc.co>¹

¹ ICAO DOC 8071 Fifth Edition, 2018

2.4.6 Navigational Aid Performance Reports

2.4.6.1 The reporting of aviation safety occurrences is vital to the prevention of aircraft accidents and contributes to the understanding of where safety risks lie within the aviation system. This information provides an understanding of the safety related issues thus allowing these to be addressed and relevant measures adopted. Safety occurrence reporting by aviation professionals contributes to the prevention of accidents and fundamentally promotes the safety of aviation activities within the organisations that employs them or uses their services.

2.4.6.2 Persons involved in aviation activities should be encouraged to report any safety issue they encountered. State regulations should differentiate between the cases which would require mandatory reporting and those that may be reported after judging it relevant.

2.4.6.3 The obligation of these reporting occurrences would be included within the normal operation of an organisation's SMS. ANSP or airline operator should, through a mandatory reporting system, inform the relevant authority of a particular occurrence and with defined categories that represent a significant risk to aviation safety.

2.4.6.4 Safety management systems are reliant on the collection and analysis of safety related information. Therefore, anything that is perceived by the individuals as having the potential to impact safety should be reported within reasonable time, for example, 72 hours to raise awareness of the occurrence.

2.4.6.5 Organisations SMS may define the format of the occurrence reports to be used by relevant aviation professional. It should include areas to report NAVAID performance or RNAV procedure where relevant. In general, reporting forms need to be user friendly and will not discourage potential reporters to report the occurrences. The aim should be to facilitate the collection of occurrence information as much as practicable from the front-line individuals and allow the appropriate authorities to understand and address the issues from the information provided.

2.4.6.6 The following reporting information requirements should be considered as a minimum, but not limited to, in the determination of NAVAID's performance from both an ATC and Pilots perspective.

- (a) Date/Time UTC
- (b) Aircraft Call Sign
- (c) Airline Operator
- (d) Pilot Name
- (e) SSR Code
- (f) Aircraft Type
- (g) Aircraft Flight Phase (Climb, Descent, Level, Approach), IFR/VFR, Radar Vectored, Navigational Aid in use (ILS/VOR/DME/NDB/RNAV)
- (h) Description of Occurrence

2.4.6.7 ANSP's and Airline Operators are likely to have their own organisations occurrence report forms to cover the mandated reporting requirements within their SMS. These may not contain the aforementioned information relevant for a pilot reporting an unreliable NAVAID performance. Therefore, additional information may be required for investigation purposes depending on the seriousness of the occurrence. Consultation with the ground technicians will greatly assist an immediate investigation on a system status and possible actions required.

[2.4.6.8](#) For precision approach landing aid systems such as an ILS/DME or GNSS Landing System (GLS), once an occurrence report related to the system is received from a pilot, an ANSP would have to follow up by investigation and discussion with ground technicians and may require the issue of a NOTAM on that facility once it is identified to be faulty and requires maintenance. The ANSP has to ensure a continued safe operation or provide alternative services and procedures resulting from the occurrence.

2.5 CONSIDERATIONS ON FLIGHT INSPECTION PERIODICITY DURING PANDEMIC

2.5.1 There might be occasion that the flight inspection could be affected by external factor with global impact, such as the COVID-19 pandemic. With such a huge global impact, cross-country deployment of flight inspection aircraft might become difficult, especially for those States who do not have their own FISP. As such,

States should assess and consider the flight inspection periodicity on radio navigation aids to secure continuous service or keep minimum impact to service.

2.5.2 ICAO has published a reference note on the considerations of radio navigation aids flight inspection periodicity practices during COVID-19 the pandemic and restoration to service after temporary removal from service, (at Attachment C to this chapter details please refer to the following link:)

<https://www.icao.int/safety/OPS/OPS-Normal/Pages/Flight-inspection-for-radio-aids.aspx>

2.5.2

Attachment A

Example Flight Inspection Programme

Example Routine Flight Inspection Program

Day 1	Day 2	Day 3	Day 4	Day 5	Day 6	Remarks
In-briefing at (time)						In-briefing with flight inspection team
	XX VOR OFF (time)	XX VOR F/I (start time)				XX VOR – periodic F/I after annual maintenance
			XX ILS maintenance (off time)	XX Tx 1 F/I (start time) XX Tx 2 F/I (start time)		XX ILS - periodic F/I after annual maintenance
					De-briefing	De-briefing with flight inspection team

Notes for ATC and/or Aerodrome Operator:

- Expected period and end time for VOR and ILS flight inspection
- Runway closure and maintenance requirements

Attachment B

Example Flight Inspection Profiles

VOR/DME Routine Inspection

EXAMPLE VOR/DME INSPECTION PROCEDURES LIST					Profile Version
Facility ID		[Facility ID]	Routine Inspection		
Target Completion Time (LT)	Run No.	Flight Procedure	Procedure Description	Facility Transmitter Number	Items To Be Inspected
xxxx-xxxx		Radial xxx ^o	xxNM-xxNM, QNH xxxxFt	VOR/DME No.1	e.g. Reference Radial/Alignment Check
		Radial xxx ^o	xxNM-xxNM, QNH xxxxFt	VOR/DME No.2	e.g. Reference Radial/Alignment Check
		Radial xxx ^o	xxNM-xxNM, QNH xxxxFt	VOR/DME No.1 Only	e.g. VOR Monitor Alarm Check
		Radial xxx ^o	xxNM-xxNM, QNH xxxxFt		
		Radial xxx ^o	xxNM-xxNM, QNH xxxxFt	VOR/DME No.1	e.g. VOR Monitor Alarm Normal
		Orbiting (C.C.W. / C.W.)	Radius: xxNM, QNH xxxxFt	VOR/DME No.1	Mean Alignment Error, Bends, Roughness, DME Range Error
		Orbiting (C.C.W. / C.W.)	Radius: xxNM, QNH xxxxFt	VOR/DME No.2	Mean Alignment Error, Bends, Roughness, DME Range Error

Routine Inspection (ILS Tx1)

EXAMPLE ILS INSPECTION PROCEDURES LIST					Profile Version
Runway		ILS Name	ID	ILS Identification	Routine Inspection
Target Completion Time (LT)	Run No.	Flight Procedure	Procedure Description	Facility Transmitter Number	Items To Be Inspected
xxxx-xxxx		e.g. Threshold Parking	Runway	LOC No.1&2	e.g. Monitor Alarm Check
xxxx-xxxx		e.g. Level Run	xxNM-xxNM QNH xxxxFT	GP No.1	e.g. Width (including alarm), Symmetry SBP, etc.
xxxx-xxxx		e.g. Level Arc	xxNM, +xx ^o -xx ^o , QNH xxxxFT	LOC No.1	e.g. Width (including alarm), Symmetry, Clearance, etc.
xxxx-xxxx		e.g. Approach with low pass	Initial From xxNM and QNH xxxxFT	DME No.1; LOC/GP No.1	e.g. DME and Runway Lighting, Path Angle, Datum, Mod Sum, Structure, etc.

Routine Inspection (ILS Tx2)

EXAMPLE ILS INSPECTION PROCEDURES LIST					Profile Version
Runway		ILS Name	ID	ILS Identification	Routine Inspection
Target Completion Time (LT)	Run No.	Flight Procedure	Procedure Description	Facility Transmitter Number	Items To Be Inspected
xxxx-xxxx		e.g. Level Run	xxNM-xxNM QNH xxxxFT	GP No.2	e.g. Width (including alarm), Symmetry SBP, etc.
xxxx-xxxx		e.g. Level Arc	xxNM, +xx ^o -xx ^o , QNH xxxxFT	LOC No.2	e.g. Width (including alarm), Symmetry, Clearance, etc.
xxxx-xxxx		e.g. Approach with low pass	Initial From xxNM and QNH xxxxFT	DME No.2; LOC/GP No.2	e.g. DME and Runway Lighting, Path Angle, Datum, Mod Sum, Structure, etc.

Remarks:

- Any protection to ILS sensitive area should be applied

Attachment C

Flight Inspection Periodicity Considerations for Radio Navigation Aids during the COVID-19 Pandemic and Related Recovery Phase

1. Introduction

1.1. The present note discusses issues related to flight inspection that could arise during the COVID-19 pandemic and during the recovery phase, with particular regard to periodicity. The main purpose of the document is to ensure that flight inspection will be able to maintain safe operation of navigation aids during the pandemic and will not be on the critical path to aviation recovery after the pandemic.

1.2. To this end the document stresses the need to maintain regular ground and flight checks of nav aids to ensure that they are available during recovery (delaying implementation of new facilities if necessary). It provides information on flight inspection experiences and best practice currently adopted in several ICAO States, including recommendations on how to deal with periodicity intervals when delays are experienced.

2. ICAO Requirements on Flight Inspection Periodicity

2.1. The fundamental ICAO provision addressing flight inspection in general is the Standard in Annex 10, Volume I, Chapter 2, 2.2.1 (reproduced in Appendix).

2.2. Guidance on flight inspection, including periodicity, is given in the ICAO *Manual on Testing of Radio Navigation Aids* (Doc 8071). The general aspects of periodicity requirements are addressed in section 1.15 of the document (reproduced in Appendix), whereas suggested [1] periodicities for specific navigation aids are given in the chapters corresponding to each aid. States may have determined their periodicity requirements based on local circumstances and as such the recovery should consider these periodicities.

3. Relationship between Ground Testing and Flight Inspection

3.1. This document focuses on flight inspection periodicity. However, Doc 8071 also specifies a number of ground tests with an associated periodicity. Normal practice is to ensure that a navigation facility passes all of its ground tests prior to conducting a flight inspection. Local maintenance staff normally accomplish this. This document assumes that such ground testing can be carried out as required and in accordance with the local COVID-related health precautions. Some of the measures discussed herein can also be applied to ground maintenance staff. The document focuses on flight inspection due to its often international dimension (cross-border operations).

4. Flight Inspection Practices during the Pandemic

4.1. The ICAO Secretariat and EUROCONTROL have conducted an informal survey of flight inspection practices during the pandemic in twenty-seven States.

4.2. The survey results show that the majority of States surveyed are maintaining a regular or near-regular flight inspection schedule during the pandemic. This is consistent with the general recognition of ATC as an essential public service and the related need for reliable system performance of radio navigation aids. However, it should also be noted that the majority of the responses came from States that operate their own flight inspection aircraft. So the survey may not fully reflect the situation in States where issues may exist due to delays or suspended flight inspection operations, especially if they rely on cross-border flights by flight inspection providers (see below).

5. Special Measures

5.1. In order to sustain the flight inspection schedule notwithstanding the pandemic-related difficulties, the majority of the States surveyed have adopted special health safety procedures and operational measures, as discussed below.

6. Health Safety Procedures

6.1. Some or all of the following health safety procedures have been put in place:

- (a) daily sanitization of aircraft^[2] and equipment;
- (b) daily supply of personal protection devices to crew, with detailed instructions on usage;
- (c) flight inspection crew segregation from ground support personnel (ground maintenance, dispatch, refuel etc);
- (d) flight inspection crew segregation from engineering personnel responsible for the nav aids under test (telephone coordination only);
- (e) segregation between the flight inspection crews themselves (fixed crew staffing); and
- (f) implementation of alternate on/off crew rotation rosters taking into account potential incubation period.

7. Operational Measures

7.1. While flight inspection operations have been to some extent facilitated by the low air traffic levels currently prevailing, overall significant operational restrictions are being experienced, calling for special measures to mitigate them.

7.2. A common approach adopted for flight inspection operations during pandemic is to keep individual missions within a single day, returning to base at the end of the day and thus avoiding overnight stays at the destination.

7.3. The impact of the associated reduction in efficiency could be mitigated by prioritizing regular flight inspection missions over new implementation projects (new facilities and procedures).

7.4. Furthermore, among regular missions, those addressing facilities that are approaching the flight inspection due date, particularly in the case of ILS Category III facilities, should be prioritized.

7.5. In some cases however, reductions in aerodrome operating hours may limit the number of working hours available in a day. In such cases and in other cases when overnight stays are necessary (e.g. to avoid exceeding flight duty time limitations), particular care should be given to assessing the chosen accommodation to ensure compliance with pandemic sanitation provisions and minimize the need for external contacts.

8. Specific Issues with Cross Border Flights

8.1. In some cases, in which flight inspection services are supported by cross border flights (international flight service operations), a number of specific issues have been encountered:

- (a) requirements for special authorization to access aerodromes that would otherwise be closed to all traffic;
- (b) requirements for special authorization for crew access to country;
- (c) requirements for quarantine on crew arrival to destination and return to base;
- (d) difficulties in ensuring avoidance of contact between crew and ground personnel at destination (eg due to custom/immigration controls); and
- (e) suspension of ground maintenance activities.

8.2. These issues were largely unexpected, due to the situation being effectively unprecedented, and were not taken into account in the original inspection schedules. They have required ad-hoc adjustments, negotiated bilaterally on a case-by-case basis by the entities involved. This has typically led to scheduling delays. However, notwithstanding the delays, cross border flights have remained largely feasible, if less efficient, thanks to the commitment of all the parties to the flight inspection requirements.

8.3. In the process, the need for international recognition in pandemic situations of the special status and needs of flight inspection as a key element of the safety-critical air navigation infrastructure has been highlighted. Future work by ICAO will address the development of guidance to States on facilitating cross-border flight inspection

~~operations in pandemic situations, including development of an advisory health safety protocol to minimize interaction between crew and ground personnel.~~

~~9. Dealing with Potential Periodicity Issues during and after the Pandemic~~

~~9.1. The informal survey results suggest that in principle flight inspection should be feasible even in COVID-19 times, possibly with some restrictions requiring prioritization/rearranging of schedule as discussed above.~~

~~9.2. As a result, periodicity of flight inspection should not be affected substantially, and it should be possible to limit any potential deviations from the nominal intervals to within the time window of extension mentioned in Doc 8071, 1.15.15. While Doc 8071 makes no recommendations on the length of such time windows, the extension window needs to be a reasonable fraction of the nominal interval. For example, some States use a maximum delay of 1 month for nominal inspection periodicities of 6 months.~~

~~9.3. In cases in which nominal periodicity cannot be maintained and the appropriate extension time window is exceeded (e.g. because of initial set up issues with cross-border operations, as discussed above), Doc 8071, 1.15.15 offers a choice of actions that may be considered:~~

- ~~(a) allowing for further extension time, after engineering evaluation and/or ground maintenance reinforcement;~~
- ~~(b) downgrading of ILS (Category III down to Category I or II); and~~
- ~~(c) temporarily removing the navigation aid from service.~~

~~9.4. In choosing among these actions, the responsible entities should take into account the exceptionality of the current situation, in which aviation has suffered an unprecedented setback and is facing what can be expected to be a very difficult recovery phase. In this context, the navigation infrastructure must remain operational both to support the reduced level of traffic during containment measures (including flights meeting critical pandemic-related needs, such as delivery of medical supplies) and to facilitate the resumption of regular flight operations. Therefore, in cases where timely flight inspection cannot be ensured, the preferred method for maintaining safe signals in space is to either take advantage of the (short) periodicity extension window, or, if a longer extension is required, to grant an extension of periodicity intervals in line with the principles described in Doc 8071. Furthermore, in cases where flight inspection operations were suspended and periodicity intervals extended, careful planning should ensure that navigation aid availability of service can be ensured to support the recovery.~~

~~9.5. At the same time, no compromise on operational safety due to non-standard performance of navigation aids should be accepted. Instead, potential extensions of nominal inspection intervals should be considered only in the presence of appropriate mitigations maintaining nominal safety levels. To this end, the provisions of Doc 8071, 1.15 should be taken into account.~~

~~9.6. Doc 8071, 1.15.2 recognizes that the suggested periodicities are given as general guidance and may be modified based on the manufacturer's recommendation or operational experience. Subsequent sections (1.15.4 – 1.15.6) discuss the factors influencing the inspection intervals, including reliability and stability of operation of the equipment, extent of ground monitoring, degree of correlation between ground and flight measurements, changes in the operating environment, manufacturer recommendations, and quality of maintenance. In many cases, modern ground facilities using current technology provide highly stable and reliable signals. A point of particular practical interest in the current context is given in 1.15.6 with the observation that equipment reliability may be adversely affected by too frequently scheduled major maintenance activities, which should therefore be limited to essential needs if extended periodicity is desired.~~

~~9.7. Further sections of Doc 8071, (1.15.7 – 1.15.8 and 1.15.10 – 1.15.14) discuss the type of technical analysis that would need to be performed to extend nominal ground and flight inspection periodicities in a normal situation. While performing such detailed analysis may be unpractical in a pandemic situation, it should be noted that the most important item to ensure safe facility performance is the verification of the proper functioning of executive monitor shutdown capabilities. Special attention should also be given to site safeguarding, especially if aircraft or other large equipment is being parked near a navigation aid.~~

~~9.8. While the guidance in Doc 8071 does not explicitly address the current situation, it does indicate that, in situations in which maintaining nominal flight inspection periodicity is effectively impossible, case-by-case extensions can legitimately be considered on an exceptional basis when the relevant enabling factors are present. In other words, in the unprecedented situation now being faced by aviation, a reliable system running in a stable configuration with a history of nominal performance, undergoing regular ground checks consistent with~~

manufacturer recommendations which indicate normal functioning, and in the absence of anomaly reports, should normally qualify for an extension of the periodicity interval.

9.9. Special considerations apply to the specific case of Category III ILS. Because of the particularly demanding requirements, rigorous testing is essential. For that reason, during the current pandemic several States are prioritizing flight inspection of Category III ILS. Should it nevertheless occur that flight inspection intervals for a Category III ILS are significantly exceeded, as mentioned above a potential option would be downgrading of the facility from Category III to Category II or Category I.

Note:

[1] It should be noted that "suggested" is the term used in Doc 8071, as opposed to "required". See for instance Doc 8071, 1.5.2: "This document contains suggested schedules for each radio navigation aid, which should be considered (and modified, if necessary), based on the conditions relevant to each State and each site."

[2] See for example EASA "Safety Directive under Article 76(6)(b) of Regulation (EU) No 2018/1139—SD No.: 2020-01"

Chapter 3

Conducting Flight Inspection

3.1 TYPICAL FLIGHT INSPECTION PROCEDURES

3.1.1 Flight Inspection Procedures Manual

3.1.1.1 Each FISP should provide evidence of operating to a Flight Inspection Procedure Manual. This manual provides assurance to the customer that the necessary compliance checks are being carried out as intended by Doc 8071 and can help with demonstrating compliance. These may vary State to State depending on the regulatory oversight. Some investigation into other areas of aviation within your State can aid with what could be acceptable criteria such as:

- (a) Procedure Development (Procedures for Air Navigation Services – Aircraft Operations (PANS-Ops) or Terminal Instrument Procedures (TERPs)); and
- (b) Aircraft Recognized Approval Documentation (FAA/EASA, etc.).

3.1.1.2 Doc 8071 provides guidance on typical check methods intended for both Ground and Air for each facility type. The operator should ensure that each listed item is applicable to the inspection type (Commissioning or Categorization, Site, Periodic). The operator or owner of the facility should verify the FISP is adequate to satisfy the required parameter check. For comparison, flight test procedures have been also included in Doc 8071 for guidance.

3.1.1.3 Some flight profiles have been included in this document to assist with comparisons. In some situations, flight validation of the procedure is considered a separate inspection, and therefore it is important to check if the intended procedure covers flying the approach procedure. This may be of benefit in satisfying the procedure revalidation criteria.

3.1.1.4 Clear procedures should be provided to cover any navigational, surveillance or communication equipment that is subject to flight inspections. Inspections should be undertaken with equipment that has calibration traceability and where the FISP can provide clear evidence of the suitability for individual parameter assessment. A Test Accuracy Ratio (TAR) of minimum three or better for each parameter measured can provide a good picture of uncertainties and if the system is fit for purpose.

3.1.1.5 As a provider of service such as DVOR, ILS or other navigational equipment, it is important that the ANSP can demonstrate the facilities are operating to the respective ICAO standard. For this reason, the closer the inspecting receivers represents the level of avionics needed in large aircraft, the less risk of finding inconsistencies between airline approaches and ground check measurements. Hence it is sometimes advantageous if the equipment has international accreditation such as TSO conformance and other relevant aircraft software development standards. This is more important for systems that are directly used for the purpose of Air Navigation verification. The degree of compliance is less for items used as a surveillance tool.

3.1.2 Instrument Landing System (ILS)

3.1.2.1 Key requirements:

- (a) Antenna should be calibrated for field strength through the frequency range and different orientations. This should also include frequency response and polar patterns. This data should be available for verification.
- (b) The antenna should have TSO compliance for IFR and comply with the local airworthy certification. Location and installation of the antenna should be in accordance with the following:
 - (i) Recordings should show minimum propeller modulation.
 - (ii) Aircraft should be fitted with airworthy ILS/DME/Markers equipment approved for IFR flight.

- (iii) Kit should be capable of recording the required parameters against the reference system, typically at a rate greater than 5 samples per second.
- (iv) The antenna should also have the appropriate TSO rating as required by IFR flight.
- (v) The kit should be capable of recording the parameters as outlined in Doc 8071 within the accuracy specified.

3.1.2.2 Typical Flight Profiles for ILS flight checks:

- (a) Alignment runs normally commencing as required by the published procedure or 10NM for periodic Inspections.
- (b) 6-10NM arc profiles, forty degrees either side of the runway centre-line.

3.1.2.3 Typical parameters to be recorded as applicable for the items being checked:

- (a) Receiver course deviation for all systems include Localizer/Glidepath/markers/DME
- (b) Aircraft position fixing system deviation
- (c) The difference (a) minus (b)
- (d) Receiver input signal level
- (e) Modulation levels
- (f) Frequency spectrum (optional)

3.1.2.4 Careful consideration should be made with regard to the procedures used and the purpose of the check.

3.1.2.5 Depending on the methods employed to ensure monitor integrity, instead of inspecting both the transmitting and monitoring systems of the ILS in every check, some locations may choose to flight inspect the transmitting system once in every two inspections.

3.1.2.6 FISP should be able to provide a table of parameters to assist with comparisons against Doc 8071.

3.1.2.7 An example checklist of commissioning and periodic flight inspection items for ILS is tabulated below for reference.

Check Item	Commission	Periodic
Identification	X	X
Modulation Balance	X	R
Modulation Depth	X	X
Polarisation	X	R
Front Course Alignment	X	X
Course Structure	X	X
Course Sector Width and Symmetry	X	R
Off-course DDM Clearance	X	-
Coverage or Usable Distance	X	-
Monitor Alarm – Front Course Alignment (Position Alarm)	X	X
Monitor Alarm - Course Sector Width (Width Alarms)	X	X
Monitor Alarm - Off-Course DDM Clearance	X ⁽¹⁾	X
Monitor Alarm – Coverage	X	-
Dual Equipment	X	X ⁽³⁾
Flyability	X	X
Associated Navigation Aids (Nav aids)	X	X ⁽²⁾

LEGEND: R = To action on request
X = To action

- = Not required
- (1) = Capture/Clearance Wide Alarm applies only for a dual frequency localizer
- (2) = Includes runway visual aids
- (3) = Alignment, Modulation Depth and Identification Only

3.1.3 Doppler Very High Frequency Omni-Directional Range (DVOR)

3.1.3.1 Key requirements:

- (a) Antenna should be calibrated for field strength, and data should be available for verification. The antenna should have TSO compliance for IFR and comply with the local airworthy certification.
- (b) Recordings should show minimum propeller modulation.
- (c) Aircraft should be fitted with airworthy DVOR equipment approved for IFR flight.
- (d) Kit should be capable of recording the required parameters against the reference system, typically at a rate greater than 5 samples per second.
- (e) The antenna should also have the appropriate TSO rating as required by IFR flight.
- (f) The kit should be capable of recording the parameters as outlined in Doc 8071, within the accuracy specified.

3.1.3.2 Typical parameters to be recorded as applicable for the items being checked:

- (a) Receiver course deviation
- (b) Aircraft position fixing system deviation
- (c) The difference (a) minus (b)
- (d) Receiver input signal level
- (e) Modulation levels
- (f) Modulation index

3.1.3.3 An example checklist of commissioning and periodic flight inspection items for DVOR is tabulated below for reference.

Check	Commission	Periodic
Identification	X	X
Voice	X	X
9960 Hz/30 Hz Levels	X	X
Vertical Polarisation	X	-
Orbit	X	X
En route Radials	X	R
Terminal Radials and Procedures	X	X ⁽²⁾
Radial Plan	X	-
Intersections and Changeover Points	X	-
Off-track Coverage	X	-
VOR/DME Sector Altitude Coverage	X	R
High Angle Coverage	X	R
Receiver Checkpoint	X	X
VOR Monitor Checks	X	X
Dual Equipment	X	X
Transmitter Differential	X	-
Standby Power	X	-
Associated Navigation Aids (Nav aids)	X	X ⁽¹⁾

LEGEND: R = To action on request
X = To action

- = Not required
- (1) = An appearance inspection of the VASI/PAPI is to be included if not otherwise subject to a routine inspection
- (2) = Final approach radial(s) only, profile as published

3.1.3.4 Some typical Flight Profiles for DVOR flight inspections:

- (a) Arcs at published minimum safe altitude.
- (b) Published approach radials at advisory altitudes.

3.1.4 Distance Measuring Equipment (DME)

3.1.4.1 Key requirements:

- (a) Antenna should be calibrated for field strength and data should be available for verification. This should consider cables and connectors.

3.1.4.2 A summary of flight test requirements is listed in ICAO Doc 8071. These form a comparison against the FISP's procedure manual. If there are missing parameters, further clarification should be made where in some cases, with acceptable technical and statistical validation, these parameters could be moved to a ground inspection. This is more common on DME facilities. However, this may not be acceptable by your State's regulatory authority and may need to be endorsed by them.

3.1.4.3 Often the DME equipment would be included as part of the ILS or DVOR flight inspections where it is considered an associated facility.

3.1.4.4 Typically, published DME arcs with the appropriate altitude restrictions would be flown, and in accordance with any associated procedures.

3.1.4.5 Doc 8071 provides a list of parameters for reference. It is important to consider both ground check requirements and flight inspection requirements for DME.

3.1.4.6 An example checklist of commissioning and periodic flight inspection items for DME is tabulated below for reference.

Check	Commission	Periodic
Identification	X	X
DME System Distance Accuracy	X	X
Coverage - Terminal Procedures	X	X
Coverage - En-route Radials	X	-
Coverage - Off-track	X ⁽¹⁾	-
Coverage - Steps, Intersections and Changeover Points	X	-
Sector Coverage	X ⁽¹⁾	-
Dual Equipment	X	X ⁽²⁾
Standby Power	X	-
Associated Navigation Aids (Nav aids)	X	X

- LEGEND:
- X = To action
 - = Not required
 - (1) = As specified by Navigation Services
 - (2) = Identification only for second transponder

3.1.5 Primary Surveillance Radar and Secondary Surveillance Radar (PSR/SSR)

3.1.5.1 The requirements are very dependent on the engineering assessment requirements and expected coverage volume.

3.1.5.2 Some typical considerations are:

- (a) Altitude;
- (b) Range;

- (c) Delay to alert; and
- (d) Minimum radar coverage elevation.

3.1.5.3 According to Doc 8071, Civil ATC PSR and SSR facilities, after being commissioned and set into operational service, do not require a periodic flight inspection.

3.1.5.4 Special flight inspections may be conducted as part of a measurement campaign after major equipment modifications, or for specific problem investigation.

(d)——

3.2 OTHER TYPES OF FLIGHT INSPECTION

3.2.1 Procedure Validation

3.2.1.1 This is detailed in ICAO Doc 9906, Quality Assurance Manual for Flight Procedure Design. Volume 5 – Validation of Instrument Flight Procedures. The ANSP, FISP and Procedure Design Company need to work closely to ensure this aspect is covered off adequately.

3.2.2 VHF equipment, ADS-B, GBAS

3.2.2.1 Flight inspection is typically carried out under request from an appropriately trained Communications/ADS-B or GBAS engineer. The specifics such as location, type of check and flight profiles are determined by a collaborative approach between all involved disciplines. In some cases, flight inspection is used to assist in the validation of models for determining coverage.

3.2.3 Performance-based Navigation – RNAV and RNP

3.2.3.1 At a minimum, the aircraft should have the capability to undertake the desired procedure validation. RNP procedures' validation requirements would normally be specified within the Procedure Design Company specifications. The Aeronautical Design and Development organization should analyze the results to determine containment within the specified criteria. Technical assessment perspective is as follows;

- (a) Validation of obstacle survey data is recommended during the flight validation process.
- (b) Verification of survey data can be performed by setting ground stations at certain survey points. The ground survey team can check and compare the DGPS signal to the TSO avionic aircraft receiver position.
- (c) The survey data may be affected by waypoint, track and bearing error.
- (d) The effect of terrain shielding should be taken into consideration.
- (e) Verification is often done slightly lower than the published profile to remove altimeter error as often it is advantageous to verify in the worst-case position.

3.3 TYPICAL FLIGHT INSPECTION SYSTEM PERFORMANCE SPECIFICATIONS AND ASSOCIATED TEST ACCURACY RATIOS (TAR)

3.3.1 Test Accuracy Ratios

3.3.1.1 As the results obtained by the flight inspection system could potentially be used to defend a service provider in the event of an incident or accident, the State should clearly specify the standards adopted in the maintenance and calibration of the systems used for flight inspection purposes. To effectively perform calibration of a system, the calibration equipment should be typically five (minimum three) times more accurate than the system equipment. Some considerations should be as follows:

- (a) Temperature stability and compensation.
- (b) Electromagnetic interference.
- (c) Polar Pattern considerations.
- (d) Absolute measurements.
- (e) Relative measurements.
- (f) Aircraft receiver and calibration equipment duplication.

3.3.1.2 The calibration equipment should also undergo regular periodic checking as part of verification against traceable international standards that support the TAR required.

3.3.1.3 A dedicated calibration facility operated by the ANSP or ISO/IEC 17025 approved facility is the preferred means by which to achieve this to ensure a good consistency of standards.

3.3.2 Duplication

3.3.2.1 System duplication is important throughout the calibration process of both the flight inspection equipment and calibration laboratory used to calibrate the systems. Duplication of equipment can very quickly identify system drift and prevent unknowingly using a bad receiver to adjust an air critical system incorrectly.

Chapter 4

Reporting of Flight Inspection Results

4.1 TYPICAL FLIGHT INSPECTION REPORTS

4.1.1 After each daily flight inspection, the flight inspector should prepare the flight inspection report. The formal flight inspection report signed by the responsible captain and flight inspector should be provided after the flight inspection. The contents of flight inspection report typically include the following items:

- (a) Location
- (b) Identification
- (c) Flight inspection date(s)
- (d) Facility inspected
- (e) Type of inspection
- (f) Inspected items
- (g) Results
- (h) NOTAM
- (i) Facility status
- (j) Remarks
- (k) Aircraft registration number

4.1.2 A sample flight inspection report is provided in Attachment A to this Chapter for reference.

4.2 TYPICAL FLIGHT INSPECTION RECORDS

4.2.1 Flight inspection records and flight inspection data sheet should be provided by flight inspector. The contents of flight inspection record typically comprise of the following items:-

- (a) Airport name
- (b) Aircraft registration number
- (c) Date of inspection
- (d) Inspector's name
- (e) Flight hours
- (f) Facility type and identification
- (g) Run numbers
- (h) Transmitter number
- (i) Flight inspection results of each run

4.2.2 A sample Flight Inspection Report is provided in Attachment B to this Chapter for reference.

Attachment A

Sample Flight Inspection Reports

Sample Flight Inspection Report for ILS/DME

1.LOCATION:			2.RUNWAY NO:	
3.DATE(S) OF INSPECTION:			4.IDENTIFICATION:	
5.TYPE OF INSPECTION		SITE EVALUATION	PERIODIC	SPECIAL
		COMMISSIONING	SURVEILLANCE	INCOMPLETE
6.FACILITY INSPECTED		LOCALIZER	GLIDE SLOPE	DME
		LIGHTING SYSTEM	7. AIRCRAFT NO:	
8.CATELOGY:			9.FREQUENCY:	
10.COMMISSIONED COURSE WIDTH:			11.COMMISSIONED PATH ANGLE:	
12.LOCALIZER				
FLIGHT INSPECTION ITEMS	TX1		TX2	
	INITIAL	FINAL	INITIAL	FINAL
IDENTIFICATION				
MODULATION				
ALIGNMENT				
COURSE STRUCTURE—Z1/RNG				
COURSE STRUCTURE—Z2/RNG				
COURSE STRUCTURE—Z3/RNG				
COURSE STRUCTURE—Z4/RNG				
COURSE STRUCTURE—Z5/RNG				
VERTICAL POLARIZATION/RNG				
WIDTH/SYMMETRY				
MEAN WIDTH(HALF)/SYMMETRY				
CLEARANCE 90/DEG				
CLEARANCE 150/DEG				
MOD.BALANCE(COS/CLR)				
Z5 ROLL OUT RESULT:				

USABLE DISTANCE				
MONITOR				
WIDTH ALARM(NARROW)/SYM				
WIDTH ALARM(WIDE)/SYM				
CLEARANCE 90 (WIDE ALARM)				
CLEARANCE 150(WIDE ALARM)				
ALIGNMENT ALARM(+)				
ALIGNMENT ALARM(-)				
13.GLIDE SLOPE				
FLIGHT INSPECTION ITEMS	TX1		TX2	
	INITIAL	FINAL	INITIAL	FINAL
ANGLE /REFERENCE DATUM HEIGHT				
MODULATION				
PILOT IN CHARGE:	FLIGHT INSPECTOR:		AIRCRAFT NUMBER:	

Sample Flight Inspection Report for Runway Approach Lights and PAPI

1.LOCATION:				2.RUNWAY NO:		
3.DATE/DATES OF INSPECTION:						
4.TYPE OF INSPECTION		SITE EVALUATION		PERIODIC		SPECIAL
		COMMISSIONING		SURVEILLANCE		INCOMPLETE
5.FACILITY INSPECTED		PAPI		RUNWAY LIGHTS		APPROACH LIGHTS
6.COMMISSIONED PAPI ANGLES		NO.1	NO.2	NO.3	NO.4	PATH ANGLE
	LEFT					
	RIGHT					
7.PAPI INSPECTION RESULTS						
ACTUAL PAPI ANGLES		NO.1	NO.2	NO.3	NO.4	PATH ANGLE
	LEFT					
	RIGHT					
ITEMS CHECKED	SAT	UNSAT	ITEMS CHECKED	SAT	UNSAT	
COVERAGE ANGLE			VISIBLE DISTANCE			
INTENSITY LEVEL			INTENSITY COINCIDENCE			
NO. OF INOPERATIVE LIGHTS			COINCIDENCE WITH ILS			
8.APPROACH LIGHTS RESULTS INSPECTION RESULTS						
ITEMS CHECKED	SAT	UNSAT	ITEMS CHECKED	SAT	UNSAT	
LAMP ALINMENT			VISIBLE DISTANCE			
INTENSITY LEVEL			INTENSITY COINCIDENCE			
NO. OF INOPERATIVE LIGHTS			LIGHTS CATEGORY			
9.RUNWAY LIGHTS INSPECTION RESULTS						
ITEMS CHECKED	SAT	UNSAT	ITEMS CHECKED	SAT	UNSAT	
LAMP ALINMENT			VISIBLE DISTANCE			
INTENSITY LEVEL			NO. OF INOPERATIVE LIGHTS			
RUNWAY END LIGHTS			LANDING ZONE LIGHTS			

10.FACILITY STATUS	PAPI	RUNWAY LIGHTS	APPROACH LIGHTS	11.NOTAM's:
UNRESTRICTED				
RESTRICTED				
UNUSABLE				
12.REMARKS:				
PILOT IN CHARGE'S SIGNATURE:		FLIGHT INSPECTOR'S SIGNATURE:		AIRCRAFT NO:

Sample Flight Inspection Report for DVOR/DME

1.LOCATION:				2.IDENTIFICATION:			
3.FLIGHT INSPECTION DATE(S):			4.FACILITY INSPECTED		VOR		DME
5.TYPE OF INSPECTION		SITE EVALUATION		PERIODIC		SPECIAL	
		COMMISSIONING		SURVEILLANCE		INCOMPLETE	
6.ORBIT RESULTS							
NO.	TX NO.	FLIGHT LEVEL(MSL)	ORBIT RADIUS(NM)	MEAN BEARING ERROR		MEAN RANGE ERROR	
1	1						
2	2						
7.RADIAL RESULTS							
RADIAL USE							
AZIMUTH							
TX NO.							
MSL ALTITUDE							
DISTANCE FROM							
DISTANCE TO							
ALIGNMENT ERROR							
MAX BEND/RANGE							
ROUGHNESS/RANGE							
POLARIZATION							
TRANSMITTER DIFF							
MOD30HZ AM							
MOD30HZ FM							
MOD9960HZ							
MINIMUM SS							

DME RANGE ERROR								
INTERFERENCE								
8.MONITORS								
TX NO.	REFERENCE RADIAL	MSL	RANGE	ALIGNMENT	ALARM+	ALARM-		
9.ORBIT BEARING ERROR (TX NO.1)								
9.ORBIT BEARING ERROR (TX NO.2)								
10.GROUND RECEIVER CHECK POINT								
GROUND CHECK POINT		TX NO.		BEARING READING		RANGE READING		
11.GENERAL		TX1		TX2				
		SAT	UNSAT	SAT	UNSAT			
STANDBY POWER								
VOICE								
VOR IDENTIFICATION								
DME IDENTIFICATION								

DME ACCURACY						
DME COVERAGE						
12.FACILITY STATUS			13.NOTAM's:			
STATUS	VOR	DME				
UNRESTRICTED						
RESTRICTED						
UNUSABLE						
14.REMARKS:						
PILOT IN CHARGE'S SIGNATURE:			FLIGHT INSPECTOR'S SIGNATURE:		AIRCRAFT NO:	

Appendix 1

1. USEFUL REFERENCE

- ICASC - Document on Standards and Recommended Practises for Flight Inspection & Flight Validation Organisations
http://www.icasc.co/sites/faa/uploads/documents/Library/ICASC/ICASC_SARPs_FI_FV_v14_11102018_final101.pdf
- ICASC Recommended Flight Inspection & Flight Validation Contract Annex
http://www.icasc.co/sites/faa/uploads/documents/Library/ICASC/ICASC_FIS_Contract_Annex_v0_2_2_6_05_2016_final101.pdf
- Reference note from ICAO on the considerations of radio navigation aids flight inspection periodicity during COVID-19
<https://www.icao.int/safety/OPS/OPS-Normal/Pages/Flight-inspection-for-radio-aids.aspx><https://www.icao.int/safety/COVID-19OPS/Pages/ANS.aspx>

Appendix 2

1. Use of Emerging Technology to Supplement Flight Inspection

1.1. Flight navigation systems are essential in the world where global air traffic grows continuously. These systems enable Air Navigation Service Providers (ANSPs) to ensure that aircraft can reach their destination in due time safely, despite the continuous increase in air traffic density. Indeed, Air Traffic Management (ATM) companies strongly rely on advanced, unfailing and efficient navigation aid equipment in order to accomplish their mission in the best conditions.

1.2. Among the numerous requirements from the International Civil Aviation Organization (ICAO), flight navigation systems must be regularly calibrated, inspected and maintained to ensure that all essential navigation aids for pilots are always working properly. This means that these systems must be tuned and maintained to radiate the correct signals in the airspace, at any time. To achieve this, a combination of ground and air inspections is necessary, like the localizer measurements for CAT III ILS (Instrument Landing System).

1.3. ILS is an essential navigation aid to help pilots land their aircraft in low visibility conditions during IFR (Instrument Flight Rules) flights. In order to maintain the ICAO ILS certification, dynamic measurements need to be performed by the airport operators / ANSPs, their subcontracted flight inspection organizations or government agencies. These companies are always looking to improve and streamline inspection processes to mitigate impacts on airport operations. The regular ILS signal inspection is made in flight, using a manned aircraft. It requires prior coordination and preparation with various stakeholders, together with ground measurements in order to optimize the manned flight inspection.

1.4. Both of the above flight and ground operations have their limitations: the manned aircraft is costly, noisy and environmental unfriendly with large fuel consumption by flight inspection aircraft, while the ground one is limited in terms of reachable distance and height for the measurement antenna. The ground ILS inspections are indeed restrained to the runway threshold, since they are performed using masts that generally don't go higher than around 25 meters, from the ground. This is where the initiative for developing drones or Unmanned Aerial Vehicle (UAV) inspection solution. With improved lifting power, efficiency and reliability, the drone / UAV could perform inspections in the ILS far field as well as ILS elevation profiles and mini approaches with inspection to analyze the ILS signals (course alignment, slope angle, alarms, displacement sensitivity, etc.) and to supplement the ground and manned flight measurements in a more comprehensive mean.

1.5. With the technology of UAV being widely and rapidly developing, more and more flight inspection institutes came into the research on how to utilize UAVs for flight inspection and many practices have been made. The UAVs are normally classified in two groups, the drones, which are smaller, normally with multiple rotors; and Remotely Piloted Aircraft System (RPAS), which are heavier and with fixed wings. Some institutes concentrate on the development of RPAS flight inspection, which is quite similar to the performance of normal flight inspection aircrafts, but cheaper on cost.

1.6. It should be noted that the technology of UAV/RPAS is still emerging. Major issues that still need to be addressed including the integration of UAV/RPAS with other manned civil aviation traffic in unsegregated airspace, while maintaining a similar high level of integrity and reliability that have been developed and matured over the past decades. These integrity requirements, especially those apply to the operations beyond line of sight, would be even more significant when operating in Terminal Airspace, with a mixture of UAV/RPAS operations and regular traffic in densely used airspace. Major challenges in mastering UAV/RPAS autonomous operations (traffic sensing and avoidance), improving system integrity and reliability, as well as establishing a suitable certification framework and process, still need to be addressed. Nowadays, UAV/RPAS are already well positioned to assist Ground and Flight Inspection under a clearly defined and restrained operational environment.

2. Flight Inspection with Drones

2.1. Application of drone inspection allows improvements on ILS inspection operations by dramatically reducing the manned aircraft flight inspection frequency and thus decreasing the overall operational cost for airport operators. Highlights of advantages that could be brought by applying drone in ILS flight inspections are listed below:

- (a) Supplement to ILS ground measurements
- (b) Excellent repeatability
- (c) Cost & time saving

- (d) Flexible inspection time
- (e) Reducing operational disturbances
- (f) Reducing CO₂ and noise emissions

2.2. This major step in ILS maintenance domain for preventive and corrective maintenance is only a beginning. Thanks to the technology advancement, research institutes are going further in developing the next generation ATM systems. In addition to ILS flight inspections, new horizon also arise for drone / UAV inspection on other systems like VOR, DF, PAPI, radars, etc.

2.3. With user-friendly interface, preparing the drone operation could take less than 1 minute. The operator just has to select the airport and the runway from database and then choose the type of the required inspection. Once this is done, all the required data (missions, waypoints, distances, altitudes, etc.) is generated automatically. There is no need to read the procedures to figure out which measurements that are to be made and where to be made. The operation could be created in platform with simple access from the tablet to view and download the details. This database of airports, runways and navigation aids can be expanded and updated with an easy-to-use web interface.

2.4. Once the corresponding operation has been downloaded to the inspection program / application, the operator could launch the mission and monitor the automated procedures. The operator is guided throughout the mission. Each mission takes only a few minutes of flight and could be repeated as many times as needed. Measurements are available and could be viewed in real-time.

2.5. Reports are viewable on-site through the program / application. There is no need to download the measured data to compile the reports. Reports contain all the relevant measurements and parameters same as any report generated from generic flight inspection aircraft, in the form of tables and images. Reports, along with all the measurements, images or videos, are uploaded into a platform for centralized recording, future reference or additional processing.

3. Worldwide Development of Drones to Assist Flight Inspection / Testing

3.1. As in 2019, flight inspection organizations or institutes in Belgium, China, Germany, Italy, Russia, Spain have used drones to assist and provide supplementary tests in flight inspection works. The drones are normally be used to assist testing of navigation equipment signals, since they are not competent for all flight inspection missions with limited performance in speed, service ceiling, endurance, crosswind resistance, payload, etc.

3.2. Belgium

- (a) The development of the UAV / drone solution for ILS inspection was started in 2015 and in operation since January 2018 in Belgium and has extended the usage to Geneva (GVA – LSGG) and Zurich (ZRH – LSZH) airports.

3.3. Germany

- (a) In early November 2018, a drone specially developed for carrying out ILS measurements was employed at Hannover International Airport in Germany during the commissioning of a new ILS. This entailed generating DDM (Difference of Depth of Modulation) measurement curves above and below the 3° approach path of the new 09R ILS at 1 km distance from the threshold. The measurement flights were monitored not only in the control tower of the Hannover airport, but also at the DFS headquarters in Langen via a drone tracking system. The flights were very successful and form an important impulse for the rapid operational introduction of measurement drones for ground measurements of the numerous Instrument Landing Systems installed at German airports.

4. Flight Inspection with RPAS

4.1. Balancing the factors of performance, cost, operation, maintenance, management, safety, the fixed-wing RPAS with 8-11 meters wing span is better for flight inspection due to its stability in flying, with following example performance for reference.

4.2. Typical performance of RPAS for flight inspection

- (a) Wingspan: 8-11 meters

- (b) Cruising speed: 100-180 km/h
- (c) Max speed: 200-240km/h
- (d) Ceiling: 6000m or higher
- (e) Runway length for take-off and landing: 300m or longer
- (f) Payload for inspection equipment: 50kg or more
- (g) Electrical power supply: 2kw or more
- (h) Endurance: 5 hours or more after inspection system installed
- (i) Communication: C2 or 5G or Data link with bandwidth more than 2M
- (j) Flight control: fully pre-programmable

4.3. Typical RPAS flight inspection system configuration

- (a) RPAS aircraft
- (b) Airborne inspection system including all the receivers, transceivers, camera, position-fixing, communication equipment and antennas, etc.
- (c) Vehicle-borne system including control console, communication equipment, differential station, etc.
- (d) Container and transportation truck
- (e) Control car
- (f) Auxiliary equipment and mobile

4.4. Operation considerations of RPAS flight inspection

- (a) Fully pre-programmed flight for all inspection profiles including take-off and landing
- (b) Signal collection in the air and processing on the ground
- (c) Internet Big Data system and Artificial Intelligence (AI) analysis
- (d) On-site co-operation with NAVAID maintenance and ATC
- (e) Ground transportation from airport to airport
- (f) Crew members: 1 or 2 inspectors, 3 or 4 maintenances/operators

4.5. Safety management of RPAS flight inspection

- (a) Organizations or institutes operating RPAS flight inspection should establish a safety management system (SMS) to ensure flight safety of RPAS. A good experience is to evaluate with the tool named SORA (Specific Operations Risk Assessment).

5. Profiles and Items for RPAS Flight Inspection

5.1. ILS

- (a) All the ILS inspection profiles could be flown by RPAS.

- (b) All the inspection items including LOC alignment, GP angles, modulations, structures, clearance, width, coverage and all the alarms could be checked by RPAS.
 - (c) Alignment alarm of LOC should be checked closer to the antenna on the runway or using the approach since it would be difficult to get a stable result on the ground of runway threshold.
- 5.2. VOR/DME and NDB
 - (a) RPAS could implement almost all the profiles required for VOR/DME and NDB flight inspection. The only insufficiency is the high flight level en-route signal check limited by RPAS performance.
- 5.3. PAPI
 - (a) Many institutes and organizations have attempted to check PAPI with camera-equipped drones. RPAS could do this work better since it could simulate a real approach and get more realistic results. However, camera stability and the ability to zoom during high speed approach would be a challenge to RPAS flight inspection researchers.
- 5.4. Flyability
 - (a) The lack of human sensing and judgment in actual cockpit and without assistance from on-board flight instruments, it is difficult to rate the fly-ability for a specific procedure / equipment by RPAS flight inspection. . It is suggested that fly-ability should be assessed by manned aircrafts.
- 5.5. Flight inspection recordings and plotting
 - (a) Flight inspection recordings and plotting, together with the inspection reports could be done on ground and transferred to a central data repository, which could then be analyzed by customers and facilitate set-up of a Big Data system for future management and reference.