Table CNS II-CARSAM-7

AM(R) VHF SUB-BANDS ALLOTMENT TABLE

Version 0 of 2 Oct 2026, no PfA (initial baseline). 18 frequency sub-bands. Source file: Table CNS II-11 (rebuilt).docx (2 Oct 2026), rebuilt from Table CNS II-11.docx.

For evaluation. The Word file of this table held only the page layout; the table was rebuilt as proper rows and awaits the OK of the CNS Officer.

Frequency sub-band (MHz)	Worldwide utilization	CAR/SAM application	Remarks
118.00 – 118.925	National/International	TWR	
119.00 – 121.375	National/International	APP	
121.5	Emergency frequency	Emergency frequency	
121.60 – 121.975	National/International	SMC	
122.00 – 123.05	National	—	
123.1	Aux. frequency SAR	Aux. frequency SAR	
123.15 – 123.675	National	—	Note
123.45	Air-to-air communications	Air-to-air communications	
123.70 – 126.675	National/International	ACC	
126.70 – 127.575	National/International	General purpose (GP)	
127.60 – 127.90	National/International	VOLMET/ATIS	
127.950 – 128.80	National/International	ACC	
128.850 – 129.850	National/International	APP	
129.90 – 132.025	National/International	AOC	
132.050 – 132.950	National/International	VOLMET/ATIS	
133.00 – 135.950	National/International	ACC	
136.00 – 136.875	National/International	—	
136.90 – 136.975	National/International	Reserved for VDL	

Note. — With the exception of 123.45 MHz, which is also used as the worldwide air-to-air communications channel

SAMPLE