



International Civil Aviation Organization

ATN Seminar and Third ATN Transition Task Force Meeting

Singapore, 26-30 March 2001

Agenda Item 3: Develop ATN Interface Control Documents

Proposed Draft AMHS ICD

(Presented by Japan)

Summary

This paper presents a proposed draft Interface Control Document (ICD) for ATS Message Handling System (AMHS). The proposed document is based on the agreed specification between the US and Japan as well as ICAO ATN SARPs. It is expected that the meeting reviews the document and takes it as a draft AMHS ICD in the Asia/Pacific Region.

1. Background

1.1 ICAO has published ATN SARPs (Doc9705) which include technical provisions for ATS Message Handling System (AMHS).

NOTE: Doc9705 Edition 1 and 2 have been published. Edition 3 has been approved and will be published in mid of 2001.

Based on the SARPs, many States and organizations are planning to implement AMHS for the communication between States and/or within State.

1.2 In Asia/Pacific Region, it has been agreed to implement AMHS service between the US and Japan. Also it was reported that many States such as Australia, Republic of Korea, Hong Kong (China), Thailand and Singapore were planning AMHS trials and/or implementations.

2. Discussions

2.1 In order to keep the interoperability between States within the Region and to have flexibility in the future introduction of ATN applications, States must implement AMHS fully complied with ICAO ATN SARPs (Doc9705). However, the SARPs itself is not enough to be referred since there are options (local matters) in it and there are other items to be referred that are not described in it. In order to cover such flexibility of AMHS specification, it is necessary to develop ICD for the reference by implementers.

2.2 The proposed document is based on the agreed specification between the US and Japan. Since it is also fully complied with ICAO ATN SARPs, it is recommended to take it as a draft AMHS ICD in the Asia/Pacific Region. In order to specify the detailed specification of AMHS, it includes Protocol Implementation Conformance Statement (PICS) of AMHS.

NOTE: ICAO ATN Panel has developed PICS for ATN applications. However, AMHS PICS has not been developed nor will not be developed since AMHS is mostly based on the ISO Standards.

NOTE: The proposed document includes only the specification of AFTN/AMHS Gateway and ATS Message Server with only Basic ATS Message Service (specified in Doc9705 Edition 1 and 2). Enhancement to the AMHS ICD such as inclusion of Extended ATS Message Service (specified in Doc9705 Edition 3) will be done in the future, if necessary.

3. Action by the Meeting

3.1 The meeting is expected to:

- a) review the proposed document and approve it as a draft AMHS ICD in the Asia/Pacific Region;
- b) direct Working Group B to take responsibility to review the document in detail as part of its future work; and
- c) recommend all States and organizations in the Region to:
 - i) implement AMHS based on AMHS ICD; and
 - ii) change and /or adjust their AMHS based on AMHS ICD, if AMHS has been already implemented and if necessary, after the future publication of AMHS ICD at least the international communication between States is concerned.

<Attachment>

Draft Interface Control Document (ICD) for ATS Message Handling Service (AMHS) in Asia/Pacific Region (Version 1.0)

DRAFT

INTERFACE CONTROL DOCUMENT (ICD)

FOR ATS Message Handling System (AMHS)

in Asia/Pacific Region

Version 1.0

(intentionally blank)

DOCUMENT CONTROL LOG

Version	Revised contents	Date
0.1	Newly developed. Presented at APANPIRG/ATNTTF WG A & B Combined Meeting in Honolulu, Hawaii, November 2000 (WP2-11).	25 October, 2000
0.2	Revised according to the comment at the Hawaii meeting; - New Phase-3 is inserted after Phase-2 in Clause 1.3 and in Figure 1. - AMHS Support to Data TPDU numbering (extended) is changed from “no” to “yes” in Table 5 in Clause 2.3.1. (clerical error) Revised as follows; - Table of Document Control Log is added in this page. - Figure 1 is revised by adding State C and some connections. - Explanation of Figure 1 is revised. - Correction of grammatical errors.	22 November, 2000
0.3	“Table 2 AMHS Requirements” is added in Clause 2.2.1.2.	26 December, 2000
0.4	Revised according to the comment by members; - Minor correction of third sentence in 1.3 Network configuration, 3) Phase-3. (Comment by FAA on 4 January, 2001.)	9 January, 2001
1.0	Presented at 3 rd ATN Transition Task Force Meeting after cleaning up the revision marks in version 0.4.	28 March 2001

TABLE OF CONTENTS

1. Guidance for AMHS specification
 - 1.1 Introduction
 - 1.2 AMHS Functions
 - 1.3 Network Configuration
 - 1.4 Protocol Specification Overview
2. AMHS Specifications
 - 2.1 AMHS Specifications
 - 2.2 Upper Layer Specifications
 - 2.3 Lower Layer Specifications

Attachment: PICS of AMHS

<References>

- 1) ICAO Doc 9705/AN-956, "MANUAL OF TECHNICAL PROVISIONS FOR THE AERONAUTICAL TELECOMMUNICATION NETWORK (ATN)", SECOND EDITION (Effective 10 December 1999)
 - a) Sub-Volume I : 1.1 "DEFINITIONS AND REFERENCES"
 - b) Sub-Volume III : 3.1 "ATS Message Handling Services (ATSMHS)"
 - c) Sub-Volume V : "Internet Communication Service"
- 2) ICAO Doc 9739/AN-961 Comprehensive ATN Manual (Edition 1)
- 3) ICAO Annex 10, Vol. II, Fifth edition (July 1995)

NOTE: This ICD does not include the additional features such as CIDIN/AMHS Gateway, Security and Directory Service which are added in ICAO Doc 9705/AN-965, THIRD EDITION. This ICD may be enhanced to include such additional features in the future.

1. Guidance for AMHS specification

1.1 Introduction

This document is the Interface Control Document (ICD) based on which the AMHS is to be implemented in Asia/Pacific Region. It is essential to implement AMHS system which is fully complied with ICAO ATN SARPs (Doc9705) as well as this ICD, in order to keep the interoperability between States and to have flexibility in the future introduction of ATN applications. For better understanding, before the description of detailed specification, the following clauses give guidance for AMHS specification such as AMHS Functions, Network Configuration and Protocol Specification Overview.

1.2 AMHS Functions

As for the AMHS, there are mainly two End Systems defined: AFTN/AMHS Gateway and ATS Message Server (with ATS Message User Agent). As for early implementation of AMHS, it is expected to implement AFTN/AMHS Gateway since there may be AFTN connections remained within and/or outside State. However, it is also possible to replace AFTN with ATS Message Server (with User Agent) all at once when there will be no AFTN connection both within and outside State after the replacement.

NOTE: ATN Pass-Through Service (AFTN/ATN Type A Gateway) should not be implemented since it cannot be connected with AFTN/AMHS Gateway nor ATS Message Server. The description concerning the ATN Pass-Through Service has been deleted in the Third Edition of ICAO ATN SARPs. In addition, CIDIN/AMHS Gateway has been added as a new End System of AMHS in the Third Edition SARPs.

Even in the case that all the AFTN connections within States (i.e. domestic communication) are replaced with X.400 (MHS and NOT AMHS) connections, the connections outside State (i.e. international communication using ATN Routers) are to be complied with ICAO ATN SARPs and this ICD. When the domestic communication is implemented prior to the international communication, the domestic MHS Server may be so modified as to comply with ATN.

1.3 Network Configuration

The network configuration will grow according to the level of implementation of AMHS. The followings are the typical phases of AMHS implementation. The network configuration of each phase is shown in Figure 1.

1) Phase-1

AFTN connections are currently used for both all the domestic communication within State and all the international communication with other States.

2) Phase-2

AFTN/AMHS Gateways and ATN Routers are implemented for the international communication between at least two States.

3) Phase-3

Domestic AFTN connections are replaced with AMHS connections within State. AFTN/AMHS Gateway is enhanced to ATS Message Server. However, AFTN/AMHS Gateway System/Function remains for the AFTN connections (like State C in Figure). There may be AMHS-AMHS direct international communication (via ATN Routers) with the other States.

NOTE: It is a local matter whether to implement ATS Message Server and AFTN/AMHS Gateway in separated computer systems or in one computer system.

4) Phase-4

All the States in the Region implement either ATS Message Server or AFTN/AMHS Gateway and all the international communications are done by AMHS. There may be AMHS-AMHS direct international communication (via ATN Routers) with the other States.

5) Phase-5

AMHS connections are fully applied to both the domestic communication within States and the international communication with all the neighbor States.

6) Phase-6

Full ATN connection is applied within the Region. All the data of ATN applications including AMHS are exchanged through ATN Routers.

The systems in Figure 1 are as follows;


AMHS Gateway : AFTN/AMHS Gateway

AMHS Server : ATS Message Server (enhanced from AFTN/AMHS Gateway)

End Systems of ATN Applications


: End Systems of ATN applications including Air/Ground applications such as CM (Context Management), ADS (Automatic Dependent Surveillance), CPDLC (Controller and Pilot Data Link Communication) or FIS (Flight Information Service), whose ground to ground data is forwarded through the same ground network using ATN routers. The system may consist of computer(s) and/or equipment for ATN application for communication, ATM application, Human Machine Interface and maintenance.

AFTN System : AFTN host computer, domestic AFTN network and distributed AFTN systems/terminals (as shown below for an example)





AMHS System : domestic AMHS (or X.400 MHS) network, distributed AMHS (or X.400 MHS) systems/terminals (User Agents) and AMHS (or X.400 MHS) local servers if necessary (as shown below for an example)

AMHS domestic connections




X.400 MHS domestic connections






(1) Phase-1
Current AFTN connections




(2) Phase-2
Implementation of AFTN/AMHS Gateways and ATN Routers

Figure 1. AMHS Network Configuration (to be continued)



(3) Phase-3


Implementation of ATS Message Server and AMHS connections within State




(4) Phase-4

Full AMHS international connections

Figure 1. AMHS Network Configuration (to be continued)



(5) Phase-5
Full AMHS connections



(6) Phase-6
Full ATN connections

Figure 1. AMHS Network Configuration

1.4 Protocol Specification Overview

1.4.1 Protocol Stack of AMHS and ATN Router

The following figure shows the OSI protocol stack of ES and IS in the ATN. AMHS is ES and ATN Router is IS.




Figure 2. OSI Protocol Stack of ES and IS

1.4.2 AMHS Protocol Specification

The followings are the standards and/or ICAO Doc 9705/AN-956 descriptions of protocols at each OSI protocol layer, with which AMHS should comply.

(1) Application Layer

Application Layer is composed of MHS, RTSE, and ACSE.

MHS should comply with ITU-T X.400 (1988) and the additional requirements specified in 3.1 “ATS MESSAGE HANDLING SERVICE” of ICAO Doc 9705/AN-956. MHS supports all the mandatory elements of AMH11 and AMH21, and also supports the DL functional group.

RTSE should comply with ISO 9066-2 and support the mandatory services listed below among the services specified in ISO/IEC ISP 10611-2.

RT-OPEN
RT-CLOSE
RT-TRANSFER
RT-P-ABORT
RT-U-ABORT

ACSE should comply with ISO 8650 and support the mandatory functions of normal mode specified in ISO/IEC 10611-2. Moreover, the application-context name, which is used as a parameter of A-ASSOCIATE, should comply with ISO/IEC 10021-6.

(2) Presentation Layer

Presentation Layer should comply with ISO 8823 and support mandatory functions of normal mode specified in ISO/IEC ISP 10611-2.

(3) Session Layer

Session Layer should comply with ISO 8327 and support functional units listed below which are specified in ICAO Comprehensive ATN Manual and ISO/IEC ISP 10611-2.

Kernel
half duplex
exceptions
minor synchronize
activity management

(4) Transport Layer

COTP (Connection Oriented Transport Protocol) specified in ICAO Doc 9705/AN-956 should be used. COTP should comply with ISO/IEC8073 Class 4 and 5.5 “TRANSPORT SERVICE AND PROTOCOL SPECIFICATION” of ICAO Doc 9705/AN-956. The following functions should be supported as specified mandatory by ICAO Doc 9705/AN-956.

Both Initiating CR TPDU and Responding to CR TPDU	
Function of Non-use of checksum	
CR/CC/DR/DC/DT/ED/AK/EA/ER TPDUs	
Optional Parameters of CR/CC TPDUs	
	TSAP-ID (Transport-Selector designation)
	Additional option selection parameter
	Priority
	Acknowledgment time Negotiation
	Inactivity timer Negotiation
Optional Parameters of AK TPDU	
	Flow control confirmation
	Subsequence number

(5) Network Layer

The connection between AMHS and ATN Router may be a local matter. However, CLNP (Connectionless Network Protocol) should be used for the communication of subnetwork with Transport Layer. CLNP should comply with ISO/IEC8473 and 5.6 “INTERNETWORK SERVICE AND PROTOCOL SPECIFICATION” of ICAO Doc 9705/AN-956. The following functions should be supported as specified mandatory by ICAO Doc 9705/AN-956.

Security Parameter
Partial Route Recording
Priority
QoS Maintenance Information
Congestion Notification
X.25 Priority procedure

CLNP uses SNDCF (Subnetwork Dependent Convergence Function) over the subnetwork. SNDCF should comply with ISO/IEC 8473-3 and 5.7 "SPECIFICATION OF SUBNETWORK DEPENDENT CONVERGENCE FUNCTIONS" of ICAO Doc 9705/AN-956. Only ES-IS in compliance with ISO/IEC9543 is used for addressing. Routing protocol IDRP will not be supported.

(6) Data Link Layer

The connection between AMHS and ATN Router may be a local matter.

(7) Physical Layer

The connection between AMHS and ATN Router may be a local matter.

1.4.3 ATN Router Protocol Specification

(1) Network Layer

The connection uses ITU-T Recommendation X.25. Network Layer procedures should comply with Packet Layer procedures specified in ITU-T X.25 (1984). CLNP used to support Transport Layer should comply with ISO/IEC8473 and 5.6 "INTERNETWORK SERVICE AND PROTOCOL SPECIFICATION" of ICAO Doc 9705/AN-956.

The following functions should be supported as specified mandatory by ICAO Doc 9705/AN-956.

Security Parameter
Partial Route Recording
Priority
QoS Maintenance
Congestion Notification

CLNP uses SNDCF over the subnetwork. SNDCF should comply with ISO/IEC8473-3 and 5.7 "SPECIFICATION OF SUBNETWORK DEPENDENT CONVERGENCE FUNCTIONS" of ICAO Doc 9705/AN-956.

IDRP protocol is used for the exchange of routing information between ATN Routers between States. The IDRP should have the functions specified in ISO/IEC10747 and ICAO Doc 9705/AN-956. The support of IS-IS protocol and ES-IS protocol is a local matter.

NOTE: Regarding Partial Route Recording, considering early implementation, ATN Router may not put its NET in Partial Route Recording field of CLNP Header, although ATN Router relays CLNP PDUs supporting this function

(2) Data Link Layer

X.25 Data Link Layer procedures should comply with LAPB procedure specified in ITU-T X.25 (1984).

(3) Physical Layer

X.25 Physical Layer should be used. X.25 Physical Layer should comply with ITU-T X.25 (1984).

2. AMHS Specification

2.1 AMHS Specifications

Set up condition of each parameter for both AFTN/AMHS Gateway and ATS Message Server is specified in the attachment in the form of PICS. (Attachment: PICS of AMHS)

When only ATS Message Server without AFTN/AMHS Gateway is implemented, some part (the column “AMHS Action”) in the PICS can be ignored.

2.2 Upper Layer Specifications

2.2.1 Protocol Specification

Support Level is specified below:

- m : mandatory support
- o : optional support
- c : conditional support
- i : out of scope
- : not applicable

The column “AMHS use” states whether each item is “used (yes)” or “not used (no)”.

2.2.1.1. ACSE

ACSE should comply with ISO 8650 and support the level specified in ISO/IEC ISP 11188-1(1995).

PICS Proforma Reference	Name of Item	Normative reference	Status	Profile	AMHS Use
A.A.7/4	support operation of Session version 2	9.2.1	o	C11	Yes

C11 : if A.A.7/1 then m else i

NOTE: The relation between the Initiator/responder roles of ACSE, presentation and session in specified in 2.2.2 and 2.2.3.

2.2.1.2. Presentation PRL

Presentation PRL should comply with ISO 8823 and should support the level specified in ISO/IEC ISP 11188-1(1995) and AMHS Requirements.

Table 1 ISO/IEC ISP 11188-1

PICS Proforma Reference	Name of Item	Normative reference	Status	Profile	AMHS Use
P.A.6.1/1	X.410(1984)	2.2.2	o.01	C21	No
P.A.6.1/2	Normal	2.2.2	o.01	C22	Yes
P.A.7.1.1.1/1	Initiator(Presentation connection)		o.03	C23	Yes
P.A.7.1.1.1/2	Responder(Presentation connection)		o.03	C24	Yes
P.A.7.1.1.3/1	Requestor(orderly release)		o.05	C25	Yes
P.A.7.1.1.3/2	Acceptor (orderly release)		o.05	C26	Yes

C21 : if A.A.7/2 then m else i
 C22 : if A.A.7/1 then m else i
 C23 : if A.A.6.1/1 then m else i
 C24 : if A.A.6.1/2 then m else i
 C25 : if A.A.6.2/1 then m else i
 C26 : if A.A.6.2/2 then m else i

Table 2 AMHS Requirements

Name of Item	ISO/IEC 8823-1 Reference	ISO Support	AMHS Use
user-data of CP PPDU	8.2	Either Simply-Encoded-Data or Fully-Encoded-Data	Fully-Encoded-Data
user-data of CPA PPDU	8.2	Either Simply-Encoded-Data or Fully-Encoded-Data	Fully-Encoded-Data
user-data of CPR PPDU	8.2	Either Simply-Encoded-Data or Fully-Encoded-Data	Fully-Encoded-Data
presentation-data-values of PDV-list	8.4.2	Either single-ASN1-type, octet-aligned, or arbitrary	single-ASN1-type

2.2.1.3. Session PRL

Session PRL should comply with ISO 8327 and support the level specified in ISO/IEC ISP 11188-1 (1995).

PICS Proforma Reference	Name of Item	Normative reference	Status	Profile	AMHS Use
S.A.6.2/2	Reuse of transport connection		o	i	Yes
S.A.6.2/4	Extended Concatenation (sending)		o	i	Yes
S.A.6.2/5	Extended Concatenation (receiving)		o	i	Yes
S.A.7.1.1.1/1	initiator (session connection)		o.3	C41	Yes
S.A.7.1.1.1/2	Responder (session connection)		o.3	C42	Yes
S.A.7.1.1.2/1	Requestor (orderly release)		o.4	C43	Yes
S.A.7.1.1.2/2	Acceptor (orderly release)		o.4	C44	Yes
S.A.7.1.1.3/1	Requestor (normal data transfer)		o.5	C45	Yes
S.A.7.1.1.3/2	Acceptor (normal data transfer)		o.5	C46	Yes
S.A.7.1.2/2	Overflow Accept (OA)	9.2.2	c.5,c.6	i,i	No, No
S.A.7.1.2/3	Connection Data Overflow (CDO)	9.2.2	c.5,c.6	i,i	No, No
S.A.7.5.1/1	Requestor (expedited data)		o.6	C47	No
S.A.7.5.1/2	Acceptor (expedited data)		o.6	C48	No
S.A.7.6.1/1	Requestor (typed data)		o.7	C49	No
S.A.7.6.1/2	Acceptor (typed data)		o.7	C50	No
S.A.7.7.1/1	Requestor (capability data)		o.8	C51	No
S.A.7.7.1/2	Acceptor (capability data)		o.8	C52	No
S.A.7.8.1/1	Requestor (minor synchronize)		o.9	C53	Yes
S.A.7.8.1/2	Acceptor (minor synchronize)		o.9	C54	Yes
S.A.7.11.1/1	Requestor (major synchronize)		o.10	C55	No
S.A.7.11.1/2	Acceptor (major synchronize)		o.10	C56	No
S.A.7.14.1.1/1	Requestor (activity start)		o.12	C57	Yes
S.A.7.14.1.1/2	Acceptor (activity start)		o.12	C58	Yes
S.A.7.14.1.2/1	Requestor (activity resume)		o.13	C59	Yes
S.A.7.14.1.2/2	Acceptor (activity resume)		o.13	C60	Yes
S.A.7.14.1.3/1	Requestor (activity interrupt)		o.14	C61	Yes
S.A.7.14.1.3/2	Acceptor (activity interrupt)		o.14	C62	Yes
S.A.7.14.1.4/1	Requestor (activity discard)		o.15	C63	Yes
S.A.7.14.1.4/2	Acceptor (activity discard)		o.15	C64	Yes
S.A.7.14.1.5/1	Requestor (activity end)		o.16	C65	Yes
S.A.7.14.1.5/2	Acceptor (activity end)		o.16	C65	Yes

PICS Proforma Reference	Name of Item	Normative reference	Status	Profile	AMHS Use
S.A.7.14.1.6/1	Requestor (give tokens confirm)		o	C67	Yes
S.A.7.14.1.6/2	Acceptor (give tokens confirm)		o	C68	Yes
S.A.8.1.3.4	Data Overflow Item (CN)	9.2.2	c6, c5	i, i	No, No

C41 : if A.A.6.1/1 then m else i
 C42 : if A.A.6.1/2 then m else i
 C43 : if A.A.6.2/1 then m else i
 C44 : if A.A.6.2/2 then m else i
 C45 : if P.A.7.1.1.2/1 then m else i
 C46 : if P.A.7.1.1.2/2 then m else i
 C47 : if P.A.7.4.4/1 then m else i
 C48 : if P.A.7.4.4/2 then m else i
 C49 : if P.A.7.4.5/1 then m else i
 C50 : if P.A.7.4.5/2 then m else i
 C51 : if P.A.7.4.6/1 then m else i
 C52 : if P.A.7.4.6/2 then m else i
 C53 : if P.A.7.4.7/1 then m else i
 C54 : if P.A.7.4.7/2 then m else i

C55 : if P.A.7.4.10/1 then m else i
 C56 : if P.A.7.4.10/2 then m else i
 C57 : if P.A.7.4.13.1/1 then m else i
 C58 : if P.A.7.4.13.1/2 then m else i
 C59 : if P.A.7.4.13.2/1 then m else i
 C60 : if P.A.7.4.13.2/2 then m else i
 C61 : if P.A.7.4.13.3/1 then m else i
 C62 : if P.A.7.4.13.3.2 then m else i
 C63 : if P.A.7.4.13.4/1 then m else i
 C64 : if P.A.7.4.13.4/2 then m else i
 C65 : if P.A.7.4.13.5/1 then m else i
 C66 : if P.A.7.4.13.5/2 then m else i
 C67 : if P.A.7.4.13.6/1 then m else i
 C68 : if P.A.7.4.13.6/2 then m else i

2.3 Lower Layer Specifications

2.3.1 Protocol Implementation Conformance Statements of COTP

In protocol layer 4, ICS SARPs recommend COTP. The functions of COTP are specified below.

- (1) “ATN Support” indicates that the item is Mandatory (“M”), Option (“O”) or Mandatory implemented and Optionally used (“MO”).
- (2) “AMHS Support” indicates whether the item is Supported (“yes”) or NOT Supported (“no”).
- (3) “AMHS Use” indicates whether the item is Used (“yes”) or NOT Used (“no”) in transfer.

Table 1 Support Class

Class	ATN Support	AMHS Support	AMHS Use
Class 0	O	no	no
Class 1	O	no	no
Class 2	O	no	no
Class 3	O	no	no
Class 4 operation over CONS	O	no	no
Class 4 operation over CLNS	M	yes	yes

Table 2 ATN Requirements

Feature	ATN Support	AMHS Support	AMHS Use
Congestion Avoidance	M	yes	yes
Transport to Network Priority	M	yes	yes
ATN Security Label	M	yes	yes
Configurable Transport Timers	M	yes	yes
Enhanced encoding of Acknowledgment Time Parameter	M	no	no

Table 3 Initiator/Responder Capability

Class	ATN Support	AMHS Support	AMHS Use
Initiating CR TPDU	O	yes	yes
Responding to CR TPDU	O	yes	yes

Table 4 Mandatory Functions

Function	ATN Support	AMHS Support	AMHS Use
TPDU transfer	M	yes	yes
Segmenting	M	yes	yes
Reassembling	M	yes	yes
Separation	M	yes	yes
Connection establishment	M	yes	yes
Connection refusal	M	yes	yes
Data TPDU numbering (normal)	M	yes	yes
Retention and acknowledgement of TPDUs (AK)	M	yes	yes
Explicit flow control	M	yes	yes
Checksum	M	yes	yes
Frozen references	M	yes	yes
Retransmission on time-out	M	yes	yes
Resequencing	M	yes	yes
Inactivity control	M	yes	yes

Table 5 Optional Functions

Feature	ATN Support	AMHS Support	AMHS Use
Data TPDU numbering (extended)	O	yes	yes
Non-use of checksum	M	yes	yes
Concatenation	O	no	no
Retention and acknowledgement of TPDUs Use of selective acknowledgement	O	no	no
Retention and acknowledgement of TPDUs Use of request acknowledgement	O	no	no

Table 6 Supported TPDU

TPDUs		ATN Support	AMHS Support	AMHS Use
CR	supported on transmission	M	yes	yes
CR	supported on receipt	M	yes	yes
CC	supported on transmission	M	yes	yes
CC	supported on receipt	M	yes	yes
DR	supported on transmission	M	yes	yes
DR	supported on receipt	M	yes	yes
DC	supported on transmission	M	yes	yes
DC	supported on receipt	M	yes	yes
DT	supported on transmission	M	yes	yes
DT	supported on receipt	M	yes	yes
ED	supported on transmission	MO	no	no
ED	supported on receipt	MO	no	no
AK	supported on transmission	M	yes	yes
AK	supported on receipt	M	yes	yes
EA	supported on transmission	MO	no	no
EA	supported on receipt	MO	no	no
ER	supported on receipt	O	yes	yes

Table 7 Parameter Values for CR TPDU

Feature	ATN Support	AMHS Support	AMHS Use
Bits 8 and 7 in the additional options selection parameter of a CR TPDU set to zero	M	yes	yes

Table 8 Optional Parameter for a CR TPDU

Supported parameters	ATN Support	AMHS Support	AMHS Use
Called Transport-Selector	M	yes	yes
Calling Transport-Selector	M	yes	yes
TPDU size	O	no	no
Version Number	O	no	no
Protection parameters	O	no	no
Additional option selection	M	yes	yes
Throughput	O	no	no
Residual error rate	O	no	no
Priority	M	yes	yes
Transit delay	O	no	no
Acknowledgement time	M	yes	yes
Preferred maximum TPDU size	O	no	no
Inactivity timer	M	yes	yes

Table 9 Optional Parameter for a CC TPDU

Supported parameters	ATN Support	AMHS Support	AMHS Use
Called Transport-Selector	M	yes	yes
Calling Transport-Selector	M	yes	yes
TPDU size	O	no	no
Protection parameters	O	no	no
Additional option selection	M	yes	yes
Throughput	O	no	no
Residual error rate	O	no	no
Priority	M	yes	yes
Transit delay	O	no	no
Acknowledgement time	M	yes	yes
Preferred maximum TPDU size	O	no	no
Inactivity timer	M	yes	yes

Table 10 Optional Parameter for a DR TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Additional information	O	no	no

Table 11 Optional Parameter for a DT TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Request of acknowledgement	O	no	no

Table 12 Optional Parameter for an AK TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Flow control confirmation	M	yes	yes

Table 13 the Subsequence Number Parameter in the AK TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Subsequence number	M	yes	yes

Table 14 the Selective Acknowledgement Parameter in the AK TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Selective acknowledgement parameters	O	no	no

Table 15 Optional Parameter for an ER TPDU

Supported parameter	ATN Support	AMHS Support	AMHS Use
Invalid TPDU	O	no	no

Table 16 User Data in Issued TPDUs

User Data	ATN Support	AMHS Support	AMHS Use
User data of up to 32 octets in a CR with preferred class 4 ?	M	yes	yes
User data of up to 32 octets in a CC ?	M	yes	yes
User data of up to 64 octets in a DR ?	M	yes	yes

Table 17 User Data in Received TPDUs

User Data	ATN Support	AMHS Support	AMHS Use
32 octets of user data in a CC TPDU ?	M	yes	yes
64 octets of user data in a DR TPDU ?	M	yes	yes
32 octets of user data in a CR TPDU ?	M	yes	yes

Table 18 Class Negotiation - Initiator

Feature	ATN Support	AMHS Support	AMHS Use
The preferred class in the CR TPDU may contain any of the classes supported by the implementation	Class 4	Class 4	Class 4

Table 19 The table below specifies valid alternative classes

Preferred class	ATN Support	AMHS Support	AMHS Use
Class 4 over CLNS	None	None	None

Table 20 Class negotiation - responder side

Preferred class	ATN Support	AMHS Support	AMHS Use
What classes can you respond with if CR proposes only class 4?	Class 4	Class 4	Class 4
What classes can you respond with if CR proposes class 4 as preferred class and the alternative class parameter is present?	Class 4	Class 4	Class 4

Table 21 TPDU Size Negotiation

TPDU Size	ATN Support	AMHS Support	AMHS Use
If maximum TPDU size is proposed in a CR TPDU then the initiator shall support all TPDU sizes from 128 octets to the maximum proposed	M	yes	yes
If the preferred maximum TPDU size parameter is used in a CR TPDU then the initiator shall support all TPDU sizes, except 0, that are multiples of 128 octets up to the preferred maximum proposed	M	yes	yes
What is the largest value of the preferred maximum TPDU size parameter in a CR TPDU?	any multiple of 128 octets	any multiple of 128 octets	any multiple of 128 octets
What is the largest value of the preferred maximum TPDU size parameter in a CC TPDU?	any multiple of 128 octets	any multiple of 128 octets	any multiple of 128 octets
What is the largest value of the maximum TPDU size parameter in a CR TPDU with preferred class 4?	One of 128, 256, 512, 1024, 2048	One of 128, 256, 512, 1024, 2048	One of 128, 256, 512, 1024, 2048
What is the largest value of the maximum TPDU size parameter which may be sent in the CC TPDU when class 4 is selected?	128, 256, 512, 1024, 2048	128, 256, 512, 1024, 2048	128, 256, 512, 1024, 2048

Table 22 Use of Extended Format

Extended format	ATN Support	AMHS Support	AMHS Use
What formats can you propose in the CR TPDU in class 4?	normal, extended	normal	extended
What formats can you select in CC when extended has been proposed in CR in class 4?	normal, extended	normal	extended

Table 23 Expedited data Transport service

Expedited data	ATN Support	AMHS Support	AMHS Use
Is the expedited data indication supported in CR and CC TPDU?	O	no	no

Table 24 Non-use of Checksum

Non-use of checksum	ATN Support	AMHS Support	AMHS Use
What proposals can you make in the CR?	non-use, use	use	non-use
What proposals can you make in CC when non-use of checksum has been proposed in CR?	non-use, use	use	non-use

Table 25 Use of selective acknowledgement

Selective Acknowledgement	ATN Support	AMHS Support	AMHS Use
Is use of selective acknowledgement proposed in CR TPDU's ?	O	no	no
Is use of selective acknowledgement selected in a CC when it has been proposed in a CR ?	O	no	no

Table 26 Use of Request Acknowledgement

Request of Acknowledgement	ATN Support	AMHS Support	AMHS Use
Is use of request of acknowledgement proposed in CR TPDU's ?	O	no	no
Is use of request of acknowledgement selected in a CC when it has been proposed in a CR ?	O	no	no

Table 27 Action on Detection of a Protocol Error

Item	ATN Support	AMHS Support	AMHS Use
Class 4 over CLNS	ER, DR, Discard	ER, DR, Discard	ER, DR, Discard

Table 28 Actions on receipt of an invalid or undefined parameter in a CR TPDU

Event	ATN Support	AMHS Support	AMHS Use
A parameter not defined in ISO/IEC 8073 shall be ignored	M	yes	yes
An invalid value in the alternative protocol class parameter shall be treated as a protocol error	M	yes	yes
An invalid value in the class and option parameter shall be treated as a protocol error	M	yes	yes
On receipt of the additional option selection parameter bits 8 to 7, and bits 6 to 1 if not meaningful for the proposed class, shall be ignored	M	yes	yes
On receipt of the class option parameter bits 4 to 1 if not meaningful for the proposed class shall be ignored	M	yes	yes
What action is supported on receipt of a parameter defined in ISO 8073 (other than those covered above) and having an invalid value ?	Ignore, Protocol Error	Ignore, Protocol Error	Ignore, Protocol Error

Table 29 Actions on receipt of an invalid or undefined parameter in a TPDU other than a CR

Event	ATN Support	AMHS Support	AMHS Use
A parameter not defined in ISO/IEC 8073 shall be treated as a protocol error	M	yes	yes
A parameter which has an invalid value as defined in ISO/IEC 8073 shall be treated as a protocol error	M	yes	yes
A TPDU received with a checksum which does not satisfy the defined formula shall be discarded	M	yes	yes

Table 30 Class 4 Timers and Protocol Parameters

Parameters	ATN Support	AMHS Support	AMHS Use
T1 (Local Retransmission)	M	yes	yes
N (Maximum Transmission)	M	yes	yes
I _L (Local Inactivity Time)	M	yes	yes
W (Window Update)	M	yes	yes
L (Frozen Reference Time)	M	yes	yes
R (Persistence)	O	no	no
M _{LR} (NSDU Lifetime)	O	no	no
M _{RL} (NSDU Lifetime)	O	no	no
E _{LR} (Maximum Transit Delay)	O	no	no
E _{RL} (Maximum Transit Delay)	O	no	no
A _L (Acknowledgement Time)	M	yes	yes
A _R (Acknowledgement Time)	M	yes	yes
I _R (Remote Inactivity Time)	M	yes	yes
Does IUT support optional timer TS2 when operating in class 4?	O	no	no

2.3.2 Parameter values

The range of values set in the protocol layer 3 and 4 of AMHS are specified below. The actual values are to be determined through bilateral agreement on the AMHS systems connected each other.

The following table shows only the parameters, which may influence interoperability. Other parameters are also to be determined through the bilateral agreement.

Parameters set or set to the frame are shown in the following table.

Name	Lower	Upper
Local Retransmission Time(T1){COTP}[SEC]	0.5	30
Window Time(W){COTP}[SEC]	10	20
Maximum Number of Transmissions(N){COTP}	4	8
Maximum size of TPDU{COTP}[OCTETS]	1024	1024
Lifetime{CLNS}[IN UNITS OF 500MSEC]	10	30
Reassembly Time{CLNS}[IN UNITS OF 500MSEC]	10	30

Attachment: PICS of AMHS

This attachment specifies the PICS of AMHS for both AFTN/AMHS Gateway and ATS Message Server. When only ATS Message Server without AFTN/AMHS Gateway is implemented, the column “AMHS Action” in the tables can be ignored.

Followings are the contents included in this attachment.

CONTENTS

INTRODUCTION

1. Message Transfer Envelope for IPM

Table 1.1 Message Transfer Envelope (IPM)

Table 1.2 Common Data Types

Table 1.3 Extension Data Types

2. IPM

Table 2.1 IPM

Table 2.2 IPM Support of the Basic ATS Message Service

3. Message Transfer Envelope for IPN

Table 3.1 Message Transfer Envelope (IPN)

Table 3.2 Common Data Types

Table 3.3 Extension Data Types

4. IPN

Table 4.1 IPN

Table 4.2 OR Descriptor

5. Report Transfer Envelope

Table 5.1 Report Transfer Envelope

Table 5.2 Common Data Types

6. Probe Transfer Envelope

Table 6.1 Probe Transfer Envelope

Table 6.2 Common Data Types

INTRODUCTION

Description of each column in the table header is as follows;

"support" indicates the specification in the ISP and in the SARPs (ICAO ATN SARPs) respectively. The contents in the table are extracted from the ISP and the SARPs.

"AMHS-Action" indicates the specified action at Origination and at Reception in the SARPs. Please refer to the "Action" column in the SARPs. The contents in the table are extracted from the SARPs.

"AMHS-support" indicates the status of AMHS to be implemented.

"Detailed Action" indicates the detailed action specified in the SARPs, when it is described in the SARPs. The contents in the table are extracted from the SARPs.

"Origination" and "Reception" are also the terms described in the SARPs.

Definition of each support level and actions is specified in the table below :

support level and actions	Origination	Reception
M	The value is always set.	It is mandatory to set the value.
O	The value is set on conditions.	When the value is set, service is provided.
M-	-	Only the minimal support of this element. 1) allowed to set the value but no service provided 2) value is transparent when relayed
X	The value is not set.	When the value exists, it is considered to be an error.
T	Translated.	Translated.
G	Generated.	-
G1	Optionally generated.	-
G2	Conditionally generated.	-
D	-	Discarded.

1. Message Transfer Envelope for IPM

Table 1.1 Message Transfer Envelope
(Based on : ATSMHS SARPs Table 3.1.2-6 for O, Table 3.1.2-12 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	MessageTransferEnvelope	M	M	T	T	M	M	-			
1.1	per message fields										
1.1.1	message-identifier	M	M	G	D	M	M	-			See Table 2/1
1.1.2	originator-name	M	M	T	T	M	M	-			
1.1.3	original-encoded-information-types	O	M	G	D	M	M	-			
1.1.4	content-type	M	M	G	D	M	M	-	BuiltInContentType is set the abstract value "interpersonal-messaging-1984(2)"	If the value of BuiltInContentType is neither interpersonal-messaging-1984(2) nor interpersonal-messaging-1988(22), then generate NDR[NDRC=1,NDDC=15].	
1.1.5	content-identifier	O	M-	G	D	M	M-	<=16			"G"
1.1.6	priority	M	M	T	D	M	M	-			
1.1.7	per-message-indicators	M	M	G	D	M	M	-			See Table 1.2/4
1.1.8	deferred-delivery-time	O	M-	G	D	M	M-	-			
1.1.9	per-domain-bilateral-information	O	M-	X	D	X	M-	-			
1.1.10	trace-information	M	M	G	D	M	M	-			
1.1.11	extensions	M	M	G	D	M	O	-			In X.400, if the value doesn't exist, it is considered to be not selected.

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
	type	M	M	G	D	M	M	-			Only supports "standard-extension".
	criticality	M	M	G	D	M	M	-			In X.400, if the value doesn't exist, it is considered to be not selected.
	value	M	M	M	D	M	M	-	Set the value of "internal-trace-information"		
1.1.11.1	recipient-reassignment-prohibited	O	M-	X	D	X	M-	-			
1.1.11.2	dl-extension-prohibited	O	M-	X	D	X	M-	-			
1.1.11.3	conversion-with-loss-prohibited	O	M-	X	D	X	M-	-			
1.1.11.4	latest-delivery-time	O	M-	X	D	X	O	-		If this exists, and the current time exceeds the value, then generate NDR[NDRC=1,NDDC=5].	
1.1.11.5	originator-return-address	O	M-	X	D	X	M-	-			
1.1.11.6	originator-certificate	O	M-	X	X	X	M-/X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=18].	
1.1.11.7	content-confidentiality-algorithm-identifier	O	M-	X	X	X	M-/X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.1.11.8	message-origin-authentication-check	O	M-	X	X	X	M-/X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=18].	
1.1.11.9	message-security-label	O	M-	X	X	X	M-/X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=18].	
1.1.11.10	content-correlator	O	M-	X	D	X	M-	<= 512			
1.1.11.11	dl-expansion-history	O	M-	X	D	X	O	-			
1.1.11.12	internal-trace-information	O	M-	G	D	M	M-	-			See Table 3/5
1.2	per-recipient-fields	M	M	T	T	M	M	-		Support maximum of 21 parameters. (This number may be changed when negotiated.)	
1.2.1	recipient-name	M	M	T	T	M	M	-	Set the values of the recipient's MF (or XF) address.		
1.2.2	originally-specified-recipient-number	M	M	G	D	M	M	-	Set the value which comply with 12.2.1.1.1.5 of ISO/IEC 10021-4. (set continuous number from 1 to the first recipient)		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.3	per-recipient-indicators	M	M	G	D	M	M	-	Set following value : responsibility=responsible(1) originating-MTA-reportrequest=non-delivery-report(01) originator-report-request=non-delivery-report(01)	For the parameter "per-recipients-fields", only "responsibility=responsible (1)" is relayed or delivered. Reportrequest=delivery-request(10) is ignored.	BITSTRING
1.2.4	explicit-conversion	O	M-	X	D	X	M-	-			
1.2.5	extensions	M	M-	X	D	X	M	-			In X.400, if the value doesn't exist, it is considered to be not selected.
	type	M	M	-	D	X	M	-			Only supports "standard-extension".
	criticality	M	M	-	D	X	M	-		If the value does not exist, all bits are considered to be OFF.	BITSTRING for-submission(0) for-deliver(1) for-transfer(2)
	value	M	M	-	D	X	M	-			
1.2.5.1	originator-requested-alternate-recipient	O	M-	-	D	X	M-	-			
1.2.5.2	requested-delivery-method	O	M-	-	D	X	M-	-			
1.2.5.3	physical-forwarding-prohibited	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.5.4	physical-forwarding-address-request	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.5	physical-delivery-modes	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.6	registered-mail-type	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.7	recipient-number-for-advice	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.8	physical-redirection-attributes	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.5.9	physical-delivery-report-request	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.10	message-token	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.11	content-integrity-check	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.12	proof-of-delivery-request	O	M-	-	X	X	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.13	redirection-history	O	M-	-	D	X	M-	-			
2	content	M	M	T	T	M	M	-	Set the generated IPM.		

Table 1.2 Common Data Types
(Based on : ATSMHS SARPs Table 3.1.2-6 for O, Table 3.1.2-12 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	MTS-Identifier										
1.1	global-domain-identifier	M	M	G	D	M	M	-			
1.2	local-identifier	M	M	G	D	M	M	<=32	Set the characters which identifies message in ia-5 characters.		
2	GlobalDomainIdentifier										
2.1	country-name	M	M	G	D	M	M	2 or 3	Set the country name of AMHS management domain.		
2.2	administration-domain-name	M	M	G	D	M	M	<=16	Set the AMHS management domain name.		
2.3	private-domain-identifier	O	M-	X	D	X	M-	<=16			The value of this parameter may be used in the future.
3	EncodedInformationTypes										
3.1	built-in-encoded-information-types	M	M	G	D	M	M	-	Set the value of "ia5-text(2)=1"		BITSTRING
3.2	non-basic parameters	O	M-	X	D	X	M-	-			
3.3	extended-encoded-information-types	O	M	X	D	X	O	-			
4.	PerMessageIndicators	M	M	G	D	M	M	-			BITSTRING In X.400, if the value doesn't exist, all bits are considered to be OFF.
4.1	disclosure-of-other-recipients(0)	M	M	G	D	M	M	-	Set the abstract value "disclosure-of-other-recipients-prohibited(0)"		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
4.2	implicit-conversion-prohibited(1)	M	M	G	D	M	M	-	Set the abstract value "implicit-conversion-prohibited(1)"		
4.3	alternate-recipient-allowed(2)	M	M	G	D	M	M	-	Set the abstract value "alternate-recipient-allowed(1)"		
4.4	content-return-request(3)	M	M	G	D	M	M	-	Set the abstract value "content-return-not-requested(0)"	Ignored and considered "content-return-not-requested(0)". However, if error occurs in the ATN component of AMHS and "content-return-request(1)" is set, it is impossible to restrain this service.	
5	PerDomainBilateralInformation	O	M-	X	D	X	M-	-			
6	TraceInformation										
6.1	TraceInformationElement	M	M	G	D	M	M	-			
6.1.1	global-domain-identifier	M	C1	X	D	X	M	-		If the last trace information of this parameter differs from the input MTA, then generate NDR.	
6.1.2	domain-supplied-information	M	M	G	D	M	M	-			
6.1.2.1	arrival-time	M	C2	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message.		
6.1.2.2	routing-action	M	M-	G	D	M	M	-	Set the abstract value of "relayed(0)".		
6.1.2.3	attempted-domain	O	M-	X	D	X	M-	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
6.1.2.4	additional actions	O	M-	X	D	X	M-	-			
6.1.2.4.1	deferred-time	O	M-	X	D	X	M-	-			
6.1.2.4.2	converted-encode-information-types	O	M-	X	D	X	O	-			
6.1.2.4.3	other-actions	O	M-	X	D	X	M-	-			

Table 1.3 Extension Data Types
(Based on : ATSMHS SARPs Table 3.1.2-6 for O, Table 3.1.2-12 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
5	internal-trace-information	O	M-	G	D	M	M-	-			
5.1	global-domain-identifier	M	M	G	D	M	M	<=16	Set the value which identifies AMHS Management Domain.		
5.2	mta-name	M	M	G	D	M	M	<=32	Set the value of mta-name of AMHS.		
5.3	domain-supplied-information	M	M	G	D	M	M	-			
5.3.1	arrival-time	M	M	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message		
5.3.2	routing-action	M	M	G	D	M	M	-	Set the abstract value "relayed(0)"		
5.3.3	attempt-domain	O	C1	X	D	X	M-	-			
5.3.4	additional actions	O	C2	X	D	X	M-	-			
5.3.4.1	deferred-time	O	M-	X	D	X	M-	-			
5.3.4.2	converted-encoded-information-types	O	M-	X	D	X	O	-			
5.3.4.3	other-actions	O	M-	X	D	X	M-	-			

2. IPM

Table 2.1 IPM
(Based on : ATSMHS SARPs Table 3.1.2-5 for O, Table 3.1.2-11 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	Interpersonal message(IPM)	M	M	T	T	M	M	-			
1.1	heading	M	M	T	T	M	M	-			
1.1.1	this-IPM	M	M	T	D	M	M	-			
1.1.1.1	user	O	M	T	D	M	M-	-	Set the same value as the originator.		
1.1.1.2	user-relative-identifier	M	M	G	D	M	M	<=64			Set the value which identifies this IPM in less than 64 octets.
1.1.2	originator	O	M	T	D	M	M-		Set the originator XF address converted from AF address of AFTN message.		
1.1.3	authorizing-users	O	O	X	D	X	M-	-			
1.1.4	primary-recipients	O	M	T	D	M	O	-		At least one of the primary-recipients, copy-recipients, or blind-copy-recipients is mandatory.	
1.1.4.1	RecipientSpecifier	M	M	T	D	M	M	-			If the value of this parameter is as same as P1, then maximum number is 21.
1.1.4.2	recipient	M	M	T	D	M	M	-	Set the recipient XF address converted from AF address of AFTN message.		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.1.4.3	notification-requests	O	M	T	D	M	M	-	Set the bit of rn and nrn ON if and only if the value of ATS-priority-indicator is SS. (In other cases, both bits are not ON.)	If ATS-priority-indicator is SS, and value of notification of the element "primary-recipient", "copy-recipient", "blind-copy-recipient" is different from "rn", and the value of per-recipient-fields is "responsible", then it is logged as an error.	According to X.400, if this parameter does not exist, all bits are considered OFF.
1.1.4.3.1	rn(0)	O	O	T	D	M	O	-			
1.1.4.3.2	nrn(1)	O	M	T	D	M	M-	-		Ignored.	
1.1.4.3.3	ipm-return(2)	O	O	X	D	X	M-	-	Always set OFF.	Ignored.	
1.1.5	copy-recipients	O	M	X	D	X	O	-	Not set.	Processed as same as primary-recipients.	
1.1.6	blind-copy-recipients	O	M	X	D	X	O	-	Not set.	Processed as same as primary-recipients.	
1.1.7	replied-to-IPM	O	M	X	D	X	M-	-			
1.1.8	obsoleted-IPMs	O	M	X	D	X	M-	-			
1.1.9	related-IPMs	O	M	X	D	X	M-	-			
1.1.10	subject	O	M	G2	D	O	M-	<=128			
1.1.11	expiry-time	O	M	X	D	X	M-	-			
1.1.12	reply-time	O	M	X	D	X	M-	-			
1.1.13	reply-recipients	O	O	X	D	X	M-	-			
1.1.14	importance	O	O	X	D	X	M-	-			
1.1.15	sensitivity	O	O	X	D	X	M-	-			
1.1.16	auto-forwarded	O	O	X	D	X	M-	-			
1.1.17	extensions	O	O	X	D	X	M-	-			
1.1.17.1	incomplete-copy	O	O	X	D	X	M-	-			
1.1.17.2	langages	O	O	X	D	X	M-	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.1.17.3	auto-submitted	O	O	X	D	X	M-	-			
1.2	IPM BODY	M	M	M	M	M	M	-		One of the ia5-text, ia5-text-body-part, or general-text-body-part has to be set.	
1.2.1	ia5-text	O	M	T	T	M	O	-			
1.2.1.1	parameters	M	M	G	D	M	M	-			
1.2.1.1.1	repertoire	M	M	G	D	M	M	-	Set the value IA5(5).		
1.2..1.2	data	M	M	T	T	M	M	-			
1.2.2	voice	I	X	X	X	X	X	-			
1.2.3	g3-facsimile	O	X	X	X	X	X	-			
1.2.4	g4-class-1	O	X	X	X	X	X	-			
1.2.5	teletex	O	X	X	X	X	X	-			
1.2.6	videotex	O	X	X	X	X	X	-			
1.2.7	encrypted	I	X	X	X	X	X	-			
1.2.8	message	O	X	X	X	X	X	-			
1.2.9	mixed-mode	O	X	X	X	X	X	-			
1.2.10	bilaterally-defined	O	X	X	X	X	X	-			
1.2.11	nationally-defined	O	X	X	X	X	X	-			
1.2.12	externally-defined	O	X	X	X	X	X	-			
1.3	Extended Body Part										
1.3.1	ia5-text-body-part	O	X	X	T	X	O	-			
1.3.2	g3-facsimile-body-part	O	X	X	X	X	X	-			
1.3.3	g4-class1-body-part	O	X	X	X	X	X	-			
1.3.4	teletex-body-part	O	X	X	X	X	X	-			
1.3.5	videotex-body-part	O	X	X	X	X	X	-			
1.3.6	encrypt-body-part	I	X	X	X	X	X	-			
1.3.7	message-body-part	O	X	X	X	X	X	-			
1.3.8	mixed-mode-body-part	O	X	X	X	X	X	-			
1.3.9	bilaterally-defined-body-part	O	X	X	X	X	X	-			
1.3.10	nationally-defined-body-part	O	X	X	X	X	X	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.3.11	general-text-body-part	O	X	X	T	X	O	-			
1.3.12	file-transfer-body-part	O	X	X	X	X	X	-			
1.3.13	voice-body-part	I	X	X	X	X	X	-			
1.3.14	oda-body-part	O	X	X	X	X	X	-			

Table 2.2 IPM Support of the Basic ATS Message Service
(Based on : ATSMHS SARPs Table 3.1.2-5 for O, Table 3.1.2-11 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	ATS-Message-Header	-	M	T	T	M	M	-			
1.1	start- of heading	-	M	G	-	M	M	-	Set (SOH)		
1.2	ATS-Message-Priority	-	M	T	T	M	M	-			
1.2.1	priority-prompt	-	M	G	-	M	M	-	Set the value "PRI:(single space)".		
1.2.2	priority-indicator	-	M	T	T	M	M	-			
1.2.3	priority-separater	-	M	G	-	M	M	-	Set (CR)(LF)		
1.3	ATS-Message-Filing-Time	-	M	T	T	M	M	-			
1.3.1	filing-time-prompt	-	M	G	-	M	M	-	Set the value "FT:(single space)".		
1.3.2	filing-time	-	M	T	T	M	M	-			
1.3.3	filing-time-separater	-	M	G	-	M	M	-	Set (CR)(LF)		
1.4	ATS-Message-Optional-Heading-Info	-	O	T1	T1	O	M	-			
1.4.1	OHI-prompt	-	M	G	-	M	M	-	Set the value "OHI:(single space)".		
1.4.2	optional-heading-information	-	M	T	T	M	M	-			
1.4.3	OHI-separater	-	M	G	-	M	M	-	Set (CR)(LF)		
1.5	end-of-heading-blank-line	-	M	G	-	M	M	-	Set (LF)		
1.6	start-of-text	-	M	G	-	M	M	-	Set (STX)		
2	ATS-Message-Text	-	M	T	T	M	M	-			

3. Message Transfer Envelope for IPN

Table 3.1 Message Transfer Envelope (IPN)

(Based on: ATSMHS SARPs Table 3.1.2-6 and Table 3.1.2-9 for O, Table 3.1.2-12 and Table 3.1.2-15 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	MessageTransferEnvelope	M	M	T	T	M	M	-			
1.1	per message fields	M	M					-			
1.1.1	message-identifier	M	M	G	D	M	M-	-			
1.1.2	originator-name	M	M	T	T	M	M	-	Set the originator XF address converted from AF address of AFTN acknowledgement message.		
1.1.3	original-encoded-information-types	O	M-	G	D	X	M-	-			
1.1.4	content-type	M	M	G	D	M	M	-	BuiltInContentType is set the abstract value "interpersonal-messaging-1984(2)"	If the value of BuiltInContentType is neither interpersonal-messaging-1984(2) nor interpersonal-messaging-1988(22), then generate NDR[NDRC=1,NDDC=15].	
1.1.5	content-identifier	O	M-	G	D	X	M-	<=16			
1.1.6	priority	M	M	G	D	M	M	-	Set "urgent".		
1.1.7	per-message-indicators	M	M	G	D	M	M	-			See Table 3.2/4
1.1.8	deferred-delivery-time	O	M-	X	D	M	M-	-			
1.1.9	per-domain-bilateral-information	O	M-	X	D	X	M-	-			
1.1.10	trace-information	M	M	G	D	M	M	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.1.11	extensions	M	M	G	D	M	M-	-			In X.400, if the value doesn't exist, it is considered to be not selected.
	type	M	M	G	D	M	M	-	Set the abstract value "internal-trace-information (38)".		Only supports "standard-extension".
	criticality	M	M	G	D	M	M	-			In X.400, if the value doesn't exist, it is considered to be not selected.
	value	M	M	M	D	M	M	-	Set the value of "internal-trace-information"		
1.1.11.1	recipient-reassignment-prohibited	O	M-	X	D	X	M-	-			
1.1.11.2	dl-extension-prohibited	O	M-	X	D	X	M-	-			
1.1.11.3	conversion-with-loss-prohibited	O	M-	X	D	X	M-	-			
1.1.11.4	latest-delivery-time	O	M-	X	D	X	M-	-		If this exists, and the current time exceeds the value, then generate NDR[NDRC=1,NDDC=5].	
1.1.11.5	originator-return-address	O	M-	X	D	X	M-	-			
1.1.11.6	originator-certificate	O	M-	X	X	X	X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.1.11.7	content-confidentiality-algorithm-identifier	O	M-	X	X	X	X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=19].	
1.1.11.8	message-origin-authentication-check	O	M-	X	X	X	X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=20].	
1.1.11.9	message-security-label	O	M-	X	X	X	X	-		If the value is "CRITICAL FOR DELIVERY" then generate NDR[NDRC=1,NDDC=21].	
1.1.11.10	content-correlator	O	M-	X	D	X	M-	<= 512			
1.1.11.11	dl-expansion-history	O	M-	X	D	X	O	-			
1.1.11.12	internal-trace-information	O	M-	G	D	M	M-	-			
1.2	per-recipient-fields	M	M	T	D	M	M	-			Number of recipient is always one.
1.2.1	recipient-name	M	M	T	D	M	M	-	Set the MF address of the originator of the subject IPM.		
1.2.2	originally-specified-recipient-number	M	M	G	D	M	M	-	Set "1".		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.3	per-recipient-indicators	M	M	G	D	M	M	-	Set the following values : responsibility=responsible(1) originating-MTA-reportrequest=non-delivery-report(01) originator-report-request=non-delivery-report(00)		BITSTRING
1.2.4	explicit-conversion	O	M-	X	D	X	M-	-			
1.2.5	extensions	M	M-	X	D	X	M-	-			In X.400, if the value doesn't exist, it is considered to be not selected.
	type	M	M	-	D	-	M	-			Only supports "standard-extension".
	criticality	M	M	-	D	-	M	-			
	value	M	M	-	D	-	M	-			
1.2.5.1	originator-requested-alternate-recipient	O	M-	-	D	-	M-	-			
1.2.5.2	requested-delivery-method	O	M-	-	D	-	M-	-			
1.2.5.3	physical-forwarding-prohibited	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.4	physical-forwarding-address-request	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.5.5	physical-delivery-modes	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.6	registered-mail-type	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.7	recipient-number-for-advice	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.8	physical-redirection-attributes	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	
1.2.5.9	physical-delivery-report-request	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=3,NDDC=18].	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.2.5.10	message-token	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=18].	
1.2.5.11	content-integrity-check	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=18].	
1.2.5.12	proof-of-delivery-request	O	M-	-	X	-	M-/X	-		If the criticality is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=18].	
1.2.5.13	redirection-history	O	M-	-	D	-	M-	-			
2	content	M	M	T	T	M	M	-	Set the generated IPN.		

Table 3.2 Common Data Type

(Based on : ATSMHS SARPs Table 3.1.2-6 and Table 3.1.2-9 for O, Table 3.1.2-12 and Table 3.1.2-15 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	MTS-Identifier										
1.1	global-domain-identifier	M	M	G	D	M	M	<=16			
1.2	local-identifier	M	M	G	D	M	M	<=32	Set the characters which identifies message in ia-5 characters.		
2	GlobalDomainIdentifier										
2.1	country-name	M	M	G	D	M	M	2 or 3	Set the country name of AMHS management domain.		
2.2	administration-domain-name	M	M	G	D	M	M	<=16	Set the AMHS management domain name.		
2.3	private-domain-identifier	O	M-	X	D	X	M-	-			
3	EncodedInformationTypes										
3.1	built-in-encoded-information-types	M	M	G	D	X	M	-			BITSTRING
3.2	non-basic parameters	O	M-	X	D	X	M-	-			
3.3	extended-encoded-information-types	O	M	X	D	X	O	-			
4.	PerMessageIndicators	M	M	G	D	G	D	-			BITSTRING In X.400, if the value doesn't exist, all bits are considered to be OFF.
4.1	disclosure-of-other-recipients(0)	M	M	G	D	G	D	-	Set the abstract value "disclosure-of-other-recipients-prohibited(0)"		
4.2	implicit-conversion-prohibited(1)	M	M	G	D	G	D	-	Set the abstract value "implicit-conversion-prohibited(1)"		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
4.3	alternate-recipient-allowed(2)	M	M	G	D	G	D	-	Set the abstract value "alternate-recipient-allowed(1)"		
4.4	content-return-request(3)	M	M	G	D	G	D	-	Set the abstract value "content-return-not-requested(0)"	Ignored and considered "content-return-not-requested(0)". However, if error occurs in the ATN component of AMHS and "content-return-request(1)" is set, it is impossible to restrain this service.	
5	PerDomainBilateralInformation	O	M-	X	D	X	D	-			
6	TraceInformation										
6.1	TraceInformationElement	M	M	G	D	M	M	-			
6.1.1	global-domain-identifier	M	C1	X	D	M	M	-		If the last trace information of this parameter differs from the input MTA, then generate NDR.	
6.1.2	domain-supplied-information	M	M	G	D	M	M	-			
6.1.2.1	arrival-time	M	C2	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message		
6.1.2.2	routing-action	M	M-	G	D	M	M	-	Set the abstract value of "relayed(0)".		
6.1.2.3	attempt-domain	O	M-	X	D	X	M-	-			
6.1.2.4	additional actions	O	M-	X	D	X	M-	-			
6.1.2.4.1	deferred-time	O	M-	X	D	X	M-	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
6.1.2.4.2	converted-encode-information-types	O	M-	X	D	X	M-	-			
6.1.2.4.3	other-actions	O	M-	X	D	X	M-	-			

Table 3.3 Extension Data Types
(Based on: ATSMHS SARPs Table 3.1.2-6 for O, Table 3.1.2-12 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
5	internal-trace-information	O	M-	G	D	M	M-	-			
5.1	global-domain-identifier	M	M	G	D	M	M	16	Set the value which identifies AMHS Management Domain.		
5.2	mta-name	M	M	G	D	M	M	32	Set the value of mta-name of AMHS.		
5.3	domain-supplied-information	M	M	G	D	M	M	-			
5.3.1	arrival-time	M	M	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message		
5.3.2	routing-action	M	M	G	D	M	M	-	Set the abstract value "relayed(0)"		
5.3.3	attempt-domain	O	C1	X	D	X	M-	-			
5.3.4	additional actions	O	C2	X	D	X	M-	-			
5.3.4.1	deferred-time	O	M-	X	D	X	M-	-			
5.3.4.2	converted-encoded-information-types	O	M-	X	D	X	O	-			
5.3.4.3	other-actions	O	M-	X	D	X	M-	-			

3. IPN

Table 4.1 IPN

(Based on: ATSMHS SARPs Table 3.1.2-8 for O, Table 3.1.2-14 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	Interpersonal Notification(IPN)	M	M	-	-	M	M	-			
1.1	Common-fields	M	M	-	-	M	M	-			
1.1.1	subject-ipm	M	M	G	D	M	M	-	Set the value of this-IPM of the subject IPM.		
1.1.2	ipn-originator	O	M	T	D	M	O	-	Set the originator XF address converted from AF address of AFTN message.		
1.1.3	ipm-preferred-recipient	O	M	G2	D	O	O	-	This parameter exists when the recipient indicated by subject IPM and the real recipient differs, and set the recipient which was on the subject IPM.		
1.1.4	conversion-eits	O	M	G2	D	O	O	-	If the originally-encoded-information-types of the subject IPM and encoded-information types at the reception differ, set the encoded-information-types at the reception.		
1.1.5	notification-extensions	O	M	X	D	X	M	-			
1.2	non-receipt-fields	M	M	X	D	X	O	-		Either non-receipt-field or receipt-field is mandatory.	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.3	receipt-fields	M	M	T	T	M	M	-			
1.3.1	receipt-time	M	M	T	T	M	M	-	Convert the time to UTC-TIME format and set the value.	Convert to AFTN format.	UTC-TIME format is YYMMDDhhmm[ss]Z or YYMMDDhhmm[ss]+(or -) hhmm
1.3.2	acknowledgment-mode	O	O	G	D	M	M-	-	Set the abstract value "manual(0)"		The default value of this element is "manual", so it is not necessary to set the value.
1.3.3	suppl-receipt-info	O	O	X	D	X	M-	-			
1.3.4	rn-extension	O	I	X		X	M-	-			
1.3.5	other-notification-type-fields	O	I	X		X	M-	-			

Table 4.2 OR Descriptor
(Based on: ATSMHS SARPs Table 3.1.2-8 for O, Table 3.1.2-14 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	ORDescriptor										
1.1	formal-name	M	M	T	-	M	M	-			
1.2	free-form-name	O	O	X	-	X	M-	<=64			
1.3	telephone-number	O	O	X	-	X	M-	-			

5. ReportTransfer Envelope

Table 5.1 Report Transfer Envelope
(Based on: ATSMHS SARPs Table 3.1.2-17 for O, Table 3.1.2-18 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	ReportTransferEnvelope	M	M	G	D	M	M	-			
1.1	report-identifier	M	M	G	D	M	M	-			
1.2	report-destination-name	M	M	G	T	M	M	-	If the subject message has the element "dl-expansion-history", and OR name of last element of dl-expansion-history does not exist, set the originator-name of the subject message.		
1.3	trace-information	M	M	G	D	M	M	-			
1.4	extensions	M	M	G	D	M	M	-			In X.400, if the value doesn't exist, it is considered to be not selected.
1.4.1	type	M	M	G	D	M	M	-			Only supports "standard-extension".
1.4.2	criticality	M	M	G	D	M	M	-			In X.400, if the value doesn't exist, it is considered to be not selected.
1.4.3	value	M	M	M	D	M	M	-	Set the value of "internal-trace-information".		
1.4.4	message-security-label	O	M-	X	D	X	D	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1.4.5	originator-and-DL-expansion-history	O	M-	G2	D	O	D	-	Only when the element "DL-expansion-history" exists in the subject message, set the value.		
1.4.6	reporting-DL-name	O	M-	X	D	X	M-	-			
1.4.7	reporting-MTA-certificate	O	M-	X	D	X	M-	-			
1.4.8	report-origin-authentication-check	O	M-	X	D	X	M-	-			
1.4.9	internal-trace-information	O	M-	G	D	M	M-	-			
1.4.9.1	global-domain-identifier	M	M	G	D	M	M	<=16	Set the value which identifies the AMHS management domain.		
1.4.9.2	domain-supplied-information	M	M	G	D	M	M	-			
1.4.9.3	arrival-time	M	M	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message		
1.4.9.4	routing-action	M	M	G	D	M	M	-	Set the abstract value "relayed(0)".		
1.4.9.5	attempt-domain	O	C1	X	D	X	M	-			
1.4.9.6	additional actions	O	C2	X	D	X	M	-			
1.4.9.7	deferred-time	O	M-	X	D	X	M	-			
1.4.9.8	converted-encoded-information-types	O	M-	X	D	X	M	-			
1.4.9.9	other-actions	O	M-	X	D	X	M	-			
2	ReportTransferContent	M	M			M	M	-			
2.1	per report fields							-			
2.1.1	subject-identifier	M	M	G	D	M	M	-	Set the value of the "message-identifier" of the subject message."	It is expected that the value of message-identifier of the subject message is set.	

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
2.1.2	subject-intermediate-trace-information	O	M	G2	D	O	M-	-	If the originating-MTA-report-request of the per-recipient-indicator of the recipient of the subject message per-recipient-indicator takes the value "audited-report", set the value of trace-information of the subject message.		
2.1.3	original-encoded-information-types	O	M	X	D	X	M-	-			
2.1.4	content-type	O	M	X	D	X	M-	-			
2.1.5	content-identifier	O	M	X	D	X	M-	-			
2.1.6	returned-content	O	M-	X	D	X	M-	-			
2.1.7	additional-information	O	M-	X	D	X	M-	-			
2.1.8	extensions	M	M	G2	D	O	M-	-			
2.1.8.1	content-correlator	O	M	G2	D	O	M-	-	If the element "content-correlator" exists in the subject message, the value of the element is set.		
2.2	per-recipient-fields	M	M	T	T	M	M	-			
2.2.1	actual-recipient-name	M	M	T	T	M	M	-	Set the recipient-name of the corresponding per-recipient field of the subject message.		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
2.2.2	originally-specified-recipient-number	M	M	G	D	M	M	-	Set the value of originally-specified recipient number of the corresponding per-recipient field of the subject message.		
2.2.3	per-recipient-indicators	M	M	G	D	M	M	-	Set the value of the corresponding per-recipient-indicator of the per-recipient-fields of the subject message.		BITSTRING
2.2.4	last-trace-information	M	M	G	D	M	M	-			
2.2.4.1	arrival-time	M	M	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message		
2.2.4.2	converted-encoded-information-types	O	M	G2	D	O	M-	-	If the original-EIT and the final EIT are different, set the value of the final EIT. In other cases, nothing is set.		
2.2.4.3	report-type	M	M	G	D	M	M	-			
2.2.4.3.1	delivery	M	M	G2	D	O	X	-	Set this value when the probe is successfully passed to AFTN Component.		
2.2.4.3.2	message-delivery-time	M	M	G	D	M	X	-	If the report is a delivery report, set the time at which the subject message has been successfully passed to AFTN Component.		

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
2.2.4.3.3	type-of-MTS-user	M	M	G	D	M	X	-	Set the abstract value "other(6)".		If this parameter is omitted, then set the value "public(0)".
2.2.4.3.2	non-delivery	M	M	G	D	M	M	-			
2.2.4.3.2.1	non-delivery-reason-code	M	M	G	D	M	M	-	Set the defined NDRC.	If NDRC=1 and NDDC=0, then generate unknown addressee AFTN service message.	
2.2.4.3.2.2	non-delivery-diagnostic-code	O	M	G	D	M	M	-	Set the defined NDDC.		
2.2.5	originally-intended-recipient-name	O	M-	G2	D	O	O	-	If there exists redirection-history element, set the first O/R name of the subject message.		
2.2.6	supplementary-information	O	M-	G2	D	O	O	<=256	a) If delivery report (probe), set the value "This report only indicates successful (potential) conversion to AFTN, not delivery to a recipient" b) If non-delivery report set the value defined in each error (if not defined, set nothing)		
2.2.7	extensions	M	M-	G2	D	O	O	-			In X.400, if the value doesn't exist, it is considered to be not selected.
2.2.7.1	type	M	M	G2	D	M	M	-			Only supports "standard-extension".
	criticality	M	M	G2	D	M	M	-			
	value	M	M	G2	D	M	M	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
2.2.7.1.1	redirection-history	O	M-	G2	D	O	M-	-	If there exists the "redirection-history", set that value.		
2.2.7.1.2	physical-forwarding-address	O	M-	X	X	X	X	-			
2.2.7.1.3	recipient-certificate	O	M-	X	X	X	X	-			
2.2.7.1.4	proof-of-delivery	O	M-	X	X	X	X	-			

Table 5.2 Common Data Types
(Based on: ATSMHS SARPs Table 3.1.2-17 for O, Table 3.1.2-18 for R)

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
1	MTS-Identifier										
1.1	global-domain-identifier	M	M	G	D	M	M	<=16			
1.2	local-identifier	M	M	G	D	M	M	<=32	Set the value which identifies the report in ia-5 characters.		
2	GlobalDomainIdentifier										
2.1	country-name	M	M	G	D	M	M	2 or 3	Set the country name of the AMHS management domain.		
2.2	administration-domain-name	M	M	G	D	M	M	<=16	Set the name of the AMHS management domain.		
2.3	private-domain-identifier	O	M-	X	D	X	M-	<=16			
6	TraceInformation										
6.1	TraceInformationElement	M	M	G	D	M	M	-			
6.1.1	global-domain-identifier	M	C1	X	D	M	M	-		If the last trace information of the global-domain-identifier differs from input MTA, generate NDR.	
6.1.2	domain-supplied-information	M	M	G	D	M	M	-			
6.1.2.1	arrival-time	M	C2	G	D	M	M	-	Set the value of the time which AFTN/AMHS Gateway received the message.		
6.1.2.2	routing-action	M	M-	G	D	M	M	-	Set the abstract value "relayed(0)".		
6.1.2.3	attempt-domain	O	M-	X	D	X	M-	-			

NO.	element	support		AMHS-Action		AMHS-support		size	Detailed Action		Note
		ISP	SARPs	O	R	O	R		Origination	Reception	
6.1.2.4	additional actions	O	M-	X	D	X	M-	-			
6.1.2.4.1	deferred-time	O	M-	X	D	X	M-	-			
6.1.2.4.2	converted-encode-information-types	O	M-	X	D	X	M-	-			
6.1.2.4.3	other-actions	O	M-	X	D	X	M-	-			

6. Probe Transfer Envelope

Table 6.1 Probe Transfer Envelope

NO.	element	support ISP	AMHS support	size	Detailed Action	Note
					Reception	
1	probeTransferEnvelope	M	M	-		
1.1	per message fields	M	M	-		
1.1.1	probe-identifier	M	M	-		
1.1.2	originator-name	M	M	-		
1.1.3	original-encoded-information-types	O	M	-		
1.1.4	content-type	M	M	-	If the value of BuiltInContentType is neither interpersonal-messaging-1984(2) nor interpersonal-messaging-1988(22), then generate NDR[NDRC=1,NDDC=15].	
1.1.5	content-identifier	O	M-	<=16		It was agreed to be "X" in the TMC.
1.1.6	content-length	O	M-	-		
1.1.7	per-message-indicators	M	M	-		BITSTRING In X.400, if the value doesn't exist, all bits are considered to be OFF.
1.1.7.1	disclosure-of-other-recipients(0)	M	M	-		
1.1.7.2	implicit-conversion-prohibited(1)	M	M	-		
1.1.7.3	alternate-recipient-allowed(2)	M	M	-		
1.1.7.4	content-return-request(3)	M	M	-		
1.1.8	per-domain-bilateral-information	O	M-	-		It was agreed to be "X" in the TMC."
1.1.9	trace-information	M	M	-		
1.1.10	extensions	M	M	-		In X.400, if the value doesn't exist, it is considered to be not selected.

NO.	element	support ISP	AMHS support	size	Detailed Action	Note
					Reception	
	type	M	M	-		Only supports "standard-extension".
	criticality	M	M	-		In X.400, if the value doesn't exist, it is considered to be not selected.
	value	M	M	-		
1.1.10.1	recipient-reassignment-prohibited	O	M-	-		
1.1.10.2	dl-extension-prohibited	O	M-	-		
1.1.10.3	conversion-with-loss-prohibited	O	M-	-		
1.1.10.4	originator-certificate	O	M-/X	-	If the value is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=18].	
1.1.10.5	message-security-label	O	M-/X	-	If the value is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=21].	
1.1.10.6	content-correlator	O	M-	<=5 12		
1.1.10.7	probe-origin-authentication-check	O	M-	-		
1.1.10.8	internal-trace-information	O	M-	-		
1.1.10.8.1	global-domain-identifier	M	M	-		
1.1.10.8.2	mta-name	M	M	<=3 2	Set the value which identifies AMHS.	
1.1.10.8.3	mta-supplied-information	M	M	-		
1.1.10.8.3.1	arrival-time	M	M	-		
1.1.10.8.3.2	routing-action	M	M	-		
1.1.10.8.3.3	attempt-domain	O	M-	-		

NO.	element	support ISP	AMHS support	size	Detailed Action	Note
					Reception	
1.1.10.8.4	additional actions	O	M-	-		
1.1.10.8.4.1	deferred-time	O	M-	-		
1.1.10.8.4.2	converted-encoded-information-types	O	M-	-		
1.1.10.8.4.3	other-actions	O	M-	-		
1.2	per-recipient-fields	M	M	-		
1.2.1	recipient-name	M	M	-		
1.2.2	originally-specified-recipient-number	M	M	-		
1.2.3	per-recipient-indicators	M	M	-		BITSTRING
1.2.4	explicit-conversion	O	M-	-		
1.2.5	extensions	M	M-	-		In X.400, if the value doesn't exist, it is considered to be not selected.
	type	M	M	-		Only supports "standard-extension".
	criticality	M	M	-		
	value	M	M	-		
1.2.5.1	originator-requested-alternate-recipient	O	M-	-		
1.2.5.2	requested-delivery-method	O	M-	-		
1.2.5.3	physical-redirection-attributes	O	M-/X	-	If the value is "CRITICAL FOR DELIVERY", then generate NDR[NDRC=1,NDDC=18].	
1.2.5.4	redirection-history	O	O	-		

Table 6.2 Common Data Type

NO.	element	support ISP	AMHS support	size	Action	Note
					Reception	
1.	MTS-Identifier					
1.1	global-domain-identifier	M	M	<=1 6		
1.2	local-identifier	M	M	<=3 2		
2	GlobalDomainIdentifier					
2.1	country-name	M	M	2 or 3		
2.2	administration-domain-name	M	M	<=1 6		
2.3	private-domain-identifier	O	M-	<=1 6		The value of this parameter may be used in the future.
3	EncodedInformationTypes					
3.1	built-in-encoded-information-types	M	M	-		BITSTRING
3.2	non-basic parameters	O	M-	-		
3.3	extended-encoded-information-types	O	O	-		
6	TraceInformation					
6.1	TraceInformationElement	M	M	-		
6.1.1	global-domain-identifier	M	M	-	If the last trace information of this parameter differs from the input MTA, then generate NDR.	
6.1.2	domain-supplied-information	M	M	-		
6.1.2.1	arrival-time	M	M	-		
6.1.2.2	routing-action	M	M	-		
6.1.2.3	attempt-domain	O	M-	-		
6.1.2.4	additional actions	O	M-	-		
6.1.2.4.1	deferred-time	O	M-	-		

NO.	element	support ISP	AMHS support	size	Action	Note
					Reception	
6.1.2.4.2	converted-encode-information-types	O	M-	-		
6.1.2.4.3	other-actions	O	M-	-		