



Agenda Item 3: CNS Developments

3.1 Follow-up on the status of the E/CAR AFS and MEVA II digital networks and their related inter and intra-regional interconnection/integration

ICAO GUIDELINES ON PERFORMANCE OF VSAT NETWORKS

(Presented by Secretariat)

SUMMARY

This Information Paper presents the ICAO guidelines on the harmonization of implementation activities relating the use of very small aperture terminal (VSAT) networks.

References:

- Fifth ALLPIRG Meeting, Montreal, Canada, 23-24 March 2006.

1. Introduction

1.1 The Fifth Meeting of the All Planning and Implementation Regional Group (ALLPIRG) / Advisory Group, held in Montreal, Canada, from 23 to 24 March 2006, agreed the Conclusion 5/16 – *Implementation of very small aperture terminals (VSATs)* that urged the PIRGs to discourage the proliferation of VSAT networks where one/some of the existing ones can be expanded to serve the new areas of interest, work towards integrated regional/interregional digital communication networks with a single (centralized) operational control and preferably based on the Internet Protocol (IP) and give due consideration to managed network services (e.g. a virtual private network [VPN]), subject to availability and cost-effectiveness; and the Conclusion 5/17 - *Provisions for digital communication networks*, urged the ICAO initiate the development of provisions governing the end-to-end performance of digital communication networks, irrespective of the technologies and protocols utilized therein.

2. ICAO Guidelines on Performance of VSAT Network

2.1 As part of the aforementioned work and following the Conclusion 5/17 of the ALLPIRG/5 Meeting, some guidelines on performance of VSAT networks have been prepared by ICAO to establish a basis for planning and basic system design of such network in support of aeronautical ground-ground communications. These guidelines are shown in **Appendix** of this paper.

APPENDIX

GUIDELINES ON PERFORMANCE OF VSAT NETWORKS

1. Introduction

1.1 Digital communication networks based on very small aperture terminal (VSAT) are being increasingly used in the provision of aeronautical ground-ground communications in areas where terrestrial communication systems are unavailable, unreliable or uneconomical. VSAT networks are generally flexible, scalable, versatile, easy to implement/operate and cost-effective in certain areas, terrains or conditions.

1.2 On the other hand, a wide variety of often incompatible architectures, configurations, access techniques, management, operation schemes and protocols are used in different VSAT networks. Moreover, almost all VSAT networks available in the market employ some proprietary products. As a result, in general, non-identical VSAT networks are not interoperable.

1.3 There are no international standards specifically governing VSAT networks. A number of International Telecommunication Union (ITU) Recommendations relating to radio frequency or other aspects of communication systems are applicable to VSATs and are often complied with by VSAT vendors. Such compliance should not, however, be interpreted as an indication of compatibility with other products.

1.4 ICAO has not standardized the physical layer of communications, therefore there are no provisions for VSATs, nor for terrestrial-based systems-like cable, microwave relay system or optical fibre.

1.5 Noting the above, States or organizations that plan to implement VSAT networks for the provisions of aeronautical ground-ground communications, are advised to:

- a) ascertain that VSAT is in fact the preferred and most cost-effective means of communications in the geographical area(s) of interest;
- b) take into consideration Conclusion 5/16 of ALLPIRG/5; and
- c) use the performance requirements stated in the ensuing paragraph as a guide to planning, system design and evaluation activities.

2. Performance requirements

2.1 Many factors influence the architecture, configuration and system design of a VSAT network. The end user is however mainly interested in the quality or performance of the communication service that is being provided and not so much in the technical details. As such, the user should state the desired basic performance requirements at the very early stage of planning to enable VSAT system design to proceed accordingly. Such performance requirements, once agreed upon by all parties concerned, would be used as a basis for further evaluation and continuing monitoring of the network.

2.2 In general, there is a direct relationship between performance and cost. This is particularly important for VSAT networks and there are also many parameters involved in achieving a given performance level. For example, insisting on higher availability implies duplicate terminals using different satellites. Similarly, a very low bit error rate requires large earth station antennas, high power transmitters and large satellite transponder bandwidth. All those directly translate to significantly higher acquisition and operation costs.

2.3 The minimum performance targets state below are generally suitable for aeronautical ground-ground communication and can be achieved with “reasonable” resources and cost. The state performance parameters apply to the overall communication service as seen by the end user of a digital VSAT network.

Availability $\geq 99.8\%$
(See note 1)

Bit error rate (BER) ≤ 1 in 10^7
(See note 2)

One-way latency (for voice communications) < 400 ms
(See note 3)

Call blocking probability $\leq 2.5 \times 10^{-3}$ (or in 400 attempts)
(See note 4)

Call set-up time ≤ 2 s

Note 1. The above shows the required overall availability of the communication service to the end user. It includes the consideration of all scheduled/non-scheduled maintenance and sun outages.

Note 2. BER is applicable to the physical layer of communications. Forward error correction (FEC) may be employed to achieve this figure.

Note 3. The above implies that for voice communications, only a single satellite hop should be used. The major contributor to the latency is the propagation delay of approximately 240 ms (a single hop). Voice compression and encoding also introduce additional delays.

Note 4. The above applies to a normal switched voice communications environment. In certain operational scenarios, it may be necessary to guarantee the availability of a voice circuit upon demand by employing priority/pre-emption techniques or dedicated satellite resources.

Suggested readings

Maral, G. (2003) *VSAT Networks*, 2nd edition, John Wiley & Sons.

(1994) *Handbook on Satellite Communications, Supplement No. 3 “VSAT Systems and Earth Stations”*, International Telecommunications Union (ITU).