



International Civil Aviation Organization

**MIDANPIRG Steering Group**

**Second Meeting (ANSIG/2)**  
*(Cairo, Egypt, 6 – 8 December 2016)*

---

**Agenda Item 4.1: Air Navigation Strategy and Planning**

**MID REGION AIR NAVIGATION STRATEGY**

*(Presented by the Secretariat)*

**SUMMARY**

This paper presents the MID Air Navigation Strategy (MID Doc 002) for review by the meeting and proposals for update (priorities and targets), as deemed necessary.

Action by the meeting is at paragraph 3.

**REFERENCES**

- GANP 2016
- MID Region Air Navigation Strategy (MID Doc 002)
- MIDANPIRG/15 Report
- MSG/5 Report

**1. INTRODUCTION**

1.1 The ASBUs included in the *Global Air Navigation Plan* (GANP, Doc 9750) provides the strategic direction for the global air navigation, however priorities, targets and applicability of the Modules are to be defined by PIRGs (at regional level) and States (at national level).

**2. DISCUSSION**

2.1 The meeting may wish to recall that the MIDANPIRG/15 meeting, through Conclusion 15/10, updated and endorsed the MID Region Air Navigation Strategy (MID Doc 002):

*CONCLUSION 15/10: MID REGION AIR NAVIGATION STRATEGY*

*That,*

a) *the revised MID Region Air Navigation Strategy:*

i. *is endorsed as the framework identifying the regional air navigation priorities, performance indicators and targets; and*

ii. *be published as MID Doc 002*

b) *MID States be urged to:*

- i. *develop their National Air Navigation Performance Framework, ensuring the alignment with and support to the MID Region Air Navigation Strategy; and*
- ii. *provide the ICAO MID Regional Office, on an annual basis (by the end of November), with relevant data necessary for regional air navigation planning, reporting and monitoring.*

2.2 Detailed information on the monitoring of certain ASBU modules has been included in Volume III of the MID eANP, in order to be used as planning tools for the measurement of the air navigation systems performance.

2.3 The meeting may wish to recall that the MSG/5 meeting agreed that, for a timely planning of the ASBU Block 1 Modules implementation, it would be necessary to start the consultation process between all stakeholders to identify those ASBU Block 1 Modules that are considered a priority for the Region, based on operational needs/improvements.

2.4 The meeting may wish to recall that the Assembly 39 endorsed the fifth edition of the GANP which while maintaining the stability of the document, includes a new organization of the aviation system block upgrades (ASBUs) in non-overlapping six-year increments starting in year 2013 and continuing through 2031 and beyond (WP/3 refers). Accordingly, the blocks' timeline should change as follows: Block 0 (2013-2018); Block 1 (2019-2024); Block 2 (2025-2030); and Block 3 (2031 and beyond).

2.5 The meeting may wish to note that the targets for different Priority 1 ASBU Block 0 Modules/elements have been assigned by the related technical subsidiary bodies and consequently are not necessarily harmonized (too many different timelines, which make the monitoring more difficult). In order to facilitate the process of measuring and monitoring the implementation of the Modules/elements, it is proposed to minimize the number of target dates (harmonize) for the Priority 1 ASBU Modules/elements (for example use 2016, 2018 and 2020 as targets and avoid the use of 2017 and 2019, etc).

2.6 The meeting may wish to note that reviewing priority level and timelines of the ASBU Modules is an ongoing task of MIDANPIRG and its Subsidiary Bodies. Therefore, taking into consideration the current operational needs/requirements and status of implementation, as well as the preparation for ASBU Block 1 implementation, it's proposed to review and propose updates to the priority levels of the ASBU Block 0 Modules in the MID Air Navigation Strategy (the priority 2 Modules). In this regard, a new column (Timelines/Start Date) is to be added to reflect the start date of the newly assigned priority 1 Modules in the Strategy.

2.7 The meeting may wish to recall that MSG/5 agreed with the proposal to include a new performance indicator related to the implementation of SIGMET in the MID Region Air Navigation Strategy (MSG Conclusion 5/13 refers). Furthermore, the cessation of SADIS 2G on 31 July 2016 requires an update to the first element of the B0-AMET and it should be called *SADIS FTP*.

2.8 The meeting may also wish to recall that the PBN SG/2 (Sharm El Sheikh, Egypt, 22 – 25 February 2016) agreed on the applicability areas for the B0-CDO and B0-CCO which is reflected in the draft revised Strategy.

2.9 A revised Draft version of the MID Air navigation Strategy is at **Appendix A**.

**3. ACTION BY THE MEETING**

3.1 The meeting is invited to:

- a) agree on the proposals at para 2.4 to 2.8; and
- b) review and propose updates, as deemed necessary, to the MID Air Navigation Strategy.

-----



**INTERNATIONAL CIVIL AVIATION ORGANIZATION**

**MIDDLE EAST AIR NAVIGATION PLANNING  
AND IMPLEMENTATION REGIONAL GROUP  
(MIDANPIRG)**

**MID REGION  
AIR NAVIGATION STRATEGY**

EDITION **FEBRUARY, 2017**

The designations employed and the presentation of material in this publication do not imply the expression of any opinion whatsoever on the part of ICAO concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontier or boundaries.

**TABLE OF CONTENTS**

1. Introduction ..... 1

2. Strategic Air Navigation Capacity and Efficiency Objective..... 1

3. MID Air Navigation Objectives ..... 1

- ✓ Near Term Objectives .....1
- ✓ MID Term Objectives .....2
- ✓ Long Term Objectives.....2

4. MID Region ASBU Modules prioritization ..... 2

5. Measuring and monitoring air navigation performance ..... 3

6. Governance ..... 4

DRAFT

# MID-REGION AIR NAVIGATION STRATEGY

## 1. Introduction

1.1 As traffic volume increases throughout the world, the demands on air navigation service providers in a given airspace increase, and air traffic management becomes more complex.

1.2 It is foreseen that the implementation of the components of the ATM operational concept will provide sufficient capacity to meet the growing demand, generating additional benefits in terms of more efficient flights and higher levels of safety. Nevertheless, the potential of new technologies to significantly reduce the cost of services will require the establishment of clear operational requirements.

1.3 Taking into account the benefits of the ATM operational concept, it is necessary to make many timely decisions for its implementation. An unprecedented cooperation and harmonization will be required at both global and regional level.

1.4 ICAO introduced the Aviation System Block Upgrades (ASBU) methodology as a systemic manner to achieve a harmonized implementation of the air navigation services. An ASBU designates a set of improvements that can be implemented globally from a defined point in time to enhance the performance of the ATM system.

1.5 Through Recommendation 6/1 - *Regional performance framework – planning methodologies and tools*, AN-Conf/12 urged States and PIRGs to harmonize the regional and national air navigation plans with the ASBU methodology in response to this, the MID region is developing MID Region Air Navigation Strategy that is aligned with the ASBU methodology.

1.6 Stakeholders including service providers, regulators, airspace users and manufacturers are facing increased levels of interaction as new, modernized ATM operations are implemented. The highly integrated nature of capabilities covered by the block upgrades requires a significant level of coordination and cooperation among all stakeholders. Working together is essential for achieving global harmonization and interoperability.

## 2. Strategic Air Navigation Capacity and Efficiency Objective

2.1 To realize sound and economically-viable civil aviation system in the MID Region that continuously increases in capacity and improves in efficiency with enhanced safety while minimizing the adverse environmental effects of civil aviation activities.

## 3. MID Air Navigation Objectives

3.1 The MID Region air navigation objectives are set in line with the global air navigation objectives and address specific air navigation operational improvements identified within the framework of the Middle East Regional Planning and Implementation Group (MIDANPIRG).

### *Near-term Objective (2013 - 2018): ASBU Block 0*

3.2 Block '0' features Modules characterized by operational improvements which have already been developed and implemented in many parts of the world today. It therefore has a near-term implementation period of 2013–2018. The MID Region near-term priorities are based on the implementation of an agreed set of Block 0 Modules as reflected in **Table 1** below.

3.3 The MID Region Air Navigation Strategy is aimed to maintain regional harmonisation. The States should develop their national performance framework, including action plans for the implementation of relevant priority 1 ASBU Modules and other modules according to the State operational requirements.

**Mid-term Objective (2019~~8~~ - 2024~~3~~): ASBU Block 1**

3.4 Blocks 1 through 3 are characterized by both existing and projected performance area solutions, with availability milestones beginning in 2019~~8~~, 2025~~3~~ and 2031~~28~~, respectively. Associated timescales are intended to depict the initial deployment targets along with the readiness of all components needed for deployment.

**Long-term Objective (2025~~3~~ - 2031~~28~~): ASBU Block 2**

3.5 The Block Upgrades incorporate a long-term perspective matching that of the three companion ICAO Air Navigation planning documents. They coordinate clear aircraft- and ground-based operational objectives together with the avionics, data link and ATM system requirements needed to achieve them. The overall strategy serves to provide industry wide transparency and essential investment certainty for operators, equipment manufacturers and ANSPs.

**4. MID Region ASBU Block 0 Modules Prioritization and Monitoring**

4.1 On the basis of operational requirements and taking into consideration the associated benefits, **Table 1** below shows the priority for implementation of the 18 Block “0” Modules, as well as the MIDANPIRG subsidiary bodies that will be monitoring and supporting the implementation of the Modules:

**Table 1. MID REGION ASBU BLOCK 0 MODULES PRIORITIZATION AND MONITORING**

Module Code	Module Title	Priority	Timeline/ Start Date	Monitoring		Remarks
				Main	Supporting	
<b>Performance Improvement Areas (PIA) 1: Airport Operations</b>						
B0-APTA	Optimization of Approach Procedures including vertical guidance	1	2014	PBN SG	ATM SG, AIM SG, CNS SG	
B0-WAKE	Increased Runway Throughput through Optimized Wake Turbulence Separation	2				
B0-RSEQ	Improve Traffic flow through Runway Sequencing (AMAN/DMAN)	2				
B0-SURF	Safety and Efficiency of Surface Operations (A-SMGCS Level 1-2)	1	2014	ANSIG	CNS SG	Coordination with RGS WG
B0-ACDM	Improved Airport Operations through Airport-CDM	1	2014	ANSIG	CNS SG, AIM SG, ATM SG	Coordination with RGS WG
<b>Performance Improvement Areas (PIA) 2 Globally Interoperable Systems and Data Through Globally Interoperable System Wide Information Management</b>						
B0-FICE	Increased Interoperability, Efficiency and Capacity through Ground-Ground Integration	1	2014	CNS SG	AIM SG, ATM SG	
B0-DATM	Service Improvement through Digital Aeronautical Information Management	1	2014	AIM SG		



B0-AMET	Meteorological information supporting enhanced operational efficiency and safety	1	2014	MET SG		
<b>Performance Improvement Areas (PIA) 3 Optimum Capacity and Flexible Flights – Through Global Collaborative ATM</b>						
B0-FRTO	Improved Operations through Enhanced En-Route Trajectories	1	2014	ATM SG		
B0-NOPS	Improved Flow Performance through Planning based on a Network-Wide view	1	2014			
B0-ASUR	Initial capability for ground surveillance	2				
B0-ASEP	Air Traffic Situational Awareness (ATSA)	2				
B0-OPFL	Improved access to optimum flight levels through climb/descent procedures using ADS-B	2				
B0-ACAS	ACAS Improvements	1	2014	CNS SG		
B0-SNET	Increased Effectiveness of Ground-Based Safety Nets	2				
<b>Performance Improvement Areas (PIA) 4 Efficient Flight Path – Through Trajectory-based Operations</b>						
B0-CDO	Improved Flexibility and Efficiency in Descent Profiles (CDO)	1	2014	PBN SG		
B0-TBO	Improved Safety and Efficiency through the initial application of Data Link En-Route	2		ATM SG	CNS SG	
B0-CCO	Improved Flexibility and Efficiency Departure Profiles - Continuous Climb Operations (CCO)	1	2014	PBN SG		

**Priority 1:** Modules that have the highest contribution to the improvement of air navigation safety and/or efficiency in the MID Region. These modules should be implemented where applicable and will be used for the purpose of regional air navigation monitoring and reporting for the period 2016<sup>3</sup>-2018<sup>4</sup>.

**Priority 2:** Modules recommended for implementation based on identified operational needs and benefits.

## 5. Measuring and monitoring air navigation performance

5.1 The monitoring of air navigation performance and its enhancement is achieved through identification of relevant air navigation Metrics and Indicators as well as the adoption and attainment of air navigation system Targets. The monitoring of the priority 1 ASBU modules is carried out through the MID eANP Volume III.

5.2 MIDANPIRG through its activities under the various subsidiary bodies will continue to update and monitor the implementation of the ASBU Modules to achieve the air navigation targets.

5.3 The priority 1 Modules along with the associated elements, applicability, performance Indicators, supporting Metrics, and performance Targets are shown in the **Table 2** below.

*Note: The different elements supporting the implementation are explained in detail in the ASBU Document which is attached to the Global Plan (Doc 9750).*

## **6. Governance**

6.1 Progress report on the status of implementation of the different priority 1 Modules and other Modules, as appropriate, should be developed by the Air Navigation System Implementation Group (ANSIG) and presented to the MIDANPIRG Steering Group (MSG) and/or MIDANPIRG on regular basis.

6.2 The MIDANPIRG and its Steering Group (MSG) will be the governing body responsible for the review and update of the MID Region Air Navigation Strategy.

6.3 The MID Region Air Navigation Strategy will guide the work of MIDANPIRG and its subsidiary bodies and all its member States and partners.

6.4 Progress on the implementation of the MID Region Air Navigation Strategy and the achievement of the agreed air navigation targets will be reported to the ICAO Air Navigation Commission (ANC), through the review of the MIDANPIRG reports, MID Air navigation Report, etc.; and to the stakeholders in the Region within the framework of MIDANPIRG.

**Table 2. MONITORING THE IMPLEMENTATION OF THE ASBU BLOCK 0 MODULES  
IN THE MID REGION**

*B0 – APTA: Optimization of Approach Procedures including vertical guidance*

**Description and purpose:**

The use of performance-based navigation (PBN) and ground-based augmentation system (GBAS) landing system (GLS) procedures will enhance the reliability and predictability of approaches to runways, thus increasing safety, accessibility and efficiency. This is possible through the application of Basic global navigation satellite system (GNSS), Baro vertical navigation (VNAV), satellite-based augmentation system (SBAS) and GLS. The flexibility inherent in PBN approach design can be exploited to increase runway capacity.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
Y	Y	Y	Y	Y

**Applicability consideration:**

This module is applicable to all instrument, and precision instrument runway ends, and to a limited extent, non-instrument runway ends.

<i>B0 – APTA: Optimization of Approach Procedures including vertical guidance</i>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
States' PBN Implementation Plans	All States	Indicator: % of States that provided updated PBN implementation Plan  Supporting metric: Number of States that provided updated PBN implementation Plan	80 % by Dec. 2014  100% by Dec. 2015
LNAV	All RWYs Ends at International Aerodromes	Indicator: % of runway ends at international aerodromes with RNAV(GNSS) Approach Procedures (LNAV)  Supporting metric: Number of runway ends at international aerodromes with RNAV (GNSS) Approach Procedures (LNAV)	All runway ends at Int'l Aerodromes, either as the primary approach or as a back-up for precision approaches by Dec. 2016
LNAV/VNAV	All RWYs ENDS at International Aerodromes	Indicator: % of runways ends at international aerodromes provided with Baro-VNAV approach procedures (LNAV/VNAV)  Supporting metric: Number of runways ends at international aerodromes provided with Baro-VNAV approach procedures (LNAV/VNAV)	All runway ends at Int'l Aerodromes, either as the primary approach or as a back-up for precision approaches by Dec. 2017

**Module B0-SURF: Safety and Efficiency of Surface Operations (A-SMGCS Level 1-2)**

**Description and purpose:**

Basic A-SMGCS provides surveillance and alerting of movements of both aircraft and vehicles on the aerodrome thus improving runway/aerodrome safety. ADS-B information is used when available (ADS-B APT).

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
Y	Y	Y	Y	Y

**Applicability consideration:**

A-SMGCS is applicable to any aerodrome and all classes of aircraft/vehicles. Implementation is to be based on requirements stemming from individual aerodrome operational and cost-benefit assessments. ADS-B APT, when applied is an element of A-SMGCS, is designed to be applied at aerodromes with medium traffic complexity, having up to two active runways at a time and the runway width of minimum 45 m.

<b>B0-SURF: Safety and Efficiency of Surface Operations (A-SMGCS Level 1-2)</b>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
A-SMGCS Level 1*	OBBI, HECA, OIII, OKBK, OOMS, OTBD, OTHH, OEJN, OERK, OMDW, OMAA, OMDW	Indicator: % of applicable international aerodromes having implemented A-SMGCS Level 1  Supporting Metric: Number of applicable international aerodromes having implemented A-SMGCS Level 1	70% by Dec. 2017
A-SMGCS Level 2*	OBBI, HECA, OIII, OKBK, OOMS, OTBD, OTHH, OEJN, OERK, OMDW, OMAA, OMDW	Indicator: % of applicable international aerodromes having implemented A-SMGCS Level 2  Supporting Metric: Number of applicable international aerodromes having implemented A-SMGCS Level 2	50% by Dec. 2017

\*Reference: Eurocontrol Document – “Definition of A-SMGCS Implementation Levels, Edition 1.2, 2010”.

**B0 – ACDM: Improved Airport Operations through Airport-CDM**

**Description and purpose:**

To implement collaborative applications that will allow the sharing of surface operations data among the different stakeholders on the airport. This will improve surface traffic management reducing delays on movement and manoeuvring areas and enhance safety, efficiency and situational awareness.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N	Y	Y	Y	N

**Applicability consideration:**

Local for equipped/capable fleets and already established airport surface infrastructure.

**B0 – ACDM: Improved Airport Operations through Airport-CDM**

Elements	Applicability	Performance Indicators/Supporting Metrics	Targets
A-CDM	OBBI, HECA, OIII, OKBK, OOMS, OTBD, OTHH, OEJN, OERK, OMDB, OMAA, OMDW	Indicator: % of applicable international aerodromes having implemented improved airport operations through airport-CDM  Supporting metric: Number of applicable international aerodromes having implemented improved airport operations through airport-CDM	40% by Dec. 2017

***B0 – FICE: Increased Interoperability, Efficiency and Capacity through Ground-Ground Integration***

**Description and purpose:**

To improve coordination between air traffic service units (ATSUs) by using ATS Interfacility Data Communication (AIDC) defined by the ICAO *Manual of Air Traffic Services Data Link Applications* (Doc 9694). The transfer of communication in a data link environment improves the efficiency of this process particularly for oceanic ATSUs.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N	Y	Y	N	Y

**Applicability consideration:**

Applicable to at least two area control centres (ACCs) dealing with enroute and/or terminal control area (TMA) airspace. A greater number of consecutive participating ACCs will increase the benefits.

***B0 – FICE: Increased Interoperability, Efficiency and Capacity through Ground-Ground Integration***

<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
AMHS capability	All States	Indicator: % of States with AMHS capability  Supporting metric: Number of States with AMHS capability	70% of States with AMHS capability by Dec. 2017
AMHS implementation /interconnection	All States	Indicator: % of States with AMHS implemented (interconnected with other States AMHS)  Supporting metric: Number of States with AMHS implemented (interconnections with other States AMHS)	60% of States with AMHS interconnected by Dec. 2017
Implementation of AIDC/OLDI between adjacent ACCs	All ACCs	Indicator: % of FIRs within which all applicable ACCs have implemented at least one interface to use AIDC/OLDI with neighboring ACCs  Supporting metric: Number of AIDC/OLDI interconnections implemented between adjacent ACCs	70% by Dec. 2017

**B0 – DATM: Service Improvement through Digital Aeronautical Information Management**

**Description and purpose:**

The initial introduction of digital processing and management of information, through aeronautical information service (AIS)/aeronautical information management (AIM) implementation, use of aeronautical information exchange model (AIXM), migration to electronic aeronautical information publication (AIP) and better quality and availability of data

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N	N	Y	Y	Y

**Applicability consideration:**

Applicable at State level, with increased benefits as more States participate

<b>B0 – DATM: Service Improvement through Digital Aeronautical Information Management</b>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
National AIM Implementation Plan/Roadmap	All States	Indicator: % of States that have National AIM Implementation Plan/Roadmap  Supporting Metric: Number of States that have National AIM Implementation Plan/Roadmap	80% by Dec. 2016  90% by Dec. 2018
AIXM	All States	Indicator: % of States that have implemented an AIXM-based AIS database  Supporting Metric: Number of States that have implemented an AIXM-based AIS database	60% by Dec. 2015  80% by Dec. 2017  100% by Dec. 2019
eAIP	All States	Indicator: % of States that have implemented an IAID driven AIP Production (eAIP)  Supporting Metric: Number of States that have implemented an IAID driven AIP Production (eAIP)	60% by Dec. 2016  80% by Dec. 2018  100% by Dec. 2020
QMS	All States	Indicator: % of States that have implemented QMS for AIS/AIM  Supporting Metric: Number of States that have implemented QMS for AIS/AIM	70% by Dec. 2016  90% by Dec. 2018
WGS-84	All States	Indicator: % of States that have implemented WGS-84 for horizontal plan (ENR, Terminal, AD)  Supporting Metric: Number of States that have implemented WGS-84 for horizontal plan (ENR, Terminal, AD)  Indicator: % of States that have implemented WGS-84 Geoid Undulation  Supporting Metric: Number of States that have implemented WGS-84 Geoid Undulation	Horizontal: 100% by Dec. 2017  Vertical: 90% by Dec. 2018

eTOD	All States	<p>Indicator: % of States that have implemented required Terrain datasets</p> <p>Supporting Metric: Number of States that have implemented required Terrain datasets</p> <p>Indicator: % of States that have implemented required Obstacle datasets</p> <p>Supporting Metric: Number of States that have implemented required Obstacle datasets</p>	<p>Area 1 : Terrain: 50% by Dec. 2015, 70% by Dec. 2018</p> <p>Obstacles: 40% by Dec. 2015, 60% by Dec. 2018</p> <p>Area 4: Terrain: 50% by Dec. 2015, 100% by Dec. 2018</p> <p>Obstacles: 50% by Dec. 2015, 100% by Dec. 2018</p>
Digital NOTAM*	All States	<p>Indicator: % of States that have included the implementation of Digital NOTAM into their National Plan for the transition from AIS to AIM</p> <p>Supporting Metric: Number of States that have included the implementation of Digital NOTAM into their National Plan for the transition from AIS to AIM</p>	<p>80% by Dec. 2016</p> <p>90% by Dec. 2018</p>

DRAFT



## B0 – AMET: Meteorological information supporting enhanced operational efficiency and safety

### Description and purpose:

Global, regional and local meteorological information:

- a) forecasts provided by world area forecast centres (WAFC), volcanic ash advisory centres (VAAC) and tropical cyclone advisory centres (TCAC);
- b) aerodrome warnings to give concise information of meteorological conditions that could adversely affect all aircraft at an aerodrome including wind shear; and
- c) SIGMETs to provide information on occurrence or expected occurrence of specific en-route weather phenomena which may affect the safety of aircraft operations and other operational meteorological (OPMET) information, including METAR/SPECI and TAF, to provide routine and special observations and forecasts of meteorological conditions occurring or expected to occur at the aerodrome.

This module includes elements which should be viewed as a subset of all available meteorological information that can be used to support enhanced operational efficiency and safety.

### Main performance impact:

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N	Y	Y	Y	Y

### Applicability consideration:

Applicable to traffic flow planning, and to all aircraft operations in all domains and flight phases, regardless of level of aircraft equipage.

<i>B0 – AMET: Meteorological information supporting enhanced operational efficiency and safety</i>			
Elements	Applicability	Performance Indicators/Supporting Metrics	Targets
<del>SADIS 2G and Secure</del> SADIS FTP	All States	Indicator: % of States that have implemented <del>SADIS 2G satellite broadcast or Secure</del> SADIS FTP service  Supporting Metric: Number of States that have implemented <del>SADIS 2G satellite broadcast or Secure</del> SADIS FTP service	90% by Dec. 2015  100% by Dec. 2017
QMS	All States	Indicator: % of States having implemented QMS for MET  Supporting metric: number of States having implemented QMS for MET	60% by Dec. 2015  80% by Dec. 2017
SIGMET	All MWOs in MID Region	Indicator: % of FIRs in which SIGMET is implemented  Supporting metric: number of FIRs SIGMET is implemented	90% by Dec. 2016  100% by Dec. 2018

**B0 – FRT0: Improved Operations through Enhanced En-Route Trajectories**

**Description and purpose:**

To allow the use of airspace which would otherwise be segregated (i.e. special use airspace) along with flexible routing adjusted for specific traffic patterns. This will allow greater routing possibilities, reducing potential congestion on trunk routes and busy crossing points, resulting in reduced flight length and fuel burn.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
Y	Y	Y	Y	N/A

**Applicability consideration:**

Applicable to en-route and terminal airspace. Benefits can start locally. The larger the size of the concerned airspace the greater the benefits, in particular for flex track aspects. Benefits accrue to individual flights and flows. Application will naturally span over a long period as traffic develops. Its features can be introduced starting with the simplest ones.

<b>B0 – FRT0: Improved Operations through Enhanced En-Route Trajectories</b>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
Flexible use of airspace (FUA)	All States	Indicator: % of States that have implemented FUA  Supporting metric*: number of States that have implemented FUA	40% by Dec. 2017
<b>Flexible routing</b>	All States	Indicator: % of required Routes that are not implemented due military restrictions (segregated areas)  Supporting metric 1: total number of ATS Routes in the Mid Region  Supporting metric 2*: number of required Routes that are not implemented due military restrictions (segregated areas)	60% by Dec. 2017

\* Implementation should be based on the published aeronautical information

***B0 – NOPS: Improved Flow Performance through Planning based on a Network-Wide view***

**Description and purpose:**

Air Traffic Flow Management (ATFM) is used to manage the flow of traffic in a way that minimizes delay and maximizes the use of the entire airspace. ATFM can regulate traffic flows involving departure slots, smooth flows and manage rates of entry into airspace along traffic axes, manage arrival time at waypoints or Flight Information Region (FIR)/sector boundaries and re-route traffic to avoid saturated areas. ATFM may also be used to address system disruptions including crisis caused by human or natural phenomena.

Experience clearly shows the benefits related to managing flows consistently and collaboratively over an area of a sufficient geographical size to take into account sufficiently well the network effects. The concept for ATFM and demand and capacity balancing (DCB) should be further exploited wherever possible. System improvements are also about better procedures in these domains, and creating instruments to allow collaboration among the different actors.

Guidance on the implementation of ATFM service are provided in the ICAO Doc 9971– Manual on Collaborative Air Traffic Flow Management

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
Y	Y	Y	Y	N/A

**Applicability consideration:**

Applicable to en-route and terminal airspace. Benefits can start locally. The larger the size of the concerned airspace the greater the benefits. Application will naturally span over a long period as traffic develops.

***B0 – NOPS: Improved Flow Performance through Planning based on a Network-Wide view***

Elements	Applicability	Performance Indicators/Supporting Metrics	Targets
ATFM Measures implemented in collaborative manner	All States	Indicator: % of States that have established a mechanism for the implementation of ATFM Measures based on collaborative decision  Supporting metric: number of States that have established a mechanism for the implementation of ATFM Measures based on collaborative decision	100% by Dec. 2017

**B0 – ACAS: ACAS Improvements**

**Description and purpose:**

To provide short-term improvements to existing airborne collision avoidance systems (ACAS) to reduce nuisance alerts while maintaining existing levels of safety. This will reduce trajectory deviations and increase safety in cases where there is a breakdown of separation

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N/A	N/A	Y	N/A	Y

**Applicability consideration:**

Safety and operational benefits increase with the proportion of equipped aircraft.

<b>B0 – ACAS: ACAS Improvements</b>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
Avionics (TCAS V7.1)	All States	Indicator: % of States requiring carriage of ACAS (TCAS v 7.1) for aircraft with a max certificated take-off mass greater than 5.7 tons  Supporting metric: Number of States requiring carriage of ACAS (TCAS v 7.1) for aircraft with a max certificated take-off mass greater than 5.7 tons	80% by Dec. 2015  100% by Dec. 2016

**B0 – CDO: Improved Flexibility and Efficiency in Descent Profiles (CDO)**

**Description and purpose:**

To use performance-based airspace and arrival procedures allowing aircraft to fly their optimum profile using continuous descent operations (CDOs). This will optimize throughput, allow fuel efficient descent profiles and increase capacity in terminal areas.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N	Y	Y	Y	Y

**Applicability consideration:**

Regions, States or individual locations most in need of these improvements. For simplicity and implementation success, complexity can be divided into three tiers:

- a) least complex – regional/States/locations with some foundational PBN operational experience that could capitalize on near term enhancements, which include integrating procedures and optimizing performance;
- b) more complex – regional/States/locations that may or may not possess PBN experience, but would benefit from introducing new or enhanced procedures. However, many of these locations may have environmental and operational challenges that will add to the complexities of procedure development and implementation; and
- c) most complex – regional/States/locations in this tier will be the most challenging and complex to introduce integrated and optimized PBN operations. Traffic volume and airspace constraints are added complexities that must be confronted. Operational changes to these areas can have a profound effect on the entire State, region or location.

**B0 – CDO: Improved Flexibility and Efficiency in Descent Profiles (CDO)**

Elements	Applicability	Performance Indicators/Supporting Metrics	Targets
PBN STARS	OBBI, HESN, HESH, HEMA, HEGN, HELX, OIIE, OISS, OIKB, OIMM, OIFM, ORER, ORNI, OJAM, OJAI, OJAQ, OKBK, OLBA, OOMS, OOSA, OTHH, OEJN, OEMA, OEDF, OERK, HSNN, HSOB, HSSS, HSPN, OMAA, OMAD, OMDB, OMDW, OMSJ	Indicator: % of International Aerodromes/TMA with PBN STAR implemented as required.  Supporting Metric: Number of International Aerodromes/TMAs with PBN STAR implemented as required.	100% by Dec. 2016 for the identified Aerodromes/TMAs  100% by Dec. 2018 for all the International Aerodromes/TMAs
International aerodromes/TMAs with CDO	OBBI, HESH, HEMA, HEGN, OIIE, OIKB, OIFM, OJAI, OJAQ, OKBK, OLBA, OOMS, OTHH, OEJN, OEMA, OEDF, OERK, HSSS, HSPN, OMAA, OMDB, OMDW, OMSJ	Indicator: % of International Aerodromes/TMA with CDO implemented as required.  Supporting Metric: Number of International Aerodromes/TMAs with CDO implemented as required.	100% by Dec. 2018 for the identified Aerodromes/TMAs

**B0 – CCO: Improved Flexibility and Efficiency Departure Profiles - Continuous Climb Operations (CCO)**

**Description and purpose:**

To implement continuous climb operations in conjunction with performance-based navigation (PBN) to provide opportunities to optimize throughput, improve flexibility, enable fuel-efficient climb profiles and increase capacity at congested terminal areas.

**Main performance impact:**

KPA- 01 – Access and Equity	KPA-02 – Capacity	KPA-04 – Efficiency	KPA-05 – Environment	KPA-10 – Safety
N/A	N/A	Y	Y	Y

**Applicability consideration:**

Regions, States or individual locations most in need of these improvements. For simplicity and implementation success, complexity can be divided into three tiers:

- a) least complex: regional/States/locations with some foundational PBN operational experience that could capitalize on near-term enhancements, which include integrating procedures and optimizing performance;
- b) more complex: regional/States/locations that may or may not possess PBN experience, but would benefit from introducing new or enhanced procedures. However, many of these locations may have environmental and operational challenges that will add to the complexities of procedure development and implementation; and
- c) most complex: regional/States/locations in this tier will be the most challenging and complex to introduce integrated and optimized PBN operations. Traffic volume and airspace constraints are added complexities that must be confronted. Operational changes to these areas can have a profound effect on the entire State, region or location.

<b>B0 – CCO: Improved Flexibility and Efficiency Departure Profiles - Continuous Climb Operations (CCO)</b>			
<b>Elements</b>	<b>Applicability</b>	<b>Performance Indicators/Supporting Metrics</b>	<b>Targets</b>
PBN SIDs	OBBI, HESN, HESH, HEMA, HEGN, HELX, OIIE, OISS, OIKB, OIMM, OIFM, ORER, ORNI, OJAM, OJAI, OJAQ, OKBK, OLBA, OOMS, OOSA, OTHH, OEJN, OEMA, OEDF, OERK, HSNN, HSOB, HSSS, HSPN, OMAA, OMAD, OMDB, OMDW, OMSJ	Indicator: % of International Aerodromes/TMA with PBN SID implemented as required.  Supporting Metric: Number of International Aerodromes/ TMAs with PBN SID implemented as required.	100% by Dec. 2016 for the identified Aerodromes/TMAs  100% by Dec. 2018 for all the International Aerodromes/TMAs
International aerodromes/TMAs with CCO	OBBI, HESN, HESH, HEMA, HEGN, HELX, OIIE, OIKB, OIFM, ORER, ORNI, OJAM, OJAI, OJAQ, OKBK, OLBA, OOMS, OOSA, OTHH, OEJN, OEMA, OEDF, OERK, HSNN, HSOB, HSSS, HSPN, OMAA, OMDB, OMDW, OMSJ	Indicator: % of International Aerodromes/TMA with CCO implemented as required.  Supporting Metric: Number of International Aerodromes/TMAs with CCO implemented as required.	100% by Dec. 2018 for the identified Aerodromes/TMAs

-END-