International Civil Aviation Organization

## Fifth Meeting of MIDANPIRG AIM Sub-Group

AIM SG/5 (Cairo, Egypt, 22-24 January 2019)

## **Agenda Item 5:** AIM Planning and Implementation in the MID Region

## GUIDANCE FOR AIM PLANNING AND IMPLEMENTATION IN THE MID REGION (MID DOC 008)

(Presented by the Secretariat)

#### **SUMMARY**

This paper presents an updated version of the Guidance for AIM Planning and Implementation in the MID Region (MID Doc 008) for review and update by the AIM SG.

Action by the meeting is at paragraph 3.

#### REFERENCES

- AIM SG/4 Report

## 1. Introduction

1.1 The MIDANPIRG/16 meeting, through MIDANPIRG Conclusion 16/10, endorsed the "Guidance for AIM Planning and implementation in the MID Region" as MID Doc 008.

## 2. DISCUSSION

- 2.1 The meeting may wish to recall that the AIM SG/3 meeting agreed that additional guidance related to the eANP Volume III Tables and in particular B0-DATM 3-1 "Provision of AIS/AIM products and services based on the Integrated Aeronautical Information Database (IAID)" should be included in the Guidance for a better and harmonized understanding.
- 2.2 The AIM SG/4 meeting reviewed and updated the MID Doc 008. An updated version of the MID Doc 008 is as at **Appendix A**.

## 3. ACTION BY THE MEETING

3.1 The meeting is invited to review and update the Guidance for AIM Planning and implementation in the MID Region (MID Doc 008) at **Appendix A**, for endorsement by MIDANPIRG/17.

\_\_\_\_\_



## INTERNATIONAL CIVIL AVIATION ORGANIZATION

## MIDDLE EAST AIR NAVIGATION PLANNING AND IMPLEMENTATION REGIONAL GROUP (MIDANPIRG)

# GUIDANCE FOR AIM PLANNING AND IMPLEMENTATION IN THE MID REGION

**EDITION APRIL, 2019** 

(Version 2.0)

The designations employed and the presentation of material in this publication do not imply the expression of any opinion whatsoever on the part of ICAO concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontier or boundaries.

## **RECORD OF AMENDMENTS**

Edition Number	Edition Date	Description	Pages Affected
0.1	1 September 2015	Initial draft version	All
0.2	7 October 2015	Inputs incorporated by AIM SG/2	All
0.3	April 2016	Change in Doc title; improving order and content of chapters; States comments considered; Reviewed by MSG/5	All
0.4	November 2016	Review by ANSIG/2	All
1.0	February 2017	Endorsed by MIDANPIRG/16	All
1.1	February 2018	AIM SG/4	All
1.2	January 2019	AIM SG/5	All

## TABLE OF CONTENTS

RECORD OF AMENDMENTS	3
Table of Contents	4
FOREWARD	6
Abbreviations and Acronyms	7
Chapter 1: ICAO AIM CONCEPT	9
Introduction	9
Transition from AIS to AIM	9
ICAO Roadmap for the transition from AIS to AIM	9
AIS-AIM Study Group	11
Information Management Panel (IMP)	12
Chapter 2	13
REGIONAL AIM PLANNING	13
Regional Roadmap for AIM Implementation	13
Chapter 3	15
ASBU FRAMEWORK AND THE MID AIR NAVIGATION STRATEGY (AIM/S' ASBU MODULES)	
ASBU Framework	15
MID Region Air Navigation Strategy	16
B0-DATM Implementation	16
Aeronautical Information Exchange Model (AIXM)	20
electronic AIP (eAIP)	20
Quality Management System (QMS)	
World Geodetic System-1984 (WGS-84)	
terrain and Obstacle Dataset (TOD)	
AIM/SWIM related Modules	

Performance Improvement Area 2: Globally Interoperable Systems and Data – Thro Interoperable System Wide Information Management	•
Block 0 (2013)	23
Block 1 (2018)	23
Block 2 (2023)	23
Block 3 (2028)	23
Chapter 4	25
AIM NATIONAL PLANNING AND IMPLEMENTATION	25
AIM National Planning	25
Implementation of a system for AIRAC adherence monitoring	25
Air Navigation Deficiencies	27
Human Resource and Training	28
Chapter 5	29
REPORTING AND MONITORING	29
MID eANP Volume III	29
Regional Performance Dashboard	29
MID Region Air Navigation Report	29
methodology for reporting the progress of AIM implementation	30
APPENDICES	34
Appendix A: NATIONAL AIM implementation ROADMAP TEMPLATE	35
Appendix B: AIRAC ADHERENCE MONITORING	37
Appendix C: Sample State's Corrective action plan	38
References	39

## **FOREWARD**

The "Guidance for AIM Planning and Implementation in the MID Region" has been developed to harmonize transition from AIS to AIM in the MID Region and to addresses Global and Regional issues related to planning and implementation of Aeronautical Information Management. This Regional AIM Guidance material explains concept and operational elements of AIM; outlines the Regional and National AIM Roadmaps; and provides guidance and tools for their implementation at the Regional and National levels.

This Document consolidates updates and supersedes all previous guidance materials on the AIM implementation in the MID Region (National AIM Roadmap Template, Regional AIM Roadmap, etc.). The "Guidance for AIM Planning and Implementation in the MID Region" will be reviewed and updated, whenever deemed necessary, by the AIM Sub-Group.

First edition of the Document, developed by the ICAO MID Regional Office, was endorsed by MIDAPIRG/16 (Kuwait, 13-16 February 2017).

The Document was prepared in accordance with ICAO provisions related to AIM, including Global ATM Operational Concept, Global Air Navigation Plan, Aviation System Block Upgrades (ASBU) methodology, MID Region Air Navigation Plan and the MID Region Air Navigation Strategy. States are recommended to use this document and notify their experiences and practices related to transition from AIS to AIM.

Note - Provisions of this document are recommended practices and do not – under any circumstances – substitute/replace any of the ICAO SARPS related to AIS/AIM (e.g. Annex 15).

## ABBREVIATIONS AND ACRONYMS

The abbreviations and acronyms used in this document along with their expansions are given in the following List:

AI Aeronautical Information

AICM Aeronautical Information Conceptual Model

AIP Aeronautical Information Publication

AIRAC Aeronautical Information Regulation and Control

AIS Aeronautical Information Services

AIS-AIM SG AIS to AIM Study Group

AIM Aeronautical Information Management

AIM SG Aeronautical Information Management Sub-Group

AIXM Aeronautical Information Exchange Model

AN-Conf/11 Eleventh Air Navigation Conference

AN-Conf/12 Twelfth Air Navigation Conference

ANP Air Navigation Plan

ANSP Air Navigations Services Provider

ASBU Aviation System Block Upgrade

ATM Air Traffic management

eAIP electronic Aeronautical Information Publication

eANP electronic Air Navigation Plan

TOD terrain and Obstacle Data

GANP Global Air Navigation Plan

GANR Global Air Navigation Report

GIS Geographic Information System

GML Geography Mark-up Language

IM Information Management

IMP Information Management Panel

ISO International Organization for Standardization

MET Meteorology

MIDAD MID Region AIM Database

MIDANPIRG Middle East Air Navigation Planning and Implementation Regional Group

MIL Military

MSG MIDANPIRG Steering Group

PBN Performance-Based Navigation

QMS Quality Management System

RWY Runway

SARPs Standards and Recommended Practices

SMART Specific, Measurable, Achievable, Relevant and Timely

SWIM System Wide Information Management

TORs Terms of Reference

UML Unified Modelling Language

WGS-84 World Geodetic System-1984

XML Extensible Mark-up Language

## **CHAPTER 1: ICAO AIM CONCEPT**

#### INTRODUCTION

- 1.1 The Eleventh Air Navigation Conference (AN-Conf/11) held in Montréal, 22 September to 3 October 2003, endorsed the Global ATM Operational Concept (Doc 9854) and recognized that, in the global air traffic management (ATM) system environment envisioned by the operational concept, aeronautical information service (AIS) would become one of the most valuable and important enabling services. As the global ATM system foreseen in the operational concept was based on a collaborative decision-making environment, the timely availability of high-quality and reliable electronic aeronautical, meteorological, airspace and flow management information would be necessary. Some recommendations of AN-Conf/11 addressed the importance of aeronautical information in particular.
- 1.2 Information management provides accredited, quality-assured and timely information used to support ATM operations. Information management will also monitor and control the quality of the shared information and provide information-sharing mechanisms that support the ATM community (ICAO DOC 9854 *Global ATM Operational Concept*).
- 1.3 Aeronautical Information Management (AIM) is the provision of the right Aeronautical Information (quality assured), at the right place (through digital exchange), and at the right time (timeliness). ICAO Annex 15 defines AIM as the dynamic, integrated management of aeronautical information through the provision and exchange of quality-assured digital aeronautical data in collaboration with all parties.
- 1.4 The Twelfth Air Navigation Conference (AN-Conf/12) held in Montréal, 19 to 30 November 2012, through Recommendations 3/7 and 3/8, supported and pushed:
  - Transition from AIS to AIM by implementing a fully automated digital aeronautical data chain;
  - Implementing necessary processes to ensure the quality of aeronautical data; and
  - Engage in intraregional and interregional cooperation for an expeditious transition from AIS to AIM in a harmonized manner and to using digital data exchange and consider regional or sub regional AIS databases as an enabler for the transition from AIS to AIM information from the origin to the end users

## TRANSITION FROM AIS TO AIM

## ICAO Roadmap for the transition from AIS to AIM

- 1.5 The aeronautical information/data based on paper and telex-based text messages can not satisfy anymore the requirements of the ATM integrated and interoperable system. AIS is required to evolve from the paper product-centric service to the data-centric aeronautical information management (AIM) with a different method of information provision and management.
- 1.6 ICAO published in 2009 the "Roadmap for the transition from AIS to AIM". The changes foreseen are such that this development is being referred to as the transition from aeronautical information services (AIS) to aeronautical information management (AIM). It identifies the major milestones recommended for a uniform evolution across all regions of the world and specific steps that need to be achieved for implementation.

Note – Development of a Global AIM Implementation Strategy by ICAO is in progress.

- 1.7 The Roadmap envisaged the transition into three phases and twenty one steps. Three phases of action are envisaged for States and ICAO to complete the transition to AIM:
- Phase 1 Consolidation

Phase 1 is the pre-requisite for the transition from AIS to AIM (implementation of the current SARPs). In Phase 1, QMS implementation is still a challenge for some States.


Phase 2 — Going digital

Main components of the Phase 2 are:

- Data-driven processes for the production of the current products;
- Introduction of structured digital data from databases into AIS/AIM processes;
- Introduction of highly structured databases and tools such as GIS;
- Terrain and Obstacle Datasets; and
- Implementation of aeronautical information conceptual model (AICM).
- Phase 3 Information management

Main components of the Phase 3 are:

- Enabling AIM functions to address the new requirements of the Global ATM Operational Concept in a net-centric information environment;
- Transfer of information in the form of digital data based on the established databases; and
- Aeronautical data exchange model ensuring interoperability between all systems.



Positioning of the 21 steps of the roadmap in the three phases

## AIS-AIM Study Group

- 1.8 The Air Navigation Commission in 2008 agreed to the establishment of AIS-AIM SG in order to assist with the development of:
- A global strategy/roadmap for the transition from AIS to AIM;
- SARPs and guidance material related to the provision of a standard AICM and standard AIXM to enable the global exchange of data in digital format; and
- Other SARPs, guidance material and training material necessary to support AIM implementation.
- 1.9 Some achievements of the AIS-AIM Study Group have been as follows:
  - ICAO Roadmap for transition from AIS to AIM;
  - Amendments to Annex 15:
    - Amendment 36: New provisions related to the operational use of the public Internet; volcanic ash deposition; QMS; use of automation enabling digital data exchange; eAIP; NOTAM Format; and TOD.

- o Amendment 37: Annex 15 restructuring; Chapter 1 (General), Chapter 2 (Responsibilities and functions) and Chapter 3 (Aeronautical Information Management) introduced in Nov 2014;
- o Amendment 40: Chapters 4 (Scope of AI and data), Chapter 5 (AI Products and services) and Chapter 6 (AI updates) instead of current Chapters 4-11 (Applicability date November 2018).
- New PANS AIM (ICAO DOC 10066) (Applicability date November 2018)
- Development of Aeronautical Data Catalogue (Appendix A to the new PANS AIM)
- Development of Training Manual, Quality Manual, update of AIS Manual (Doc 8126) (in progress)
- 1.10 AIS-AIMSG/12 was the last AIS-AIMSG held in Montreal, Canada from 19 to 23 October 2015. Materials related to the AIS-AIM SG including the meetings' Study Notes, Information Papers and Summary of Discussions are available on the ICAO AIM website at:

http://www.icao.int/safety/ais-aimsg/Pages/default.aspx

## Information Management Panel (IMP)

- 1.11 The Air Navigation Commission in 2014 agreed to the establishment of the Information Management Panel (IMP) to elaborate on necessary concepts and develop a global and interoperable approach to ensure effective management of information within the global air navigation system. The IMP will undertake tasks relating to the global transition from AIS to AIM, based upon Recommendations 3/1, 3/2, 3/3 and 3/9 of the Twelfth Air Navigation Conference in 2012 (AN-Conf/12).
- 1.12 Four (4) Working Groups were established to undertake tasks of the Panel:
  - Information Services and NOTAM
  - Information Architecture & Management
  - SWIM Awareness & Communication
  - SWIM Governance
- 1.13 Materials related to the IMP including the meetings' Working/Information Papers and Reports are available on the ICAO AIM website at:

http://www.icao.int/airnavigation/IMP/Pages/default.aspx

## **CHAPTER 2**

## **REGIONAL AIM PLANNING**

## REGIONAL ROADMAP FOR AIM IMPLEMENTATION

2.1 Having Phase I of the transition from AIS to AIM mostly completed in the MID Region, the focus should be on the implementation of phase II and III of the Roadmap for the transition from AIS to AIM. Accordingly, States should take into consideration the "MID Region AIM Implementation Roadmap" in planning for the transition from AIS to AIM in a prioritized manner.

## MID REGION AIM IMPLEMENTATION ROADMAP

	Related	20	16	20	017	20	18	20	19	20	20	20	21	20	22	Priority	Remarks	
	Steps	1	2	1	2	1	2	1	2	1	2	1	2	1	2			
AIXM	P07, P08															1	Target: 80% by 2018	
eAIP	P11															1	Target: 80% by 2020	
Integrated Aeronautical Information Database	P06															2		
Aeronautical Data Exchange	P09															2		
Interoperability with MET	P19															3		
Aeronautical Information Briefing	P12															3		
Agreement with data originators	P18															1		
Data Quality Monitoring	P01															1		
Data Integrity Monitoring	P02															1		
Terrain A-1	P13															2	Target: 70% by 2018	
Obstacle A-1	P14															2	Target: 60% by 2018	
Terrain A-4	P13															2	Target: 100% by 2018	
Obstacle A-4	P14															2	Target: 100% by 2018	
Terrain A-2a	P13															2		
Obstacle A-2a	P14															2		
Training	P16															1	Continuous	
Communication networks	P10															3		
Digital NOTAM	P21															3		
Electronic Aeronautical Charts	P20															3		
Terrain and Obstacle for Areas 2b, 2c, 2d and 3	P13, P14															3	Optional based on the States' decision to be reflected in the States' national Regulations and AIM National Plans, in accordance with operational needs	
Aerodrome Mapping	P15															3	Optional based on the States' decision to be reflected in the States' national Regulations and AIM National Plans, in accordance with operational needs	

White: Planning Light Green: Initial/On-going Implementation


Dark Green: Implemented (Performance Target achieved)

## **CHAPTER 3**

## ASBU FRAMEWORK AND THE MID AIR NAVIGATION STRATEGY (AIM & SWIM RELATED ASBU MODULES)

#### **ASBU FRAMEWORK**

- 3.1 ICAO introduced the Aviation System Block Upgrades (ASBU) framework in the fourth edition of the Doc 9750 (Global Air Navigation Plan), endorsed by the ICAO Assembly in 2013 (further revised by Assembly 39 in 2016), as a systemic manner to achieve a harmonized implementation of the air navigation services. An ASBU designates a set of improvements that can be implemented globally from a defined point in time to enhance the performance of the ATM system.
- 3.2 The GANP represents a rolling, 15-year strategic methodology which leverages existing technologies and anticipates future developments based on State/industry agreed operational objectives. The Block Upgrades are organized in six-year time increments starting in 2013 and continuing through 2031 and beyond.
- 3.3 ASBU methodology defines improvements, through modules, over four blocks in four performance improvements areas:



Note – Major changes will be introduced by the  $6^{th}$  Edition of GANP. New materials related to ASBU framework could be found on the GANP portal at: <a href="https://www4.icao.int/ganpportal">https://www4.icao.int/ganpportal</a>

#### MID REGION AIR NAVIGATION STRATEGY

Revised MID Region Air Navigation Strategy (MID Doc 002) was endorsed by the MIDANPIRG/16 meeting to introduce Block 0 ASBU Modules implementation priorities, elements, indicators and targets for the MID Region. It recognizes 12 (out of 18) Block 0 Modules as priority 1 in the MID Region (for more information refer to the MID Doc 002 in the ICAO Secure Portal at: <a href="https://portal.icao.int/RO\_MID/Pages/MIDDocs.aspx">https://portal.icao.int/RO\_MID/Pages/MIDDocs.aspx</a>).

#### **B0-DATM IMPLEMENTATION**

3.5 Block 0 contains 18 Modules and serves as the enabler and foundation for the envisioned future aviation systems. B0-DATM is a priority 1 ASBU Module in accordance with the MID Region Air Navigation Strategy (MID Doc 002). MID Doc 002 defines the B0-DATM as follows:

Note – detailed monitoring Tables of the B0-DATM is included in the MID eANP Volume III.

## **Description and purpose**

The initial introduction of digital processing and management of information, through aeronautical information service (AIS)/aeronautical information management (AIM) implementation, use of aeronautical information exchange model (AIXM), migration to electronic aeronautical information publication (AIP) and better quality and availability of data.

## Main performance impact:

KPA- 01 – Access and	KPA-02 –	KPA-04 –	KPA-05 –	KPA-10 –
Equity	Capacity	Efficiency	Environment	Safety
N	N	Y	Y	Y

## Applicability consideration:

Applicable at State level, with increased benefits as more States participate

B0 – DATM: Service Improvement through Digital Aeronautical Information Management						
Elements	Applicability	Performance Indicators/Supporting Metrics	Targets			
National AIM	All States	Indicator: % of States that have National AIM				
Implementation Plan/Roadmap		Implementation Plan/Roadmap	90% by Dec. 2018			
		Supporting Metric: Number of States that have				
		National AIM Implementation Plan/Roadmap				
AIXM	All States	Indicator: % of States that have implemented an				
		AIXM-based AIS database	80% by Dec. 2018			
		Supporting Metric: Number of States that have				
		implemented an AIXM-based AIS database				
eAIP	All States	Indicator: % of States that have implemented an IAID				
		driven AIP Production (eAIP)	80% by Dec. 2020			
		Supporting Metric: Number of States that have implemented an IAID driven AIP Production (eAIP)				

QMS	All States	Indicator: % of States that have implemented QMS for AIS/AIM  Supporting Metric: Number of States that have	90% by Dec. 2018
		implemented QMS for AIS/AIM	
WGS-84	All States	Indicator: % of States that have implemented WGS-84 for horizontal plane (ENR, Terminal, AD)	Horizontal: 100% by Dec. 2018
		Supporting Metric: Number of States that have implemented WGS-84 for horizontal plane (ENR, Terminal, AD)	Vertical: 90% by Dec. 2018
		Indicator: % of States that have implemented WGS-84 Geoid Undulation	
		Supporting Metric: Number of States that have implemented WGS-84 Geoid Undulation	
Agreement with data originators	All States	Indicator: % of States that have signed agreement with data originators	50% by Dec. 2018
		Supporting Metric: Number of States that have	
		signed agreement with data originators	
eTOD	All States	Indicator: % of States that have	Area 1 :
		implemented required Terrain datasets	Terrain: 70% by Dec. 2018
		Supporting Metric: Number of States that	Obstacles:
		have implemented required Terrain datasets	60% by Dec. 2018
		Indicator: % of States that have	Area 4:
		implemented required Obstacle datasets	<del>Terrain:</del>
			100% by Dec. 2018
		Supporting Metric: Number of States that have implemented required Obstacle datasets	Obstacles: 100% by Dec. 2018
Digital	All States	Indicator: % of States that have included the	10070 by Dec. 2016
NOTAM*	1211 210125	implementation of Digital NOTAM into their National Plan for the transition from AIS to AIM	90% by Dec. 2018

Supporting Metrie: Number of States that have included the implementation of Digital NOTAM into their National Plan for the transition from AIS to AIM	

## Aeronautical Information Exchange Model (AIXM)

- 3.6 The objective of the Aeronautical Information Exchange Model (AIXM) is to enable the provision in digital format of the aeronautical information that is in the scope of Aeronautical Information Services (AIS). The following main information areas are in the scope of AIXM::
  - Aerodrome/Heliport including movement areas, services, facilities, etc.
  - Airspace structures
  - Organisations and units, including services
  - Points and Navaids
  - Procedures
  - Routes
  - Flying restrictions
- 3.7 AIXM takes advantages of established information engineering standards and supports current and future aeronautical information system requirements.

Note - more information on AIXM could be found at: www.aixm.aero

## electronic AIP (eAIP)

- 3.8 The AIP, AIP Amendment, AIP Supplement and AIC should also be published in a format that allows for displaying on a computer screen and printing on paper. When provided, the eAIP should be available on a physical distribution medium (CD, DVD, etc.) and/or online on the Internet. When provided, the information content of the eAIP and the structure of chapters, sections and sub-sections shall follow the content and structure of the paper AIP. The eAIP shall include files that allow for printing a paper AIP.
- Note 1 This composite electronic document is named "Electronic AIP" (eAIP) and may be based on a digital data exchange format (e.g. AIXM).
- Note 2 The eAIP is not intended to support the Digital Notice to Airmen (NOTAM) process, as Digital NOTAM require a database of aeronautical information and are, therefore, not reliant on the eAIP.

Note 3 – States are recommended to take the Implementation of electronic AIP into their National AIS/AIM Regulation.

- 3.9 Aeronautical data and aeronautical information within the AIPs, AMDTs and SUPs should be made available, as a minimum, "in a way that allows the content and format of the documents to be directly readable on a computer screen".
- 3.10 The eAIP, as a minimum, should have help and search facility and provide history of current and previous amendments to users. It should also include a table of content. Format, display and content requirement for AIP Pages, AIP SUP, AIP Amendment and AIC should be in accordance with Annex15, Doc 8126 and other related SARPs.
- Note 3 More guidance material on the specifications of eAIP could be found in the EUROCONTROL Specifications for the electronic Aeronautical Information Publication (eAIP).

## Quality Management System (QMS)

- 3.11 Quality management systems shall be implemented and maintained encompassing all functions of an aeronautical information service. The execution of such quality management systems shall be made demonstrable for each function stage.
- Note 1 An ISO 9000 certificate issued by an accredited certification body would be considered an acceptable means of compliance.
- Note 2 Necessary measures should be taken for the signature of formal arrangements concerning data quality between AIS/AIM and the data originators, commensurate with the Aerodrome operators, Air Navigation Service Providers (ANSPs) and the Military Authority.
- 3.12 QMS implementation is still a challenge for some States. The challenges may include: Lack of adequate guidance material, lack of necessary competency (need for training), financial resources, etc.
- Note 3 Manual on the Quality Management System for Aeronautical Information Services (Doc 9839) Draft provides guidance on QMS implementation based on a stepwise approach (project-based).

## World Geodetic System-1984 (WGS-84)

3.13 World Geodetic System — 1984 (WGS-84) shall be used as the horizontal (geodetic) reference system for international air navigation. Consequently, published aeronautical geographical coordinates (indicating latitude and longitude) shall be expressed in terms of the WGS-84 geodetic reference datum.

WGS-84 for Enroute and Terminal areas as well as aerodromes and Geoid Undulation shall be introduced in the published coordinates in AIP

Note - Comprehensive guidance material concerning WGS-84 is contained in the World Geodetic System - 1984 (WGS-84) Manual (Doc 9674).

## Terrain and Obstacle Dataset (TOD)

- 3.14 TOD is an electronic set(s) of terrain and/or obstacle data for the defined coverage areas and with the defined data specifications to fulfill the needs of electronic air navigation applications for digital data. The coverage areas for sets of terrain and obstacle data shall be specified as:
- Area 1: the entire territory of a State;
- Area 2: within the vicinity of an aerodrome, subdivided as follows;
- Area 2a: a rectangular area around a runway that comprises the runway strip plus any clearway that exists.
- Area 2b: an area extending from the ends of Area 2a in the direction of departure, with a length of 10 km and a splay of 15 per cent to each side;
- Area 2c: an area extending outside Area 2a and Area 2b at a distance of not more than 10 km from the boundary of Area 2a; and
- Area 2d: an area outside the Areas 2a, 2b and 2c up to a distance of 45 km from the aerodrome reference point, or to an existing TMA boundary, whichever is nearest:
- Area 3: the area bordering an aerodrome movement area that extends horizontally from the edge of a runway to 90 m from the runway centre line and 50 m from the edge of all other parts of the aerodrome movement area.
- Area 4: The area extending 900 m prior to the runway threshold and 60 m each side of the extended runway centre line in the direction of the approach on a precision approach runway, Category II or III.
- 3.15 Terrain data shall be provided for Area 1 and 4. The obstacle data shall be provided for obstacles in Area 1 higher than 100 m above ground.
- Note 1 Comprehensive guidance material concerning TOD is contained in Annex 15 and the PANS AIM; the Guidelines for electronic terrain, obstacle and aerodrome mapping information (Doc 9881) and the EUROCONTROL Terrain and Obstacle Data Manual.
- Note 2 Description and method of obtaining of the TOD should be defined in AIP GEN 3.1.6.

Note 3 - TOD area 2b, 2c, 2d and 3 are recommendations, and States should take it into their National AIS/AIM Regulations.

## AIM/SWIM RELATED MODULES

3.16 Performance Improvement Area 2 (Globally Interoperable Systems and Data – Through Globally Interoperable System Wide Information Management) focuses on ASBU Modules which mainly support Collaborative Decision Making (CDM) through Information Management (i.e. Aeronautical Information, MET, Flight and Flow, etc.) in a SWIM environment. PIA 2 includes 11 Modules over 4 blocks as follows.

Note – Information on SWIM could be found in the ICAO Manual on System Wide Information Management (SWIM) Concept (DOC 10039).

PERFORMANCE IMPROVEMENT AREA 2: GLOBALLY INTEROPERABLE SYSTEMS AND DATA - THROUGH							
GLOBALLY INTEROPERABLE	E System Wide Informatio	ON MANAGEMENT					
Вьоск д (2013)	BLOCK 1 (2018)	BLOCK 2 (2023)	BLOCK 3 (2028)				
B0-FICE	B1-FICE	<b>B2-FICE</b>	B3-FICE				
Increased	Increased	Improved Coordination	Improved Operational				
Interoperability,	Interoperability,	through multi-centre	Performance through the				
Efficiency and Capacity	Efficiency and Capacity	Ground-Ground	introduction of Full FF-				
through Ground-Ground	though FF-ICE, Step 1	Integration: (FF-ICE/1	ICE				
Integration	application before	and Flight Object,					
	Departure	SWIM)					
B0-DATM	B1-DATM						
Service Improvement	Service Improvement						
through Digital	through Integration of all						
Aeronautical Information	Digital ATM Information						
Management							
	B1-SWIM	B2-SWIM					
	Performance	Enabling Airborne					
	Improvement through the	Participation in					
	application of System-	collaborative ATM					
	Wide Information	through SWIM					
	Management (SWIM)						
B0-AMET	B1-AMET		B3-AMET				
Meteorological	Enhanced Operational		Enhanced Operational				
information supporting	Decisions through		Decisions through				

enhanced operational	Integrated Meteorological	Integrated Meteorological
efficiency and safety	Information (Planning	Information (Near-term
	and Near-term Service)	and Immediate Service)

## **CHAPTER 4**

#### AIM NATIONAL PLANNING AND IMPLEMENTATION

#### **AIM NATIONAL PLANNING**

- 4.1 States should focus on the implementation of phase II and III of the ICAO Roadmap for the transition from AIS to AIM and take into consideration the "MID Region AIM implementation Roadmap" in planning for the transition from AIS to AIM in a prioritized manner
- 4.2 States are required to develop/update their National AIM Implementation Roadmap on an annual basis (by end of December), using the Template at **Appendix A** (National AIM Implementation Roadmap Template) and provide their feedback, lessons learned and difficulties to the ICAO MID Office for further assistance, as necessary.

#### IMPLEMENTATION OF A SYSTEM FOR AIRAC ADHERENCE MONITORING

- 4.3 Operationally significant changes to the AIP, listed in Annex 15, Appendix 4 shall be published in accordance with AIRAC procedures and shall be clearly identified by the acronym AIRAC.
- When an AIP Amendment or an AIP Supplement is published in accordance with AIRAC procedures, a NOTAM called "Trigger NOTAM" shall be originated giving a brief description of the contents, the effective date and time, and the reference number of the amendment or supplement.
- 4.5 The Trigger NOTAM shall be issued as soon as possible, preferably at the publication date of the AIRAC AIP Amendment or the AIP Supplement. This NOTAM shall come into force on the same effective date and time as the amendment or supplement and shall remain valid for a period of fourteen days.
- 4.6 The text in Item E) should start with the words 'TRIGGER NOTAM' (followed only in the case of an AIP Amendment by the abbreviation PERM), the reference number of the published AIP Amendment or AIP Supplement concerned, the effective date and a brief description of its contents.
- 4.7 Trigger NOTAM shall be issued in the appropriate NOTAM series, according to the information to be promulgated and shall follow the normal NOTAM procedures.

## Example:

- Q) HECA/QARTT/I/BO/000/999
- A) HECC B) 1704270000 C) 1705102359
- E) TRIGGER NOTAM PERM AIRAC AIP AMDT 4/17 WEF 27 APR 2017.

IMPLEMENTATION OF NEW ATS ROUTE UL111.

Note – the term 'PERM' is inserted in Item E) to stress that Item C) contains an artificial end-date and that the information is of a permanent nature.

- 4.8 When information has not been submitted by the AIRAC date, a NIL notification shall be originated and distributed by NOTAM or other suitable means, not later than one cycle before the AIRAC effective date concerned.
- 4.9 Implementation dates other than AIRAC effective dates shall not be used for pre-planned operationally significant changes requiring cartographic work and/or for updating of navigation databases.
- 4.10 Information provided under the AIRAC system in paper copy form shall be distributed by the AIS unit at least 42 days in advance of the effective date with the objective of reaching recipients at least 28 days in advance of the effective date. Information provided as electronic media, concerning the circumstances listed in Annex 15, Appendix 4 shall be distributed/made available by the AIS unit so as to reach recipients at least 28 days in advance of the AIRAC effective date.

**Recommendation** – Whenever major changes are planned and where advance notice is desirable and practicable, information provided as electronic media should be distributed/made available at least 56 days in advance of the effective date. This should be applied to the establishment of, and premeditated major changes in, the circumstances listed in Appendix 4, Part 3, and other major changes if deemed necessary.

- 4.11 AIS/AIM units should:
  - 1) raise the awareness of the Data Originators regarding the AIRAC provisions; and
  - 2) include necessary procedures related to AIRAC adherence in the arrangement with the Data Originators.
- 4.12 States should implement a system for AIRAC adherence monitoring and report on annual basis (by 31 December) to the ICAO MID Regional Office the case(s) of late publication of aeronautical information of operational significance and non-adherence to the AIRAC provisions. **Appendix B** could be used as a monitoring and reporting tool in the AIRAC adherence.

## 4.13 List of AIRAC effective dates for 2019 to 2021 is as follows:

2019	2020	2021
03 January	02 January	28 January
31 January	30 January	25 February
28 February	27 February	25 March
28 March	26 March	22 April
25 April	23 April	20 May
23 May	21 May	17 June
20 June	18 June	15 July
18 July	16 July	12 August
15 August	13 August	09 September
12 September	10 September	07 October
10 October	08 October	04 November
07 November	05 November	02 December
05 December	03 December	30 December
	31 December	

#### AIR NAVIGATION DEFICIENCIES

- 4.14 A deficiency is a situation where a facility, service or procedure does not comply with a regional air navigation plan approved by the Council, or with related ICAO Standards and Recommended Practices, and which situation has a negative impact on the safety, regularity and/or efficiency of international civil aviation.
- 4.15 Priority for action to remedy a deficiency is based on the following safety assessments:
- 'U' priority = Urgent requirements having a direct impact on safety and requiring immediate corrective actions. Urgent requirement consisting of any physical, configuration, material, performance, personnel or procedures specification, the application of which is urgently required for air navigation safety.
- 'A' priority = Top priority requirements necessary for air navigation safety. Top priority requirement consisting of any physical, configuration, material, performance, personnel or procedures specification, the application of which is considered necessary for air navigation safety.

- **'B' priority** = Intermediate requirements necessary for air navigation regularity and efficiency. Intermediate priority requirement consisting of any physical, configuration, material, performance, personnel or procedures specification, the application of which is considered necessary for air navigation regularity and efficiency.
- 4.16 MIDANPIRG is responsible to identify and address specific deficiencies in the air navigation field and to facilitate the development and implementation of an action plan by States to resolve identified deficiencies, where necessary.
- 4.17 States are required to use the MID Air Navigation Deficiency Database (MANDD) for the submission of requests for addition, update, and elimination of Air Navigation Deficiencies, including the submission of a specific Corrective Action Plan (CAP) for each deficiency. Each State MANDD Focal Point is given the required credential and MANDD is accessible at: <a href="http://www.icao.int/mid">http://www.icao.int/mid</a>
- 4.18 A Sample State's Corrective Action Plan (CAP) is provided as Appendix C for assistance to States in developing their CAPs for the Air Navigation Deficiencies.
- 4.19 States are required to submit a Formal Letter to the ICAO MID Regional Office containing the evidence(s) that mitigation measures have been implemented for the elimination of deficiency(ies) when requesting the elimination of deficiency(ies) from the MANDD.

#### **HUMAN RESOURCE AND TRAINING**

4.20 Within the context of the established quality management system, the competencies and the associated knowledge, skills and abilities required for each function shall be identified, and personnel assigned to perform those functions shall be appropriately trained. Processes shall be in place to ensure that personnel possess the competencies required to perform specific assigned functions. Appropriate records shall be maintained so that the qualifications of personnel can be confirmed. Initial and periodic assessments shall be established that require personnel to demonstrate the required competencies. Periodic assessments of personnel shall be used as a means to detect and correct shortfalls.

Note - Guidance material concerning training methodology to ensure the competency of personnel is contained in the Aeronautical Information Management Training Development Manual (Doc 9991).

## **CHAPTER 5**

#### REPORTING AND MONITORING

#### MID eANP VOLUME III

The status of implementation is reported and monitored by the AIM Sub-Group and through the B0-DATM Tables contained in the MID eANP Volume III. the MID eANP is available on the ICAO MID website at: <a href="http://www.icao.int/MID/Pages/MIDeANP.aspx">http://www.icao.int/MID/Pages/MIDeANP.aspx</a>

## REGIONAL PERFORMANCE DASHBOARD

- The 38th Assembly approved the Regional Performance Dashboards. The Dashboards aim to provide a glance of both Safety and Air Navigation Capacity and Efficiency strategic objectives, using a set of indicators and targets based on the regional implementation of the Global Aviation Safety Plan (GASP) and the Global Air Navigation Plan (GANP).
- ICAO introduced the Regional Performance Dashboards as a framework of nested reporting of results with an increased focus on implementation. The initial version of the dashboard shows the globally agreed targeted performance at the regional level and contains graphics and maps with a planned expansion to include regionally agreed targets and the Aviation System Block upgrades (ASBU) Block 0 Modules (i.e. AIM National Plan/Roadmap, AIXM, eAIP, TOD, WGS-84 and QMS).
- For the first edition of the Regional Performance Dashboards, the implementation of 3 steps from Phase I of the ICAO Roadmap for transition from AIS to AIM (AIRAC, QMS and WGS-84) is monitored. The dashboard can be accessed on the ICAO website at: http://www.icao.int/safety/Pages/Regional-Targets.aspx.
- It is agreed that in the expansion of the MID Regional Performance Dashboard, AIM National Roadmap, AIXM 5+, eAIP, TOD Area 1 and 4 should be added to the MID Region Dashboard.

#### MID REGION AIR NAVIGATION REPORT

The objective of the MID Region Air navigation Report is to monitor the status of implementation of the priority 1 ASBU Block 0 Modules in the MID Region as well as the outlook of ASBU implementation in 2020. The MID Region Air Navigation Report will be an annual document for reporting and monitoring the ASBU implementation in the MID Region. The Report is available on the ICAO MID Office website at: <a href="http://www2010.icao.int/MID/Pages/default.aspx">http://www2010.icao.int/MID/Pages/default.aspx</a>

#### METHODOLOGY FOR REPORTING THE PROGRESS OF AIM IMPLEMENTATION

5.7 "Methodology for assessing and reporting the progress of transition from AIS to AIM" (endorsed by MIDANPIRG/15) aims to develop a uniform method and plan for the reporting by the States on the progress achieved for the AIM transition, based on the ICAO Roadmap for Transition from AIS to AIM. The ICAO air navigation planning and implementation performance framework requires that reporting, monitoring, analysis and review activities be conducted on a cyclical, annual basis (ICAO DOC 9750). The Methodology is used while collecting data for monitoring the progress achieved in the transition from AIS to AIM and for the purpose of Regional Performance Dashboard, MID eANP, etc.

#### METHODOLOGY FOR REPORTING AND ASSESSING THE PROGRESS RELATED TO THE TRANSITION FROM AIS TO AIM

Element (Phase/Step/Step No.)		Metric/ Indicator	Finalization/Compliance Criteria	Link to ASBU Block	Remarks
1		2	3	4	5
Phase 1					
AIRAC adherence	P-03	FC/NC	<ul> <li>Implementation of a system for AIRAC adherence monitoring (compliance with annex 15 AIRAC provisions) (TBD)</li> <li>AIRAC adherence monitoring questionnaire (???)</li> </ul>	Block 0	
WGS-84 implementation	P-05	FC/PC/NC	National AIP GEN 2.1.3 'Geodetic reference datum' provides information about the implementation of WGS-84 in ENR, Terminal and AD	Block 0	
QMS	P-17	FC/NC	ISO 9001 Certification	Block 0	
Phase 2					
Data quality monitoring	P-01	FI/NI	QMS (P-17) and Agreement with data originators (P-18) is implemented (TBD)	Block 0	
Data integrity monitoring	P-02				Linked to P-01

Element (Phase/Step/Step No.)			Metric/ Indicator	Finalization/Compliance Criteria	Link to ASBU Block	Remarks	
1			2	3	4	5	
Integrated aeronautical		P-06 FI/NI		National aeronautical data and information is stored and maintained in AIXM-based AIS database	Block 0	Structured AI Database with digital exchange capabilities (AIXM 5.1)	
information database	Implementation of IAID		FI/PI/NI	Implementation of a database providing eAIP (text, tables and charts) and NOTAM, linked to the terrain/obstacles and aerodrome mapping datasets (TBD)	Block 1		
Unique iden	tifiers	P-07				Linked to P-06	
	Aeronautical information P-08 conceptual model					Linked to P-06	
Electronic A	Electronic AIP		FI/NI	National AIP GEN 3.1.3 'Aeronautical publications' provides information about the availability of the National AIP in electronic format (eAIP)			
Terrain	Area 1	P-13	FC/NC	National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on how the dataset can be obtained	Block 0		
Area 4		Area 4 P-13		National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on how the dataset for specific CAT II/III RWY can be obtained. States should indicate in remarks the number of existing CAT II/III RWY. N/A for States with no CAT II/III RWY.	Block 0	In case of PC, list name of CAT II/III ADs having the dataset	
	Area 2a	P-13	FC/PC/NC	National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on how the dataset can be obtained. States should indicate in remarks the number of AD eligible for provision of Area 2 data (ref MID eANP Table AOP I-1)	Block 0	In case of PC, list name of ADs having the dataset	
Take-off flight path area		ff flight path P-13 FC/PC/NC Same as		Same as Terrain Area 2a	Block 0	In case of PC, list name of ADs having the dataset	
	An area bounded by the lateral extent of the aerodrome obstacle limitation surfaces	P-13	FC/PC/NC	Same as Terrain Area 2a	Block 0	In case of PC, list name of ADs having the dataset	
Obstacles	Area 1	P-14	FC/NC	National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on	Block 0		

Element (Phase/Step/Step No.)		Metric/ Indicator	Finalization/Compliance Criteria	Link to ASBU Block	Remarks
1		2	3	4	5
			how the dataset can be obtained		
Area 4	P-14	FC/PC/NC or N/A	National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on how the dataset for specific CAT II/III RWY can be obtained. States should indicate in remarks the number of existing CAT II/III RWY. N/A for States with no CAT II/III RWY.	Block 0	In case of PC, list name of CAT II/III ADs having the dataset
Area 2a	P-14	FC/PC/NC	National AIP GEN 3.1.6 'Terrain and obstacle data' provides information on how the dataset can be obtained. States should indicate in remarks the number of AD eligible for provision of Area 2 data(ref MID eANP Table AOP I-1)	Block 0	In case of PC, list name of ADs having the dataset
objects in the take-off flight path area which project above a plane surface having a 1.2 per cent slope and having a common origin with the take-off flight path area	P-14	FC/PC/NC	Same as Obstacles Area 2a	Block 0	In case of PC, list name of ADs having the dataset
penetrations of the aerodrome obstacle limitation surfaces	P-14	FC/PC/NC	Same as Obstacles Area 2a	Block 0	In case of PC, list name of ADs having the dataset
Aerodrome mapping	P-15	FI/PI/NI	National AIP GEN 3.1 provides information on how the dataset can be obtained	Block 1	In case of PC, list name of ADs having the dataset
Phase 3					
Aeronautical data exchange	P-09	FI/PI/NI	Direct data exchange between AIS and data originators/users (TBD)	Block 1	In case of PC, list name of Units (Data Originators/Users)
Communication networks	P-10				
Aeronautical information briefing	P-12	FI/PI/NI	Provision of preflight aeronautical information briefing at the international aerodromes (TBD)  Mandatory for international aerodromes contained in the MID eANP Table AOP	Block 1	In case of PC, list name of ADs providing AI briefing

Element (Phase/Step/Step No.)		Metric/ Indicator	Finalization/Compliance Criteria	Link to ASBU Block	Remarks
1		2	3	4	5
			<u>I-1</u>		
Training	P-16				
Agreement with data originators	P-18	FI/PI/NI	Signed agreements between AIS and ANSPs (ATM, CNS, etc.), Aerodromes and Military	Block 0	In case of PC, list name of Data Originator(s)
Interoperability with meteorological products	P-19				Linked to P-12
Electronic aeronautical charts	P-20	FI/NI	National AIP GEN 3.2 'Aeronautical Charts provides information about the availability of the e-Aeronautical Charts	Block 1	
Digital NOTAM	P-21	FI/NI	TBD	Block 1	

FC: Fully Compliant; PC: Partially Compliant; NC: Not Compliant; FI: Fully Implemented; PI: Partially Implemented; NI: Not Implemented; N/A: Not Applicable

-----

## **APPENDICES**

## APPENDIX A: NATIONAL AIM IMPLEMENTATION ROADMAP TEMPLATE

											STATE DATE
Phase/Step	Step				Timeline	Start	End	Remarks			
	No.	2016	2017	2018	2019	2020	2021	2022			
Phase I	<u> </u>		•	•			•		•	<u> </u>	
AIRAC adherence	P-03										
WGS-84	P-05										
QMS	P-17										
Phase II								<u> </u>			
Data Quality Monitoring	P-01										
Data Integrity Monitoring	P-02										
AIXM	P-06								Ì		
Unique identifiers	P-07	100									
Aeronautical Information Conceptual Model	P-08										
eAIP	P-11										
Terrain Area 1	P-13										
Obstacle Area 1	P-14										
Terrain Area 4	P-13										
Obstacle Area 4	P-14										
Terrain Area 2	P-13										Please specify implementation of Area 2a, 2b, 2c and/or 2d
Obstacle Area 2	P-14				İ						Please specify implementation of Area 2a, 2b, 2c and/or 2d
Terrain Area 3	P-13										

Obstacle Area 3	P-14	1	-	İ	1	I							 	 
				2									 	 
AD Mapping	P-15					Ì								
Phase III		•	•				•	•				•		
Aeronautical data exchange	P-09													
Communication networks	P-10												 	 
Aeronautical information briefing	P-12													
Training	P-16								***************************************				 	 
Agreement with data originators	P-18													
Interoperability with METproducts	P-19													
Electronic aeronautical charts	P-20													
Digital NOTAM	P-21													 

	Not Started
Legend	In Progress
_	Implemented

## APPENDIX B: AIRAC ADHERENCE MONITORING

YEAR:	•••••		STATE:					
AIRAC EFF Date	AIRAC AMDT Serial Number; or NIL Notification	AIRAC AMDT PUB/Distribution Date	Trigger NOTAM (Serial Number)	No change until 28 days after EFF Date? (Yes / No)	Remarks			
	- AIRAC xx/xx; or - NIL notification issued on							
	- AIRAC xx/xx; or - NIL notification issued on							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	<ul><li>AIRAC xx/xx; or</li><li>NIL notification issued on</li></ul>							
	- AIRAC xx/xx; or - NIL notification issued on							
	- AIRAC xx/xx; or - NIL notification issued on							
	- AIRAC xx/xx; or - NIL notification issued on							

## APPENDIX C: SAMPLE STATE'S CORRECTIVE ACTION PLAN

DEFICIENCY DESC	PRIORITY (U/A/B)	
		RATIONALE F:Financial, H:HR, S:State, O:Other
STATE'S COMN	MENTS/OBSERVAT	TION
CORRECTIVE ACTION(S) PROPOSED	ACTION OFFICE/BODY	DATE OF COMPLETION

## **REFERENCES**

- ICAO Annex 15 Aeronautical Information Services
- ICAO DOC 9750 Global Air Navigation Plan
- ICAO DOC 9854 Global ATM Operational Concept
- ICAO DOC 10039 Manual on System Wide Information Management (SWIM) Concept
- ICAO DOC 10066 Procedures for Air Navigation Services Aeronautcial Information Management (PANS AIM)
- ICAO Roadmap for the transition from AIS to AIM
- EUROCONTROL Guidelines Operating procedures for AIS Dynamic Data (OPADD)
- EUROCONTROL Specifications for the electronic Aeronautical Information Publication (eAIP)
- EUROCONTROL Terrain and Obstacle Data Manual
- MIDANPIRG/15 Report
- MID Doc 002 MID Region Air Navigation Strategy
- MSG/4 Report
- <a href="http://www.aixm.aero">http://www.aixm.aero</a>
- http://www.icao.int/airnavigation/Documents/ICAO AN%20Report EN final 30042014.pdf
- http://www.icao.int/airnavigation/IMP/Pages/default.aspx
- <a href="http://www.icao.int/safety/ais-aimsg/Pages/default.aspx">http://www.icao.int/safety/ais-aimsg/Pages/default.aspx</a>
- http://www.icao.int/safety/Pages/Regional-Targets.aspx.
- https://portal.icao.int/RO MID/Pages/MIDDocs.aspx
- https://portal.icao.int/space/anp/Pages/Home.aspx