



**Twentieth Meeting of the CAR/SAM Regional Planning and Implementation Group  
 (GREPECAS/20)  
 Salvador, Brazil, 16 – 18 November 2022**

**Agenda Item 2: Global and Regional Developments**  
 2.3 Programmes and Projects Progress Report

**GUIDANCE FOR STATES ON PARAMETERS TO MONITOR THE PERFORMANCE  
 OF AUTOMATIC DEPENDENT SURVEILLANCE - BROADCAST (ADS-B) SYSTEMS**

(Presented by the Secretariat)

<b>EXECUTIVE SUMMARY</b>	
<p>This working paper presents the document entitled “Parameters to Monitor the Performance of ADS-B Systems”, developed in collaboration with members of the Surveillance Task Force (NACC/WG/SURV) during a meeting held in Mexico City, Mexico, from 13 to 15 July 2022 and approved by the North American, Central American and Caribbean Working Group (NACC/WG) in September 2022.</p>	
<b>Action:</b>	Suggested actions are presented in Section 3.
<i>Strategic Objectives:</i>	<ul style="list-style-type: none"> <li>• Air Navigation Capacity and Efficiency</li> </ul>
<i>References:</i>	<ul style="list-style-type: none"> <li>• Air Navigation Services (ANS) Surveillance Task Force (TF) Meeting, held in Mexico City, Mexico, from 13 to 15 July 2022.</li> <li>• Seventh North American, Central American and Caribbean Working Group Meeting (NACC/WG/7), held at the ICAO NACC Regional Office in Mexico City, Mexico, from 29 August to 1 September 2022:  <a href="https://www.icao.int/NACC/Pages/meetings-2022-naccwg7.aspx">https://www.icao.int/NACC/Pages/meetings-2022-naccwg7.aspx</a></li> </ul>

**1. Introduction**

1.1 At the Air Navigation Services (ANS) Surveillance Task Force (TF) Meeting, held in Mexico City, Mexico, from 13 to 15 July 2022, an Ad hoc group met to finalise a guidance document for ICAO Member States to use it when developing an Automatic Dependent Surveillance – Broadcast (ADS-B) analytical tool to monitor ADS-B performance and quality metrics. The Adhoc group was made up of representatives from Cuba, Mexico, United States, and the Central American Corporation for Air Navigation Services (COCESNA), all of whom have extensive experience in measuring the performance of ADS-B and the surveillance data of the different systems, and have made this knowledge available to the CAR region.

1.2 The purpose of this document is to help States with a guidance on elements to consider when developing a tool to monitor the performance of the ADS-B system in their respective airspace. The document identifies the general parameters that must be included to adequately evaluate the performance of Automatic Dependent Surveillance – Broadcast (ADS-B) OUT and perform statistical analyses of the ADS-B information received by a monitoring system.

1.3 The document was presented and analysed by the NAM/CAR States during the Seventh North American, Central American and Caribbean Working Group Meeting (NACC/WG/7) in September 2022 and approved for use in the region, not only for measuring ADS-B performance, but also for surveillance data in general, considering the following identified benefits:

1. provide knowledge based on experience,
2. help technical staff speak the same technical language,
3. support monitoring data exchange and failure analysis,
4. promote the continuous improvement of surveillance systems.

## **2. Practical application of the document.**

2.1 The document “Parameters to Monitor the Performance of ADS-B Systems” is based on experience from the implementation of the following systems:

1. Analysis Tool for ADS-B: *SurvSENSOR* application and *SurvREPORT* application, by Cuba’s *Instituto de Aeronáutica Civil (IACC)*.
2. Public ADS-B Performance Report (PAPR) User’s Guide, by United States’ Federal Aviation Administration (FAA).
3. ADS-B statistical analysis system, by COCESNA, based on its experience in managing *EUROCONTROL* applications.

2.2 In each one of the States and under the performance criteria required by the applications, the functioning of the surveillance systems and, especially, the operation of ADS-B are measured.

2.3 Recently, under a Mission of the ICAO Regional Technical Cooperation Project for the Caribbean Region – “Implementation of the Performance Based Air Navigation Systems” (RLA/09/801), the *SurvSENSOR* and *SurvREPORT* applications were implemented in Mexico, which has allowed the evaluation of 15 ADS-B sensors, as part of a project in Mexico.

2.4 In this sense, the implementation of this system based on a guide that evaluates the adequate performance criteria has allowed:

1. The storage of data for statistical analysis.
2. The standardization of the results obtained, which can be used to demonstrate the performance of the implementation of the surveillance systems and to analyse both from the side of the receivers on the ground, as well as the installed configuration of the ADS-B transponders on board the aircraft.
3. The statistics obtained of the flights detected is grouped by countries, airlines, aircraft type designator and by the ADS-B parameters of different versions.
4. The instant error identification of aircraft that had misconfigured 24-bit code encoding.

5. Above all, the experience of personnel from different States who speak the same language and interpret the same results due to the technical language that the guide establishes.

2.5 The document “Parameters to Monitor the Performance of ADS-B Systems” is attached to this working paper in the **Appendix**.

### **3. Suggested actions**

3.1 The Meeting is invited to take advantage of the lessons learned and good practices to:

- a) adopt the document “Parameters to Monitor the Performance of ADS-B Systems” as a regional guide for NAM/CAR/SAM States;
- b) take advantage of the guide to standardize the technical parameters for evaluating surveillance systems and thereby promote the use of the same technical language;
- c) thereby, standardize the implementation of regional ADS-B monitoring tools as much as possible; and
- d) discuss any other matter deemed appropriate.

-----



## PARAMETERS TO MONITOR THE PERFORMANCE OF ADS-B SYSTEMS

FIRST EDITION, JULY 2022



Approved by the ICAO NACC Regional Office for use in the CAR region  
**INTERNATIONAL CIVIL AVIATION ORGANIZATION**

**INTERNATIONAL CIVIL AVIATION ORGANIZATION  
ICAO NACC**

**PARAMETERS TO MONITOR THE  
PERFORMANCE OF ADS-B SYSTEMS**

**FIRST EDITION**

**MEXICO**

**JULY 2022**

## **Disclosure**

This document has been developed by members of the Surveillance Task Force (NACC/WG/SURV), part of the North American, Central American and Caribbean Working Group (NACC/WG) based on the ADS-B implementation and monitoring experience in the NAM/CAR region and for use by CAR States.

## CONTENT

AMENDMENTS .....	<b>Error! Bookmark not defined.</b>
1 GLOSARY .....	5
2 INTRODUCTION .....	6
3 REFERENCE DOCUMENTS .....	<b>Error! Bookmark not defined.</b>
4 DATA RECORDING .....	<b>Error! Bookmark not defined.</b>
5 GENERAL FILTERS FOR QUERIES .....	<b>Error! Bookmark not defined.</b>
6 GENERAL SPECIFICATIONS OF ADS-B DATA PROCESSING .....	<b>Error! Bookmark not defined.</b>
7 PERFORMANCE EVALUATION OF ADS-B SENSORS .....	12
8 STATISTICS GENERATION .....	13
9 PROBLEM REPORTS.....	13
APPENDIX A.....	<b>Error! Bookmark not defined.</b>
APPENDIX B.....	<b>Error! Bookmark not defined.</b>
APPENDIX C.....	43





## 1 GLOSARY

**ADS-B:** Automatic dependent surveillance - broadcast

**ADS-B OUT:** automatic dependent surveillance – broadcast

**ANSP:** Air Navigation Service Provider

**ASTERIX:** All-purpose structured Eurocontrol radar information exchange  
**IP/UDP:** Internet protocol/User Datagram Protocol

**NTP:** network time protocol

**SAC:** Fields System Area Code

**SIC:** System Identification Code

**UAP:** User Application Profile

## 2 INTRODUCTION

- 2.1 The purpose of this document is to identify the general parameters to evaluate the performance of the Automatic Dependent Surveillance - Broadcast (ADS-B OUT)<sup>1</sup> and to perform statistical analyses of the ADS-B information provided by aircraft using a performance monitoring system.
- 2.2 The above-mentioned is based on the following needs:
- a) Permanently, periodically and automatically monitor the performance of the ground and/or satellite-based ADS-B systems, as well as the information provided by the aircraft, ensuring compliance with the requirements established by the States for the use of ADS-B in its defined airspaces in accordance with its procedures and systems to guarantee operational safety.
  - b) Use minimum standardized criteria to perform ADS-B statistical analyses, including technical and operational criteria based on the requirements of each airspace.
  - c) Use ADS-B performance levels to filter data based on the different parameters to be measured.
  - d) Allow a common language of interpretation of the criteria and results of the statistical analysis of the ADS-B.
  - e) Identify the items required for statistical analysis; and
  - f) Support technical-operational decision-making.
- 2.3 The information collected may provide air navigation providers (ANSP), requesting aircraft, aircraft owners, operators, and companies responsible for installing and maintaining on-board equipment of statistical information on the capabilities, performance and data of position received by ground- or satellite-based ADS-B receivers, as an additional method of verifying the proper operation of the related ADS-B and on-board navigation systems.

---

<sup>1</sup> ADS-B OUT: Automatic Dependent Surveillance – Broadcast system is a function in an aircraft or vehicle that periodically transmits its vector state (position and speed) and other information derived from airborne systems in a format suitable for ADS - B IN. ICAO Doc 9924.

- 2.4 The data is useful to air navigation providers to monitor aircraft capabilities, conduct research and support with safety case analyses, and to aircraft avionics maintainers to perform post-installation and isolation conformance/configuration checks of failures.
- 2.5 Examples of existing ADS-B performance monitors created by Cuba, United States and COCESNA can be found in Appendix A, Appendix B and Appendix C of this document.

### 3 REFERENCE DOCUMENTS

- [1]. Annex 10, Aeronautical Telecommunications; Volume II, ICAO Communication Procedures, 7th Edition, July 2016.
- [2]. EUROCONTROL Specification for ASTERIX Surveillance Data Exchange, Part 12 Category 021, ADS-B Target Reports, 22 December 2021.  
<https://www.eurocontrol.int/sites/default/files/2021-12/asterix-adsbtr-cat021-part12-v2-6.pdf>
- [3]. Specification for Surveillance Data Exchange – Part 16 - ASTERIX (CNS/ATM Earth Stations and Station Status Reports) Cat 023, Edition 1.3, 27 September 2021.  
<https://www.eurocontrol.int/sites/default/files/content/documents/nm/asterix/cat023-asterix-cns-atm-ground-station-service-messages-part-16.pdf>
- [4]. Minimum operational performance standards for 1090 MHz Automatic Dependent Surveillance - Broadcast (ADS-B), EUROCAE ED-102A/RTCA DO-260B) RTCA/EUROCAE January 2012.

## 4 DATA RECORDING

- 4.1 The system should allow real-time data recording of ADS-B Version 0, 1 and 2 messages, received in Asterix CAT<sup>2</sup> 021 edition 0.23, 2.1, 2.4 and/or 2.6 format. Version 0.23 only allows formatting Version 0 messages and from edition 2.1 it is possible to additionally format versions 1 and 2. In the case of version 2.6 it will allow formatting ADS-B messages, Version 3. The recording must be done in the version that the server processes the surveillance data of the Control Centre Automation system.
- 4.2 Cat. 23 will be used to determine the technical status of each of the ground or satellite stations.
- 4.3 The system must process and decode all the fields and data items of the standard UAP (User Application Profile) for Asterix Cat. 21 and Cat. 23 in the latest implemented edition.
- 4.4 Data recording should be done over LAN, using IP/UDP and Unicast/Multicast protocols over redundant networks.
- 4.5 Each message should identify the ground and satellite based ADS-B sensor through the System Area Code (SAC) and System Identification Code (SIC) fields of the Asterix message. In the case of multiple ADS-B sensors, a server may be required to merge the information received.

**NOTE:** The SAC is established for each of the States at the following address:

<https://www.eurocontrol.int/asterix>

The SIC is established by the authority of each civil aviation of each State.

- 4.6 Both terrestrial and satellite-based systems and recording servers will need to be synchronized with Network Time Protocol (NTP) clocks for data formatting and data latency determination.

---

<sup>2</sup> CAT: Category

4.7 Recordings should be made continuously. Once the recording is finished and the data has been processed by the system, it should be available to users to generate the queries that are required from a suitable interface.

**NOTE:** Each state has to define the configurable recording time interval and data backup time.

## 5 GENERAL FILTERS FOR QUERIES

Queries or reports should be generated from the following information:

FIELD	DESCRIPTION
<b>24-bit ICAO address:</b>	Unique six-character ICAO 24-bit hexadecimal address assigned to an aircraft at the time of registration. The ICAO code is the same as the Mode S address.
<b>Flight ID or aircraft registration:</b>	Unique number assigned to the flight (call sign/registration), it should coincide with the call sign of the aircraft used in ATC communication. The air carrier could be identified for commercial aviation.
<b>Mode A code:</b>	Received by the aircraft in octal format and assigned by ATC
<b>Emitter Category:</b>	Indication of aircraft characteristics (type/size/weight/performance), important to identify wake turbulence.
<b>Start time:</b>	Time of the first monitored report of the flight in UTC time.
<b>Ending time:</b>	Time of last flight report in UTC.
<b>Start date:</b>	Flight starting date.
<b>Aircraft location area</b>	Select area of interest/volume of airspace.

**NOTA:** It should be related by means of the ICAO address, the aircraft registry and the make and model of the ADS-B and GPS transmitter. Related information should include aircraft type and model (see DOC 8643) and operators (see DOC 8585).

## 6 GENERAL SPECIFICATIONS OF ADS-B DATA PROCESSING

- 6.1 The system must have the capacity to process and identify all versions of ADS-B (DO-260, DO-260A, DO-260B and the new version DO-260C), with the correct processing of the figures of merit for each version<sup>3</sup>.
- 6.2 The system shall process WGS-84 position data including high resolution, geometric height, flight level and enhanced aircraft intent information for each message.
- 6.3 Decode the different identifications of the aircraft: ICAO 24-bit address, flight ID, Mode 3/A and emitter category.
- 6.4 For each report, the different times of the message will be stored: time of reception of the position and speed, time of applicability of the position and speed, including the times of high precision of the message.
- 6.5 For each report, the UTC date and time of recording of the message is stored for the purpose of performing message latency analysis.
- 6.6 The system must process the aircraft status fields, the aircraft report description fields, ACAS resolution, and the power amplitude of the message.
- 6.7 Data should be collected and identified for the following phases of flight whenever there is coverage of ADS-B receivers:
  - a) 1090 – In the air
  - b) 1090 – On ground

The surface information depends on whether a service volume covered by a ground- or satellite-based ADS-B receiver exists.
- 6.8 Identify the capacity or type of transmitted link for the ADS-B capacity (1090). The 1090ES is the standard used internationally and recommended by the ICAO. Using UAT is not recommended.
- 6.9 Process and store for each message the following figures of merit according to the version of the ADS-B standard, identifying the messages that do not comply with the criteria or rules defined for each State:

---

<sup>3</sup> The versions of ADS-B, Version 0, 1, 2, and 3, refer to the DO-260, DO-260A, DO-260B, or DO-260C operational performance standards that were used by avionics manufacturers.

- a) NACp (Navigation Accuracy Category for Position): This field indicates the accuracy of the position of the aircraft being transmitted.
  - b) NACv (Navigation Accuracy Category for Velocity): This field indicates the navigation accuracy for the velocity of the aircraft being transmitted.
  - c) NIC (Navigation Integrity Category): The NIC coding is used to indicate the containment radius around the aircraft.
  - d) SDA (System Design Assurance): Measures the probability of incorrect data being sent.
  - e) SIL (Surveillance/Source Integrity Level): Measurement of the probability of not being within the containment radius.
  - f) SILs (Surveillance/Source Integrity Level Supplement): This is a one-bit field that informs the system if the SIL is administered per hour or per sample. It is not considered a priority parameter.
  - g) SQL (Signal Quality Level): Measurement of the integrity of the data sent.
- 6.10 Identification of the classes of airspace in which the aircraft operated during the flight, as long as the system allows the processing of geographic information and the airspaces are defined.
- 6.11 Define and configure different types of performance rules depending on the ADS-B version and the combination of Figures of Merit (for example, NIC, NACp, etc.) and airspace.
- 6.12 Duration of the flight in the different reports, must indicate the total flight time measured in hours, minutes and seconds.
- 6.13 Calculate the availability and reliability of the ADS-B surveillance sensor, taking into account the information on the status of the ground station provided in Asterix CAT 023, which indicates when the information provided can be used for operational use.
- 6.14 Process the other fields of the UAP Standard CAT 21 and CAT 23 according to the implemented version.

## 7 PERFORMANCE EVALUATION OF ADS-B SENSORS

The system must allow the evaluation of the general performance of the ground- and/or satellite-based ADS-B systems independently and using multi-sensor information, which allows the determination of the following parameters:



- a) Total ADS-B reports
- b) Average update rate of ADS-B reports in seconds
- c) Update Probability (Pd) in general and by aircraft, according to the volume of traffic and type of airspace.
- d) Probability of false targets
- e) Mode A code detection probability
- f) Mode C code detection probability
- g) Size of the maximum and average gaps
- h) Unassociated reports

**NOTE:** Target information does not correspond to other aircraft information (eg: flight plan).

- i) Position error (RMS)
- j) Latency
- k) Availability based on the operational status of the sensors.
- l) Maximum, minimum and average time delays of communications.
- m) Coverage based on opportunity traffic, multi-sensor track and terrain elevation information.

## 8 STATISTICS GENERATION

The system through a user interface must allow the generation of the following statistics:

- a) Total number of ASTERIX ADS-B messages historically processed by the system.
- b) Number of aircraft with ADS-B capability filtered by date and time.
- c) Number of operations with ADS-B capacity per day.
- d) Percentage of aircraft with a different ADS-B version (DO-260, DO-260A, DO-260B or DO-260C).  
The number of aircraft with erroneous versions must be identified.
- e) Percentage of aircraft according to the value of each figure of merit.
- f) Percentage of aircraft that comply with the performance rule established for each airspace.
- g) Additionally, the system must use filters to obtain flight information according to date, time and selectable fields.
- h) Aircraft trajectory reports.

## 9 PROBLEM REPORTS

The system should make it possible to identify, for the different flights, common problems of erroneous information and poor ADS-B performance in order to carry out risk analysis, identify their possible causes and mitigate them. Such reports should include the following:

- a) Number and size of intervals due to loss of message during the flight or with data interruption.
- b) List of aircraft and duration of the flight in which erroneous information was transmitted.
- c) List of aircraft and duration of the flight with wrong or missing identification (aircraft ID) due to not being configured in the avionics. Including aircraft where the three-letter operator identifier is missing.
- d) List of aircraft and flight duration with mode 3/A identification assigned, during the entire flight or part of it.
- e) List of aircraft and flight duration with an incorrect ICAO 24-bit address or duplicate address.
- f) List of aircraft and duration of the flight with the emitter category missing or not configured in the avionics.
- g) List of aircraft and flight duration with missing figures of merit or with NIC, NACv, NACp, SIL and/or SDA category problems.
- h) List of aircraft and duration of the flight in which the ADS-B rule was breached. The ADS-B rule defines a combination of required figure of merit values.
- i) List of aircraft and flight duration with inconsistent ADS-B version and reported figure of merit value.
- j) List of aircraft and flight duration with loss of data from the barometric pressure altitude source (BARO ALT).
- k) Lists of aircraft and flight duration with loss of geometric altitude data (GEO ALT).
- l) List of aircraft with inconsistency in the reported flight phase (In Flight or Surface)
- m) List of aircraft in ACAS resolution.

Acknowledgements:

**Mr. Edey Marin**

Institute of Civil Aeronautics of Cuba (IACC)

**Mr. Alejandro Rodríguez**

Federal Aviation Administration (FAA), United States

**Mr. Cesar Núñez**

Central American Corporation for Air Navigation Services (COCESNA)

ICAO Regional Office for North America, Central America and the Caribbean  
Communications, Navigation and Surveillance.

# Appendix A

## Cuba ADS-B Analysis Tool

*Cuba has developed through the Institute of Civil Aeronautics of Cuba (IACC) a Software that contains two applications that provide monitoring and statistical analysis of Radar Surveillance Systems.*


*The tool is operating in Cuba and Mexico.*

### 1. SurvSENSOR App:


Application that receives data from aeronautical surveillance sensors (RADAR, ADS-B and/or MLAT) in ASTERIX format through a communications channel (RS-232, Ethernet UDP). Description of the system for the statistical analysis of Cuban aeronautical surveillance data.

The system developed in C++ consists of two applications with the following functionality:

Application that receives data from aeronautical surveillance sensors (RADAR, ADS-B and/or MLAT) in ASTERIX format through a communications channel (RS-232, Ethernet UDP).




SurvSENSOR has the functionality of representing, storing, and processing the information received, allowing in addition for the retransmission of the information.




First, a constant monitoring of the technical status of each of the coupled sensors is carried out, allowing to determine their operational status, calculating availability and reliability over time.

It calculates the number of bytes per second received by the data from each sensor having a reference of the channel bandwidth.

It contains the possibility of performing a horizontal and vertical coverage analysis, both as an independently coupled sensor and as a multi-sensor analysis.




Horizontal Coverage. (a) RADAR (b) ADS-B.



Vertical Coverage. (a) RADAR (b) ADS-B.

Having the representation of the real coverage of the detected data, the information can be correlated with the calculated theoretical coverage of each sensor at a determined flight level as shown in the following figure, making it possible to determine the possible zones of low or null probability of detection.



Correlation between theoretical and actual coverage. (a) RADAR (b) ADS-B.


## 2. SurvReport Application:

The application that statistically analyzes the information processed and stored from the SurvSENSOR application.










It has been shown in this analysis:

- A sustained growth of aircraft with ADS-B message transmissions.
- A decrease in transponders with the DO-260 / DO-260A versions, and an increase in the DO-260B Version.
- The predominant Navigation Integrity Category (NIC) is NIC =8.
- The predominant Navigation Accuracy Category (NAC) is NACp=9.
- Different errors and inconsistencies have been detected in the information correlation of the 24-bit Mode S codes.
- A high percentage of errors has been seen related to user input of the flight identification parameter on board the aircraft, not allowing the determination of the airline to which the flight belongs when the flight identification does not correspond to the registration.

#### 4. Collaboration and installation project in Mexico's Air Traffic Control Center (AFAC – SENEAM 2022-05)

In May 2022, through a collaborative project with AFAC-SENEAM, the statistical analysis tool was installed in Mexico, coupling several ADS-B sensors detecting the ADS-B message transmissions in a region of Mexico's FIR.



This scenario was fundamental for testing the stability of the system due to the high volume of available information.

The system continues to be dynamically developed with new possibilities arising from this collaborative project.

Below are examples of reports of the statistical analysis for some of the parameters.

# Reporte de Sistemas de Vigilancia


## FIR México



Tiempo Inicio: 2022-05-01 00:00    Tiempo Final: 2022-05-31 00:00  
 Tiempo de vuelo: 00:10:00 - 23:59:59    Espera: 20.0 min.  
 Región: ---    Nivel de vuelo: 10000 - 55000  
 Cobertura RADAR: ---    ADS-B: ---    MLAT: ---  
 M3/A: 0000 - 7777    Addr: 000000 - FFFFFFFF    ID:  
 DO260: 0 - 7    NICp: 6 - 11    NACp: 0 - 15    NACv: 0 - 7    SIL: 0 - 3 (Ave)



### Análisis por versión DO-260.



### Análisis de los datos según versión DO-260

Parámetros	Cantidad	Por ciento
DO-260 = 0 :	12	( 0.7%)
DO-260 = 1 :	0	( 0.0%)
DO-260 = 2 :	1625	( 99.1%)
DO-260 = 3 :	0	( 0.0%)
DO-260 = 4 :	0	( 0.0%)
DO-260 = 5 :	0	( 0.0%)
DO-260 = 6 :	0	( 0.0%)
DO-260 = 7 :	0	( 0.0%)
<b>Filtro :</b>	<b>1637</b>	


DO-260 Version

### Reporte de Sistemas de Vigilancia

#### FIR México

Tiempo Inicio: 2022-05-01 00:00    Tiempo Final: 2022-05-31 00:00  
 Tiempo de vuelo: 00:10:00 - 23:59:59    Espera: 20.0 min.  
 Región: --- Nivel de vuelo: 10000 - 55000  
 Cobertura RADAR: --- ADS-B: --- MLAT: ---  
 MSA: 0000 - 7777    Addr: 000000 - FFFFFFFF    ID:  
 DO260: 0-7 NICp: 6-11 NACp: 0-15 NACv: 0-7 SIL: 0-3 (Ave)

#### Análisis por (NICp) Categoría de Integridad de la Navegación por posición.



#### Análisis de los datos según NICp

Parámetros	Cantidad	Porcentaje
NICp = 0 :	0	( 0.0%)
NICp = 1 :	0	( 0.0%)
NICp = 2 :	0	( 0.0%)
NICp = 3 :	0	( 0.0%)
NICp = 4 :	0	( 0.0%)
NICp = 5 :	0	( 0.0%)
NICp = 6 :	0	( 0.0%)
NICp = 7 :	11	( 0.7%)
NICp = 8 :	1503	( 91.8%)
NICp = 9 :	114	( 7.0%)
NICp = 10 :	9	( 0.5%)
NICp = 11 :	0	( 0.0%)
NICp = 12 :	0	( 0.0%)
NICp = 13 :	0	( 0.0%)
NICp = 14 :	0	( 0.0%)
NICp = 15 :	0	( 0.0%)
<b>Filtro :</b>	<b>1637</b>	


### NIC

### Reporte de Sistemas de Vigilancia

#### FIR México

Tiempo Inicio: 2022-05-01 00:00    Tiempo Final: 2022-05-31 00:00  
 Tiempo de vuelo: 00:10:00 - 23:59:59    Espera: 20.0 min.  
 Región: --- Nivel de vuelo: 10000 - 55000  
 Cobertura RADAR: --- ADS-B: --- MLAT: ---  
 MSA: 0000 - 7777    Addr: 000000 - FFFFFFFF    ID:  
 DO260: 0-7 NICp: 6-11 NACp: 0-15 NACv: 0-7 SIL: 0-3 (Ave)

#### Análisis por (NACp) Categoría de Precisión de la Navegación por posición.



#### Análisis de los datos según NACp

Parámetros	Cantidad	Porcentaje
NACp = 0 :	12	( 0.7%)
NACp = 1 :	0	( 0.0%)
NACp = 2 :	0	( 0.0%)
NACp = 3 :	0	( 0.0%)
NACp = 4 :	0	( 0.0%)
NACp = 5 :	0	( 0.0%)
NACp = 6 :	0	( 0.0%)
NACp = 7 :	0	( 0.0%)
NACp = 8 :	11	( 0.7%)
NACp = 9 :	874	( 53.3%)
NACp = 10 :	738	( 45.0%)
NACp = 11 :	2	( 0.1%)
NACp = 12 :	0	( 0.0%)
NACp = 13 :	0	( 0.0%)
NACp = 14 :	0	( 0.0%)
NACp = 15 :	0	( 0.0%)
<b>Filtro :</b>	<b>1637</b>	


### NACp

### Reporte de Sistemas de Vigilancia

#### FIR México

Tiempo Inicio: 2022-05-01 00:00    Tiempo Final: 2022-05-31 00:00  
 Tiempo de vuelo: 00:10:00 - 23:59:59    Espera: 20.0 min.  
 Región: --- Nivel de vuelo: 10000 - 55000  
 Cobertura RADAR: --- ADS-B: --- MLAT: ---  
 MSA: 0000 - 7777    Addr: 000000 - FFFFFFFF    ID:  
 DO260: 0-7 NICp: 6-11 NACp: 0-15 NACv: 0-7 SIL: 0-3 (Ave)

#### Análisis por Aerolíneas.



#### Listado por Aerolíneas / Sistemas

No	Code	Airline Name	Count	RADAR	ADSB	MLAT
1	¿?	¿?	296	0	0	0
2	AA	American Airlines	35	0	35	0
3	ACA	Air Canada	10	0	10	0
4	AFR	Air France	2	0	2	0
5	AMX	Aeromexico	300	0	300	0
6	ANA	ANA - All Nippon Airways	2	0	2	0
7	ASA	Alaska Airlines	5	0	5	0
8	AVA	Avianca	6	0	6	0
9	BAW	British Airways	2	0	2	0
10	BVA	Berry Aviation	2	0	2	0
11	CCA	Air China	1	0	1	0
12	CFA	China Flying Dragon Aviation	1	0	1	0
13	CJT	Cargolux Airways	4	0	4	0
14	CLX	Cargolux	3	0	3	0
15	OMP	Comair Airlines	16	0	16	0
16	DAL	Delta Air Lines	22	0	22	0
17	DLH	Lufthansa	2	0	2	0
18	ENY	Envoy Air	1	0	1	0
19	ESF	Estafeta Cargo Aérea	11	0	11	0
20	FDX	FastEx Express	10	0	10	0
21	GEC	Lufthansa Cargo	3	0	3	0
22	GTT	Atlas Air	2	0	2	0
23	IBR	Iberia	3	0	3	0

### By Airline

### Reporte de Sistemas de Vigilancia

#### FIR México

Tiempo Inicio: 2022-05-01 00:00    Tiempo Final: 2022-05-31 00:00  
 Tiempo de vuelo: 00:10:00 - 23:59:59    Espera: 20.0 min.  
 Región: --- Nivel de vuelo: 10000 - 55000  
 Cobertura RADAR: --- ADS-B: --- MLAT: ---  
 MSA: 0000 - 7777    Addr: 000000 - FFFFFFFF    ID:  
 DO260: 0-7 NICp: 6-11 NACp: 0-15 NACv: 0-7 SIL: 0-3 (Ave)

#### Análisis por Aerolíneas.

#### Listado de vuelos por Aerolíneas.

No	Address	Register	Flight ID	Code	Cnt	260	NICp	NACp	NACv	SIL	SDA	OVA	Cumple
1	000680	¿?	XAAFA	?E?	1	2	8	10	2	3	2	2	ST
2	000000	¿?	XBPPE	?E?	1	2	9	10	2	3	2	2	ST
3	080C8D	¿?	XBBFE	?E?	1	2	9	10	2	3	2	2	ST
4	000920	¿?	XALOB	?E?	1	2	8	10	2	3	2	2	ST
5	000115	XATEP	XATEP	?E?	1	2	9	10	2	3	3	2	ST
6	000157	¿?	XAAVO	?E?	1	2	9	10	2	3	2	2	ST
7	0001AB	¿?	XAAAO	?E?	3	2	9	10	2	3	2	2	ST
8	000000	¿?	XBPPE	?E?	2	2	9	10	2	3	2	2	ST
9	000285	XAAFA	XAAFA	?E?	1	2	8	10	2	3	2	2	ST
10	000356	¿?	XAALE	?E?	2	2	9	10	2	3	2	2	ST
11	000366	¿?	XCBJG	?E?	1	2	10	10	1	3	2	2	ST
12	00038F	XBRJC	XBRJC	?E?	2	2	8	9	2	3	2	2	ST
13	000390	¿?	XADIS	?E?	1	2	8	10	2	3	2	2	ST
14	000423	XAGXG	XAGXG	?E?	1	2	8	10	2	3	2	2	ST
15	000501	¿?	XADRO	?E?	2	2	9	10	2	3	2	2	ST
16	00055F	XAAVZ	XAAVZ	?E?	1	2	8	10	1	3	2	2	ST
17	000576	XAONE	XAONE127	?E?	2	2	8	10	1	3	2	2	ST
18	0005FD	XABOX	XABOX	?E?	1	2	9	10	2	2	2	2	ST
19	00060P	XACAC	XACAC2400	?E?	1	2	8	10	1	3	2	2	ST
20	00065P	AKX12031AN	INELWF	?E?	2	2	8	10	2	3	2	2	ST
21	00067F	XAEGL	1201	?E?	1	2	9	10	2	3	2	2	ST
22	00067F	XAEGL	ACK1200	?E?	1	2	9	10	2	3	2	2	ST
23	00068A	¿?	XANOR	?E?	1	2	9	10	2	3	2	2	ST
24	0006C5	XAXTE	XAXGL000	?E?	1	2	10	10	1	3	2	2	ST
25	00071A	XAXTE	XAXTE	?E?	1	2	8	10	2	3	2	2	ST
26	000731	¿?	?E?	?E?	1	2	8	9	2	3	2	2	ST
27	00073D	XAGAT	XAGAT	?E?	1	2	8	10	1	3	2	2	ST
28	00075A	XALXL	XALXL	?E?	1	2	8	10	2	3	2	2	ST
29	00076A	XAMNA	XAMNA	?E?	1	2	8	10	1	3	2	2	ST
30	000794	XAXIS	XAXIS	?E?	1	2	8	10	1	3	2	2	ST
31	0007AA	XACAR1	XACAR1602	?E?	2	2	8	10	2	3	2	2	ST
32	0007DL	XAMMA	XAMMA	?E?	1	2	8	10	2	3	2	2	ST
33	0007E2	¿?	XALCD	?E?	1	2	8	10	1	3	2	2	ST

### by Complying Criteria

# **Appendix B**

## **Public ADS-B Performance Report (PAPR) User's Guide**



### **Flight Standards Service**

#### **ADS-B Focus Team**

**Aircraft Maintenance Division**

**Avionics Branch**

**March 2020**

## Background – Public ADS-B Performance Report

The purpose of the Public ADS-B Performance Report (PAPR) is to provide aircraft owners, operators, and avionics installers/maintainers with an additional method of verifying proper operation of ADS-B Out equipment.

The purpose of this User's Guide is to provide information to aid in the interpretation of data associated with a PAPR and to provide general guidance to help resolve avionics issues identified within a PAPR.

PAPR data provides information on the performance of an aircraft's ADS-B system for a specific flight and will verify proper ADS-B system operation or identify specific parameters received by the FAA's ground system which failed to comply with established standards. ADS-B system performance data identified within a PAPR will be useful to aircraft avionics maintainers when performing post-installation compliance/configuration checks and fault isolation.

A PAPR is typically available 1 hour after the end of the flight at the following web address <https://adsbperformance.faa.gov/PAPRRequest.aspx>. However, the availability of a PAPR may be delayed due to system maintenance or outages. unexpected. In cases where a PAPR is not available at the web address, the user must send an email to the following address [9-AWA-AFS-300-ADSBAvionicsCheck@faa.gov](mailto:9-AWA-AFS-300-ADSBAvionicsCheck@faa.gov), and include the following information:

1. Aircraft registration number (N number) in the subject line;
2. In the body of the email include
  - a. Flight identification code;
  - b. Date and time of the flight;
  - c. ADS-B transmitter and GPS make/model; Y
  - d. Any ADS-B avionics malfunction observed or reported during the associated flight.

# Part 1 – Public ADS-B Performance Report Explanation

The FAA collects data in the following flight phases by ADS-B link type (See Figure 1):

1. 1090 – Airborne
2. 1090 - Surface 4(Outside RWY/Taxi area)
3. 1090 - Surface RWY/Taxi
4. UAT - Airborne
5. UAT - Surface (Outside RWY/Taxi area)
6. UAT - Surface RWY/Taxi




Illustration of how data is collected in operation and analysis records

Figure 1

<sup>4</sup> Surface information is only provided at U.S. locations where a surface service volume exists. As of this writing, this is limited to the 35 airports with an ASDE-X system and KSFO. Eight additional surface service volumes will be added as the Airport Surface Surveillance Capability (ASSC) is deployed.

# PAPR Cover Page

The cover page contains basic information about the aircraft, flight date/time, and the type of ADS-B information received (1090, UAT, airborne/surface). Verify this information is correct.

**FEDERAL AVIATION ADMINISTRATION**

**U.S. Department of Transportation  
Federal Aviation Administration  
ADS-B Performance Monitor**

---

**Public ADS-B Performance Report**

ICAO: AD5FE9 (12345678)    Tail Number: NZZZZ    Last Flight Id: NZZZZ  
Period: 09-12-2017 05:47:51 to 09-12-2017 08:32

**Aircraft registration number corresponding to ICAO code**    **Last Flight Id received**

**Aircraft is on No Services List.** Please Review [Federal Register Notice](#)

---

**ICAO code (Mode S address) received**

**Flight date/time (UTC)**

**Aircraft is on the No Services Aircraft List (See Page 12)**

**Operation Analysis Overview**

	Analysis
Airborne 1090	<input checked="" type="checkbox"/>
Surface 1090	<input type="checkbox"/>
Surface RWY/Taxi 1090	<input type="checkbox"/>
Airborne UAT	<input type="checkbox"/>
Surface UAT	<input type="checkbox"/>
Surface RWY/Taxi UAT	<input type="checkbox"/>

**See Figure 1 on previous page for explanation**

---

Prepared By  
Surveillance and Broadcast Services (SBS) Program  
ADS-B Performance Monitor

October 12, 2017

**Note:** Items high-lighted in red within this report indicate the ADS-B Out system installed on this aircraft failed to meet the corresponding performance requirement as specified in § 91.227.  
For more information on this report, reference the [User's Guide](#).

OMB Control No. 2120-0728 | Expiration Date 4/30/2017

Each PAPR begins with an Operation Summary with specific information about the aircraft and flight. An example of an Operation Summary Table and definitions are provided below.



## Operation Summary Table Example

<b>Operation Summary</b>		
<b>Operation Id:</b> 55555555	<b>Start Time:</b> 09-12-2017 05:47:51	
<b>ICAO Reported:</b> AAABBB (12345678)	<b>End Time:</b> 09-12-2017 07:10:22	
<b>ICAO Assigned:</b> AAABBB (12345678)	<b>Duration:</b> 01:22:31	<b>Mod:</b> 01:22:31
<b>Tail Number:</b> NZZZZ	<b>Reports:</b> 10419	<b>Best Msg:</b> 9033
<b>Country:</b> United States - Civil	<b>Stationary:</b> No	<b>TIS-B Client %:</b> 0.0%
	<b>Baro Alt (ft):</b> 36975	<b>- 37000</b>
<b>Detection:</b> <input checked="" type="checkbox"/> Airborne <input type="checkbox"/> Surface		
<b>Link Version:</b> 2	<b>Out Capability:</b> 1090	<b>In Capability:</b>
<b>Last Flight Id:</b> NZZZZ		
<b>Operator:</b> ABC		

## Operation Summary Explanation Table

<b>Operation Id:</b> Unique number assigned to the flight record.		<b>Start Time:</b> Time flight was first monitored.
<b>ICAO Reported &amp; ICAO Assigned:</b> The 24- bit ICAO address (hexadecimal & octal formats) received from the aircraft.		<b>End time:</b> Time flight was last monitored.
<b>Tail Number:</b> The N-number associated with the aircraft’s reported 24-bit ICAO code.	<b>Duration:</b> Duration of the monitored flight in hours, minutes, and seconds.	<b>Mod:</b> Flight duration minus any data gaps greater than 36 seconds.
<b>Country:</b> Country associated with aircraft registration (identified via received ICAO hexadecimal code).	<b>Reports:</b> Number of ADS-B downlinks received during this operation.	<b>BestMSG:</b> Total reports minus any duplicate reports.
<b>Detection:</b> Flight mode(s) where aircraft was monitored (airborne and/or surface).	<b>Stationary Only:</b> “No” indicates aircraft was not stationary. “Yes” indicates aircraft was stationary for duration of this Operation.	<b>TIS-B Client %:</b> Percentage of operation time TIS-B data was provided to the aircraft by the ADS-B ground system.
<b>Link Version:</b> Link version of ADS-B transmitter. Link Version 2 is required by 14 CFR 91.225 and 14 CFR 91.227.	<b>Baro Alt (ft):</b> The minimum and maximum Barometric Pressure altitude reported by the aircraft.	<b>Rule:</b> Time spent within ADS-B Out Rule Airspace. Rule Airspace is defined in 14 CFR Part 91.225.
<b>Last Flight Id:</b> Last flight identification code received. This should be identical to the aircraft call sign used by ATC.	<b>Out Capability</b> Frequency used to transmit ADS-B data (i.e. 1090, 978/UAT, or Dual) or ADS-B OUT system type (UAT or 1090)	
<b>Operator:</b> Unique air operator identification code.		<b>In Capability:</b> Indication of capability to receive ADS- B data on specified link

## Dual-Out Inconsistencies

If an aircraft is equipped with a 1090 and a UAT system and transmitting on both frequencies (referred to as Dual-Out), the following table will be provided to identify any differences in the data received from each system. In the table below, the FAA ground system is receiving length/width codes from the 1090 and UAT avionics that do not match (LWC field is highlighted in red) for a Dual-Out equipped aircraft. See Part 3 of this report for table header definitions.

Dual Out Inconsistencies:						
Category	Emit Cat	Flight ID	Mode 3A	SAF	LWC	GPS Pos
% Fail	0.00%	0.00%	0.03%	0.00%	100.00%	100.00%
Max dT	00:00:00	00:00:00	00:00:04	00:00:00	00:02:56	00:02:56
MCF	0	0	4	0	338	338

## Performance Analysis Summary Tables

Analysis Summary tables are presented in the PAPER for some, or all, of the following categories depending on the installed ADS-B avionics configuration (1090 only, UAT only, or Dual-Out), areas of operation, and availability of ADS-B coverage:

- Airborne - 1090
- Surface - 1090 (Outside RWY/Taxi area)
- Surface RWY/Taxi - 1090
- Airborne - UAT
- Surface - UAT (Outside RWY/Taxi area)
- Surface RWY/Taxi UAT

The following definitions apply to all tables in each performance assessment category:

Category	Definitions
% Fail	Percentage of flight that corresponding category element failed performance assessment.
Max dT	Total time during flight the message element failed performance assessment.
MCF	Maximum number of consecutive received ADS-B messages in which the element failed Performance assessment.

Note: An example of a Performance Analysis Summary table and summary term definitions are provided on the next page.

## Analysis Summary Example (Airborne 1090)

<i>Airborne 1090 Analysis Summary</i>				
<b>Start Time:</b> 11-26-2015 20:25:18		<b>End Time:</b> 11-26-2015 22:06:55		
<b>Duration(s):</b> 01:41:37	<b>Mod:</b> 01:24:47	<b>Processed Reports:</b> 13444	<b>Total Reports:</b> 13491	
<b>Link Version:</b> 2		<b>Out Capability:</b> 1090	<b>In Capability:</b> UAT	
<b>Emitter Category:</b> 1 - Light (<15,500lbs)		<b>Antenna(s):</b> 1 - Single		
<b>Last Flight Id:</b> NZZZZ				
<b>Last Mode 3A:</b> 4511				
<b>Exceptions:</b>				
NIC	NACp	NACv	SIL	SDA
Yes	Yes	Yes	Yes	No

## Analysis Summary Explanation

<b>Start Time:</b> The start time of the flight as observed by ground monitoring.		<b>End Time:</b> The end time of the flight as observed by ground monitoring.
<b>Duration(s):</b> Duration of flight in hours, minutes, and seconds.	<b>Mod:</b> Duration minus any data gaps greater than 36 seconds.	<b>Processed Reports:</b> Number of reports processed by the ADS-B Ground system.
<b>Link Version:</b> Indicates which 1090/UAT standard the ADS-B equipment complies with. (For 1090 DO-260 = 0, DO-260A = 1, DO-260B = 2, etc.)	<b>Out Capability:</b> ADS-B OUT system type (UAT or 1090).	<b>In Capability:</b> ADS-B IN system type (UAT or 1090).
<b>Emitter Category:</b> Code associated With the aircraft's size, weight, or performance characteristics.	<b>Antenna(s):</b> Single or Dual (top and bottom) ADS-B antenna installed.	
<b>Last Flight Id:</b> The last reported Flight ID received from the aircraft.		
<b>Last Mode 3A:</b> Last discrete Mode 3/A code received.		
<b>Exceptions:</b> NIC/NAC/NACp/SIL/SDA Value: Indicates if aircraft failed to meet performance requirements of identified parameter: <b>Yes = Fail No = Pass</b>		

## Performance Assessment Tables

ADS-B equipment performance is divided into the following 4 major assessment categories:

1. **Required Message Elements Checks (Missing Elements):** Check of 14 CFR §91.227 (d) specified message elements required for broadcast by ADS-B Out avionics.
2. **Integrity and Accuracy Checks:** Check of ADS-B Out NIC/NACp/NACv/SDA/SIL performance requirements specified by 14 CFR §91.227(c) (Ref. latest version of Advisory Circular (AC) 20-165 for additional information).
3. **Kinematics:** Includes reasonableness checks of changes in Baro/Geo altitude, horizontal position, and velocity.
4. **Other Checks:** Checks of specific message parameters for values outside an expected range or fields that are improperly formatted (24-bit ICAO address, Mode 3A, emitter category, etc.).

See Part 3 of this report for table header definitions.

1. **Missing Elements:** Missing elements will be highlighted in red by category if aircraft failed to meet performance requirements.

### Missing Elements<sup>5</sup>

Category	NACp	NACv	Vel <sup>2</sup>	Flight Id	Mode 3A	Emit Cat
% Fail	0.00%	0.00%	27.15%	0.00%	0.00%	0.00%
Max dT	00:00:00	00:00:00	00:01:13	00:00:00	00:00:00	00:00:00
MCF	0	0	68	0	0	0

2. **Integrity & Accuracy:** Failed Integrity & Accuracy categories will be highlighted in red if aircraft failed to meet performance requirements. The FAA has not approved, or otherwise evaluated, any ADS- B position source with the horizontal velocity accuracy performance required to transmit a NACv value greater than 2 (NACv of 2 = Estimated Velocity Uncertainty <3 m/s). When NACv MIN and/or AVG are highlighted yellow in the Integrity & Accuracy table of the report (i.e. transmitted NACv MIN/AVG is 3 or 4) you are advised to contact your installer and/or applicable ADS-B avionics manufacturer for guidance on how to change the NACv value to that approved by the FAA at certification, or for non- certified equipment, a NACv value not to exceed 2 without FAA evaluation.

Integrity & Accuracy					
Category	NIC	NACp	NACv	SIL	SDA
% Fail	100.00%	100.00%	100.00%	100.00%	0.00%
Max dT	01:36:25	01:36:25	01:36:25	01:36:25	00:00:00
MCF	13444	13444	13444	13444	0

Category	NIC	NACp	NACv	SIL	SDA
Avg	0.0	0.0	0.0	1.0	2.0
Min	0	0	0	1	2
Max	0	0	0	1	2

**Integrity & Accuracy Note:** *If using an uncertified GPS (or portable transmitter) the system must report as SIL = 0 (zero). SIL=0 transmitters do not meet the requirements to become a TIS-B Service Client.*

<sup>5</sup> Note: The ADS-B Performance Monitor (APM) expects track angle data to be present in Velocity (Vel) messages when aircraft are moving on the surface above 10kts. Some avionics manufacturers have determined their system's track angle is unreliable at ground speeds above 10kts and withhold the data from the Vel message based on this determination. When this occurs an associated PAPR will indicate failures for Missing Element Vel within the Surface UAT/1090 Analysis section. Users are advised to contact their ADS-B equipment installer/avionics manufacturer for guidance when a PAPR indicates a failure for Missing Element Vel on the surface to determine if corrective action is required.

3. **Kinematics:** A reasonableness check is made of changes in Baro/Geo Altitude, Position, and Velocity. Items highlighted in red were identified with position changes outside the range expected for normal aircraft performance.

Kinematics							
	Velocity	Position Δ		Baro Alt	Baro Alt Δ	Geo Alt	Geo Alt Δ
% Fail	0.00%	0.00%		0.00%	0.00%	0.00%	0.00%
MCF	0	0		0	0	0	0

4. **Other Checks:** A percentage of the total operation (% Fail) and the maximum consecutive failures (MCF) that the ADS-B avionics failed to correctly broadcast these message elements.

Other Checks												
	Emitter Cat	Mode 3A										
% Fail	0.00%	0.00%										
Max dT	00:00:00	00:00:00										
MCF	0	0										
	Flight ID	Tail # Mismatch	Non-US	No "N"	Only "N"	Partial	Spaces	All Spaces	Illegal Char	Unavail Char	FP ID Mismatch	
% Fail	0.13%	0.00%	0.00%	0.00%	0.00%	0.00%	0.13%	0.00%	0.13%	0.00%	0.00%	
Max dT	00:00:02	00:00:00	00:00:00	00:00:00	00:00:00	00:00:00	00:00:02	00:00:00	00:00:02	00:00:00	00:00:00	
MCF	2	0	0	0	0	0	2	0	2	0		
	Air on Ground											
% Fail	0.00%											
Max dT	00:00:00											
MCF	0											

Other Checks table header definitions (See Part 3 of this guide):

**Emitter Category:** Percent, total time, and max consecutive reports aircraft reported an Emitter Category = 0.

**Mode 3A:** Percent, total time, and max consecutive reports aircraft was flagged as having an invalid Mode 3/A. In the majority of cases, this indicates if the aircraft did not report Mode 3/A via ADS-B for some or all of the flight.

**Flight ID:** The received Flight ID code is assessed in the following ways:

1. **Flight ID** = Percent, total time, and max consecutive reports aircraft reported an incorrect Flight ID (any flight ID error)
2. **Tail # Mismatch** = Percent, total time, and max consecutive reports aircraft reported a N-Number Flight ID that doesn't match the N-Number derived from the 24-bit ICAO (U.S. aircraft only) code.
3. **No-US** = Percent, total time, and max consecutive reports aircraft reported an N-Number Flight ID with a 24-bit ICAO address outside the U.S. block.
4. **No "N"** = Percent, total time, and max consecutive reports aircraft reported an N Number Flight ID without

the leading "N" (e.g., 123AB vs N123AB).

5. **Only "N"** = Percent, total time, and max consecutive reports aircraft reported just "N" for flight ID.
6. **Partial** = Mostly for Air Carriers, percent, total time, and max consecutive reports aircraft reported a Flight ID missing the leading three letter identifier (e.g. 1234 vs JBU1234).
7. **Spaces** = Percent, total time, and max consecutive reports aircraft including a space within a Flight ID.
8. **All Spaces** = Percent, total time, and max consecutive reports aircraft reported a Flight ID with eight spaces.
9. **Illegal Character** = Percent, total time, and max consecutive reports aircraft reported a Flight ID with an Illegal Character.
10. **Unavail Character** = Percent, total time, and max consecutive reports aircraft reported a Flight ID with an Unavailable Character.
11. **FP ID Mismatch** = Percent of total flight the aircraft's transmitted Flight ID did not match the aircraft identification information filed on the applicable flight plan.

**Note: The FP ID Mismatch field can be disregarded when no flight plan was filed for the flight associated with the P APR.**

12. **Air on Ground** = Percent, total time, and max consecutive reports the FAA ground system received airborne formatted messages while the aircraft was on the ground.

## Part 2 – Guidance for PAPR Faults

This section provides general guidance on common ADS-B performance issues and their possible causes. The information in this section is based on observations and feedback from avionics manufacturers, repair stations, and individual aircraft owner/operators. While the information is not specific to any make/model of ADS-B transmitter or GPS, users may find it helpful in determining a course of action to resolve issues identified within a PAPR.

**PAPR Fault Table**

<b>PAPR Fault (Red Field)</b>	<b>Possible Causes</b>
<b>Missing Elements and Integrity &amp; Accuracy Category Problems</b>	
NIC, NACv, NACp, SIL and/or SDA (100% fail)	<ul style="list-style-type: none"> <li>• Component and/or software compatibility with position source</li> <li>• Improper system configuration</li> </ul>
NIC, NACv, NACp, SIL and/or SDA (partial failure)	<ul style="list-style-type: none"> <li>• Intermittent loss of GPS service</li> <li>• Antenna masking caused by maneuvering</li> <li>• Portion(s) of flight at fringe of ADS-B coverage</li> <li>• Component software issue</li> </ul>
Flight ID (100% fail)	<ul style="list-style-type: none"> <li>• Flight ID not configured in avionics or Flight ID transmit is inhibited</li> </ul>
Flight ID missing (partial fail)	<ul style="list-style-type: none"> <li>• Flight at fringe of ADS-B coverage</li> </ul>
Mode 3/A (100% fail)	<ul style="list-style-type: none"> <li>• Because the FAA ground system auto-populates ADS-B messages with 1200 when the Mode 3/A code is missing to prevent risk associated with potential ATC conflict alerts this field should always show as passed. Refer to “Other Checks” below for guidance on Mode 3/A issues.</li> </ul>
Mode 3/A (partial failure)	<ul style="list-style-type: none"> <li>• See “Other Checks” below</li> </ul>
Baro Alt	<ul style="list-style-type: none"> <li>• Loss of data from barometric pressure altitude source (encoder)</li> </ul>
Geo Alt	<ul style="list-style-type: none"> <li>• Loss of geometric altitude data from GPS</li> </ul>
Emitter Category (Missing and Other)	<ul style="list-style-type: none"> <li>• Emitter category not configured into avionics or misconfigured</li> </ul>
Flight Identification Code errors	<ul style="list-style-type: none"> <li>• Flight ID not properly entered</li> </ul>
<b>Kinematics</b>	
All parameters	<ul style="list-style-type: none"> <li>• Component and/or software (version) compatibility</li> </ul>
<b>Other Checks</b>	
Air on Ground (ADS-B system transmitting in Air mode while on the ground)	<ul style="list-style-type: none"> <li>• Squat switch issue</li> <li>• GPS stall speed setting incorrect               <ul style="list-style-type: none"> <li>○ Too low a stall speed will result in avionics transitioning to Air mode during high speed taxi or takeoff-roll</li> <li>○ Avionics initializing in Air mode at startup</li> </ul> </li> </ul>

<b>PAPR Fault Table (continued)</b>	
<b>PAPR Fault (red)</b>	<b>Possible Causes</b>
<b>Other Checks (continued)</b>	
Emitter Cat	<ul style="list-style-type: none"> <li>• Inappropriate emitter category transmitted. e.g., many “Light” aircraft (&lt;15,500 lbs) incorrectly transmit as “Small” aircraft (15,500 – 75K lbs).</li> <li>• Rotorcraft transmitting fixed-wing emitter category</li> </ul>
Mode 3A (100% fail)	<ul style="list-style-type: none"> <li>• Mode 3/A or Call-sign logic transmit function disabled (UAT specific)</li> <li>• Mode 3/A code input device not providing data to UAT system</li> </ul>
Mode 3A (partial failure)	<ul style="list-style-type: none"> <li>• Portion(s) of flight at fringes of ADS-B coverage</li> <li>• Improper pilot input (late turn on/early turn off of transponder)</li> </ul>
No flight data found for specified date	<ul style="list-style-type: none"> <li>• Aircraft transmitting wrong 24-bit ICAO address</li> <li>• Late day flight (flight times are recorded in UTC)</li> <li>• Flight with UAT system operated in anonymous mode.</li> <li>• Possible ADS-B service outage</li> <li>• Aircraft not transmitting ADS-B data</li> </ul>

**ADS-B No Services Aircraft List (NSAL) Information**

**Background:** Reference FAA Notice Docket Number: FAA-2017-1194. To reduce the potential hazard presented by ADS-B non-performing equipment (NPE) aircraft, the FAA began filtering individual 24-bit ICAO address codes (also known as Mode S codes) for certain NPE aircraft from the FAA's operational ADS-B network on January 2, 2018. The filtering process is managed through an exclusion list referred to as the No Services Aircraft List (NSAL) which prevents processing of data within ATC systems transmitted by aircraft contained on the list. Aircraft on the NSAL cannot be provided ATC services (via ADS-B data) and are excluded from the provision of TIS-B services. If authorized by ATC, traffic services for aircraft on the NSAL may be supported via the backup transponder/radar surveillance system. The NSAL has no impact on an ADS- B equipped aircraft’s air-to-air capabilities.

Aircraft on the NSAL are identified by “Aircraft is on No Services List” on the cover page of an applicable PAPR. Since aircraft on the NSAL cannot be detected by ATC via their transmitted ADS-B data, each operation conducted in §91.225 airspace by applicable aircraft on the NSAL must be authorized by ATC before flight using the ADS-B Deviation Authorization Preflight Tool (ADAPT).

**Procedures for removal of aircraft from the NSAL:** The FAA provides written notice of NPE aircraft (with applicable NSAL information) to the person/entity and address associated with the aircraft’s registration.

Owner/operators receiving an NPE notification should contact the FAA representative identified on the letter as soon as possible. When a PAPR indicates an aircraft is on the NSAL but a NPE notification letter has not been received by the owner/operator, contact the FAA at the following email address: 9-AWA-AFS-300-ADSB-AvionicsCheck@faa.gov providing the PAPR associated with the aircraft’s most recent flight. An FAA



representative will contact you as soon as possible to discuss details associated with the performance of subject ADS-B equipment.

### Part 3

## ADS-B TERMS, DESCRIPTIONS AND REFERENCES

### Parameter Description

Field Name	Full name	Description
<b>Airborne Msgs on Surface</b>		Indication that airborne specific messages were received by the FAA ground system while aircraft was on the surface
<b>All Spaces</b>	Flight ID	Flight identification code contains all spaces
<b>Anonymous</b>		Indicates whether the unit is in Anonymous mode or not.
<b>Baro Alt/ Baro Alt Δ</b>	Barometric Altitude	Barometric altitude is sent and checked against aircraft performance criteria and flagged as invalid if determined to be incorrect or unreasonable. In general, if the reported baro or geo alt is greater than 20,000 meters (65,616ft) or less than -200 meters (-656ft), the report is flagged for investigation. If there's a change in baro alt greater than 656 feet/sec (200m/s), then the report is flagged for investigation.
<b>Class A</b>		Field marks classes of airspace the aircraft operated in during the flight. Part 91 Appendix D is a special class of airspace for certain airports.
<b>Class B</b>		
<b>Class C</b>		
<b>Class D</b>		
<b>Class E</b>		
<b>Part 91AppD</b>		
<b>Country</b>		Field Identifies the country of origin for the aircraft and the type of registration (e.g. United States- Civil, Military, etc.)
<b>Dup ICAO</b>	Duplicate ICAO	Each aircraft is assigned a unique 24-bit ICAO address. When two or more aircraft are monitored operating simultaneously with the same 24-bit ICAO address both aircraft (correct & incorrect 24-bit ICAO) will be flagged for Dup ICAO.
<b>Dup ICAO Duration</b>	Duration Dup ICAO operation occurred	This field marks the duration that a duplicate 24-bit ICAO address is observed.
<b>Duration</b>		Total flight time measured in hours, minutes, and seconds.

<b>Emitter Category</b>		<p>Indication of aircraft characteristics (type/size/weight/performance. Used by future ADS-B IN applications e.g., wake avoidance.</p> <p style="text-align: center;"><u>Set A</u></p> <p>0 = No ADS-B Emitter Category Information  1 = Light (&lt;= 15500 lbs)  2 = Small (15500 to 75000 lbs)  3 = Large (75000 to 300000 lbs)  4 = High Vortex Large (aircraft such as B-757)  5 = Heavy (&gt; 300000 lbs)  6 = High Performance (&gt; 5g acceleration and 400 kts)  7 = Rotorcraft</p>
<b>Flight ID</b>	Flight Identification Code	This should match the aircraft call sign used in ATC communication. Must match the aircraft call sign in any filed flight plan.
<b>Geo Alt/Geo Alt Δ</b>	Geometric Altitude	Received geometric altitude is checked against aircraft performance criteria and flagged as invalid if determined to be incorrect or unreasonable. In general, if the reported baro or geo alt is greater than 20,000 meters (65,616ft) or less than -200 meters (-656ft), the report is flagged. If there's a change in geo alt greater than 656 feet/sec (200m/s), this field will also be flagged.
<b>ICAO Assigned</b>		Unique six character ICAO address assigned to an aircraft at registration. ICAO code is the same as the Mode S address.
<b>ICAO Reported</b>		Unique six character ICAO address transmitted by the aircraft.
<b>Illegal Char</b>	Flight ID illegal character	Flight ID contains an incorrect character (e.g., letter O in place of the number zero, etc.)
<b>In capability</b>		Indicates the link type transmitted for the ADS-B IN capability (1090/UAT).
<b>Int/Acc</b>	Integrity and Accuracy	Category of values including NIC, NACp, and NACv.
<b>Kin</b>	Kinematics	Category of exceptions that includes Baro Alt, Baro Alt Δ, Geo Alt, Geo Alt Δ, Velocity, Position Δ. Position error checks.
<b>Length/Width Code</b>		Code received that indicates the length and width of the aircraft.
<b>Link Version</b>		Field marking what version of ADS-B the transponder is using. §91.225 and §91.227 require Link Version 2.
<b>MCF</b>	Maximum Consecutive Failures	The number of non-performing reports received that occur in a row (consecutively). If an MCF exceeds its threshold, an MCF exception is identified for that parameter.
<b>Mismatch</b>		Percent, total time, and max consecutive reports aircraft reported a N-Number Flight ID that doesn't match the N-Number derived from the 24-bit ICAO address.
<b>Missing report duration</b>		Time period of flight segment that ADS-B data was not received from the aircraft. This can be caused by failure of the avionics or transiting in and out of ADS-B coverage.
<b>Mode 3/A</b>		Four digit code (ATC assigned or 1200) set by the pilot

<p><b>NACp</b></p>	<p>Navigation Accuracy Category for Position</p>	<p>This field indicates the accuracy of the aircraft position being transmitted. §91.227 requires a minimum NACp of 8. A PAPER will be flagged red if the NACp of &lt;8 duration exceeds the allowable threshold.</p> <p><b>Table A-13: Encoding of Navigation Accuracy Category for Position (NACp)</b></p> <table border="1"> <thead> <tr> <th colspan="2">Coding</th> <th rowspan="2">Meaning = 95% Horizontal Accuracy Bounds (EPU)</th> </tr> <tr> <th>(Binary)</th> <th>(Decimal)</th> </tr> </thead> <tbody> <tr><td>0000</td><td>0</td><td>EPU ≥ 18.52 km (10 NM) - Unknown accuracy</td></tr> <tr><td>0001</td><td>1</td><td>EPU &lt; 18.52 km (10 NM) - RNP-10 accuracy</td></tr> <tr><td>0010</td><td>2</td><td>EPU &lt; 7.408 km (4 NM) - RNP-4 accuracy</td></tr> <tr><td>0011</td><td>3</td><td>EPU &lt; 3.704 km (2 NM) - RNP-2 accuracy</td></tr> <tr><td>0100</td><td>4</td><td>EPU &lt; 1852 m (1NM) - RNP-1 accuracy</td></tr> <tr><td>0101</td><td>5</td><td>EPU &lt; 926 m (0.5 NM) - RNP-0.5 accuracy</td></tr> <tr><td>0110</td><td>6</td><td>EPU &lt; 555.6 m ( 0.3 NM) - RNP-0.3 accuracy</td></tr> <tr><td>0111</td><td>7</td><td>EPU &lt; 185.2 m (0.1 NM) - RNP-0.1 accuracy</td></tr> <tr><td>1000</td><td>8</td><td>EPU &lt; 92.6 m (0.05 NM) - e.g., GPS (with SA)</td></tr> <tr><td>1001</td><td>9</td><td>EPU &lt; 30 m - e.g., GPS (SA off)</td></tr> <tr><td>1010</td><td>10</td><td>EPU &lt; 10 m - e.g., WAAS</td></tr> <tr><td>1011</td><td>11</td><td>EPU &lt; 3 m - e.g., LAAS</td></tr> <tr><td>1100 - 1111</td><td>12 - 15</td><td>Reserved</td></tr> </tbody> </table> <p>NACp values &lt; 8 will be flagged red.</p>	Coding		Meaning = 95% Horizontal Accuracy Bounds (EPU)	(Binary)	(Decimal)	0000	0	EPU ≥ 18.52 km (10 NM) - Unknown accuracy	0001	1	EPU < 18.52 km (10 NM) - RNP-10 accuracy	0010	2	EPU < 7.408 km (4 NM) - RNP-4 accuracy	0011	3	EPU < 3.704 km (2 NM) - RNP-2 accuracy	0100	4	EPU < 1852 m (1NM) - RNP-1 accuracy	0101	5	EPU < 926 m (0.5 NM) - RNP-0.5 accuracy	0110	6	EPU < 555.6 m ( 0.3 NM) - RNP-0.3 accuracy	0111	7	EPU < 185.2 m (0.1 NM) - RNP-0.1 accuracy	1000	8	EPU < 92.6 m (0.05 NM) - e.g., GPS (with SA)	1001	9	EPU < 30 m - e.g., GPS (SA off)	1010	10	EPU < 10 m - e.g., WAAS	1011	11	EPU < 3 m - e.g., LAAS	1100 - 1111	12 - 15	Reserved
Coding		Meaning = 95% Horizontal Accuracy Bounds (EPU)																																												
(Binary)	(Decimal)																																													
0000	0	EPU ≥ 18.52 km (10 NM) - Unknown accuracy																																												
0001	1	EPU < 18.52 km (10 NM) - RNP-10 accuracy																																												
0010	2	EPU < 7.408 km (4 NM) - RNP-4 accuracy																																												
0011	3	EPU < 3.704 km (2 NM) - RNP-2 accuracy																																												
0100	4	EPU < 1852 m (1NM) - RNP-1 accuracy																																												
0101	5	EPU < 926 m (0.5 NM) - RNP-0.5 accuracy																																												
0110	6	EPU < 555.6 m ( 0.3 NM) - RNP-0.3 accuracy																																												
0111	7	EPU < 185.2 m (0.1 NM) - RNP-0.1 accuracy																																												
1000	8	EPU < 92.6 m (0.05 NM) - e.g., GPS (with SA)																																												
1001	9	EPU < 30 m - e.g., GPS (SA off)																																												
1010	10	EPU < 10 m - e.g., WAAS																																												
1011	11	EPU < 3 m - e.g., LAAS																																												
1100 - 1111	12 - 15	Reserved																																												
<p><b>NACv</b></p>	<p>Navigation Accuracy Category for velocity</p>	<table border="1"> <thead> <tr> <th colspan="3">Navigation Accuracy Category for Velocity</th> </tr> <tr> <th colspan="2">Coding</th> <th rowspan="2">Horizontal Velocity Error</th> </tr> <tr> <th>(Binary)</th> <th>(Decimal)</th> </tr> </thead> <tbody> <tr><td>000</td><td>0</td><td>≥ 10 m/s</td></tr> <tr><td>001</td><td>1</td><td>&lt; 10 m/s</td></tr> <tr><td>010</td><td>2</td><td>&lt; 3 m/s</td></tr> <tr><td>011</td><td>3</td><td>&lt; 1 m/s</td></tr> <tr><td>100</td><td>4</td><td>&lt; 0.3 m/s</td></tr> </tbody> </table> <p>Navigation Accuracy Category for Velocity (NACv). NACv is based on design data provided by the position source manufacturer. The NACv may be updated dynamically from the position source, or set statically based on qualification of the position source.</p> <p>(a) A NACv = 1 (&lt; 10 m/s) may be permanently set at installation for GNSS equipment passing the tests identified in appendix 2, or may be set dynamically from velocity accuracy output of a position source qualified in accordance with the AC 20-165B appendix B guidance.</p> <p>(b) A NACv = 2 (&lt; 3 m/s) may be set dynamically from velocity accuracy output of a position source qualified in accordance with the</p>	Navigation Accuracy Category for Velocity			Coding		Horizontal Velocity Error	(Binary)	(Decimal)	000	0	≥ 10 m/s	001	1	< 10 m/s	010	2	< 3 m/s	011	3	< 1 m/s	100	4	< 0.3 m/s																					
Navigation Accuracy Category for Velocity																																														
Coding		Horizontal Velocity Error																																												
(Binary)	(Decimal)																																													
000	0	≥ 10 m/s																																												
001	1	< 10 m/s																																												
010	2	< 3 m/s																																												
011	3	< 1 m/s																																												
100	4	< 0.3 m/s																																												

Appendix 2 guidance. NACv = 2 should not be permanently preset at installation, even if the position source has passed the tests identified in AC 20-165B appendix B.

A NACv = 3 or NACV = 4 should not be set based on GNSS velocity accuracy unless you can demonstrate to the FAA that the velocity accuracy actually meets the requirement.

**NIC**

Navigation Integrity Category

NIC encoding is used to indicate the radius of containment around the aircraft. §91.227 requires a minimum NIC of 7. NIC values of <7 will be flagged red within a PAPER when the MCF threshold is exceeded.

NIC Value	Radius of Containment (R <sub>c</sub> )	Airborne				Surface		
		Airborne Position TYPE Code	NIC Supplement Codes		Surface Position TYPE Code	NIC Supplement Codes		
			A	B		A	C	
0	R <sub>c</sub> unknown	0, 18 or 22	0	0	0, 8	0	0	
1	R <sub>c</sub> < 20 NM (37.04 km)	17	0	0	N/A	N/A	N/A	
2	R <sub>c</sub> < 8 NM (14.816 km)	16	0	0	N/A	N/A	N/A	
3	R <sub>c</sub> < 4 NM (7.408 km)	16	1	1	N/A	N/A	N/A	
4	R <sub>c</sub> < 2 NM (3.704 km)	15	0	0	N/A	N/A	N/A	
5	R <sub>c</sub> < 1 NM (1.852 m)	14	0	0	N/A	N/A	N/A	
6	R <sub>c</sub> < 0.6 NM (1111.2 m)	13	1	1	8	0	1	
	R <sub>c</sub> < 0.5 NM (926 m)	13	0	0	N/A	N/A	N/A	
	R <sub>c</sub> < 0.3 NM (555.6 m)	13	0	1	8	1	0	
7	R <sub>c</sub> < 0.2 NM (370.4 m)	12	0	0	8	1	1	
8	R <sub>c</sub> < 0.1 NM (185.2 m)	11	0	0	7	0	0	
9	R <sub>c</sub> < 75m	11	1	1	7	1	0	
10	R <sub>c</sub> < 25m	10 or 21	0	0	6	0	0	
11	R <sub>c</sub> < 7.5m	9 or 20	0	0	5	0	0	
12		Reserved						
13		Reserved						
14		Reserved						
15		Reserved						

**NIC Baro**

NIC baro is a one-bit field that is used to report if the altitude is being checked against another source of pressure altitude.

Coding	Meaning
0	The barometric altitude that is being reported in the Airborne Position Message is based on a Gilham coded input that has not been cross-checked against another source of pressure altitude
1	The barometric altitude that is being reported in the Airborne Position Message is either based on a Gilham code input that has been cross-checked against another source of pressure altitude and verified as being consistent, or is based on a non-Gilham coded source

**No "N"** Percent, total time, and max consecutive reports aircraft reported a N Number Flight ID without the leading "N"

**Non-US** Percent, total time, and max consecutive reports aircraft reported a N Number Flight ID and a 24-bit ICAO address outside the U.S. block

**Operation Id** Unique flight identification number that is shown in the report to allow users to return to that operation to look at it again.

**Other Checks** Category of checks that looks at assorted issues such as illegal characters in your flight ID, improper/missing Mode 3/A code, and Duplicate 24-bit ICAO addresses. See Other Checks section in Part 1 of this document.

**Only "N"** Percent, total time, and max consecutive reports aircraft reported just "N" for flight ID

**Out Capability** Indicates the type of ADS-B Out link the transmitter operates on i.e., 1090, UAT, Dual (both links)

<b>Partial</b>		Mostly for Air Carriers, percent, total time, and max consecutive reports aircraft reported a Flight ID missing the leading three letter identifier																											
<b>Processed reports</b>		Number of ADS-B reports actually processed by the FAA ground system																											
<b>Rule</b>		This overall category fails if you fail any of the categories mandated. If this box is labeled no, the test was a success.																											
<b>SDA</b>	System Design Assurance	<p>Measures the likelihood of bad data being sent. Pass for values 2 and 3</p> <table border="1"> <thead> <tr> <th colspan="2">SDA Value</th> <th rowspan="2">Supported Failure Condition <small>Note 2</small></th> <th rowspan="2">Probability of Undetected Fault causing transmission of False or Misleading Information <small>Note 2,4</small></th> <th rowspan="2">Software &amp; Hardware Design Assurance Level <small>Note 1,3</small></th> </tr> <tr> <th>(decimal)</th> <th>(binary)</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>00</td> <td>Unknown/ No safety effect</td> <td><math>&gt; 1 \times 10^{-3}</math> per flight hour or Unknown</td> <td>N/A</td> </tr> <tr> <td>1</td> <td>01</td> <td>Minor</td> <td><math>\leq 1 \times 10^{-3}</math> per flight hour</td> <td>D</td> </tr> <tr> <td>2</td> <td>10</td> <td>Major</td> <td><math>\leq 1 \times 10^{-5}</math> per flight hour</td> <td>C</td> </tr> <tr> <td>3</td> <td>11</td> <td>Hazardous</td> <td><math>\leq 1 \times 10^{-7}</math> per flight hour</td> <td>B</td> </tr> </tbody> </table>	SDA Value		Supported Failure Condition <small>Note 2</small>	Probability of Undetected Fault causing transmission of False or Misleading Information <small>Note 2,4</small>	Software & Hardware Design Assurance Level <small>Note 1,3</small>	(decimal)	(binary)	0	00	Unknown/ No safety effect	$> 1 \times 10^{-3}$ per flight hour or Unknown	N/A	1	01	Minor	$\leq 1 \times 10^{-3}$ per flight hour	D	2	10	Major	$\leq 1 \times 10^{-5}$ per flight hour	C	3	11	Hazardous	$\leq 1 \times 10^{-7}$ per flight hour	B
SDA Value		Supported Failure Condition <small>Note 2</small>	Probability of Undetected Fault causing transmission of False or Misleading Information <small>Note 2,4</small>	Software & Hardware Design Assurance Level <small>Note 1,3</small>																									
(decimal)	(binary)																												
0	00	Unknown/ No safety effect	$> 1 \times 10^{-3}$ per flight hour or Unknown	N/A																									
1	01	Minor	$\leq 1 \times 10^{-3}$ per flight hour	D																									
2	10	Major	$\leq 1 \times 10^{-5}$ per flight hour	C																									
3	11	Hazardous	$\leq 1 \times 10^{-7}$ per flight hour	B																									
<b>SIL</b>	Source Integrity Level	<p>Measurement of the probability of not being within the containment radius. Pass for value 3 only</p> <table border="1"> <thead> <tr> <th colspan="2">SIL Coding</th> <th rowspan="2">Probability of Exceeding the NIC Containment Radius (<math>R_c</math>)</th> </tr> <tr> <th>(Binary)</th> <th>(Decimal)</th> </tr> </thead> <tbody> <tr> <td>00</td> <td>0</td> <td>Unknown or <math>&gt; 1 \times 10^{-3}</math> per flight hour or per sample</td> </tr> <tr> <td>01</td> <td>1</td> <td><math>\leq 1 \times 10^{-3}</math> per flight hour or per sample</td> </tr> <tr> <td>10</td> <td>2</td> <td><math>\leq 1 \times 10^{-5}</math> per flight hour or per sample</td> </tr> <tr> <td>11</td> <td>3</td> <td><math>\leq 1 \times 10^{-7}</math> per flight hour or per sample</td> </tr> </tbody> </table>	SIL Coding		Probability of Exceeding the NIC Containment Radius ( $R_c$ )	(Binary)	(Decimal)	00	0	Unknown or $> 1 \times 10^{-3}$ per flight hour or per sample	01	1	$\leq 1 \times 10^{-3}$ per flight hour or per sample	10	2	$\leq 1 \times 10^{-5}$ per flight hour or per sample	11	3	$\leq 1 \times 10^{-7}$ per flight hour or per sample										
SIL Coding		Probability of Exceeding the NIC Containment Radius ( $R_c$ )																											
(Binary)	(Decimal)																												
00	0	Unknown or $> 1 \times 10^{-3}$ per flight hour or per sample																											
01	1	$\leq 1 \times 10^{-3}$ per flight hour or per sample																											
10	2	$\leq 1 \times 10^{-5}$ per flight hour or per sample																											
11	3	$\leq 1 \times 10^{-7}$ per flight hour or per sample																											
<b>SILs</b>	Source Integrity Level Supplement	This is a one bit field that informs the system if the SIL is being given on a per hour or a per sample basis, assigned as 0 or 1 respectively																											
<b>SQL</b>	Signal Quality Level	Measure of integrity of data sent. Not used to determine if an operation makes it onto the exception list																											
<b>Stationary only</b>		Field that marks if the recorded flight was stationary (ground only)																											
<b>Tail Number</b>		Number assigned to the aircraft at registration (N-number)																											
<b>TIS-B Client %</b>		% of flight time that the aircraft was provided TIS-B data.																											
<b>Total reports</b>		Total reports broadcast by the ADS-B transmitter																											
<b>Type Registration</b>		Type of registration associated with aircraft e.g. civil, military, etc.																											
<b>UAT Only above 18k</b>		When flagged, indicates UAT-Only equipped aircraft operating in Class A airspace (above 18K feet) where 1090 ADS-B equipment is required by 91.225.																											
<b>Unavail Char</b>		Percent, total time, and max consecutive reports aircraft reported a Flight ID with an Unavailable Character																											
<b>Vel/ Position Δ</b>	Velocity & Position delta	Velocity is encoded in ADS-B messages. The performance monitor checks these values against aircraft performance and flags a PAPR if the <u>velocity</u> is greater than 300 meters/sec (583 knots or a position is greater than 1,312 feet/sec (400m/s).																											

<b>Vertical Velocity</b>		Vertical Velocity is encoded in ADS-B messages. The performance monitor checks these values against aircraft performance and flags any unusual or unreasonable values
--------------------------	--	---

Additional information about ADS-B can be found in the following documents:

1. Advisory Circular (AC) 90-114(current version), Automatic Dependent Surveillance-Broadcast (ADS-B) Operations
2. AC 20-165(current version), Airworthiness Approval of Automatic Dependent Surveillance – Broadcast (ADS-B) OUT Systems in Aircraft (guidance on ADS-B system design, certification, and installation).
3. Aeronautical Information Manual
4. 14 CFR §91.225 and 91.227

# Appendix C

## ADS-B STATISTICAL ANALYSIS SYSTEM

Central American Corporation of Air  
Navigation Services



July 2022

# ADS-B STATISTICAL ANALYSIS SYSTEM


Hereunder, the ADS-B Dashboard developed by COCESNA is illustrated, which allows, from the continuous recordings of ADS-B data, to graphically present the statistical results of the ADS-B messages that are formatted in Asterix Category 21, for each one of the ADS-B sensors installed in Central America.

The main statistics of the Dashboard can be filtered by date and by the different identifiers of the aircraft and consolidated by time periods, see the following figure.

**Fig 1. Main filters of the ADS-B Dashboard**

The following figure illustrates the statistics of total ADS-B decoded messages since 2019, including the number of aircraft with ADS-B.


**Fig. 2. Total, de Mensajes decodificados y aeronaves con capacidad ADS-B**



The above information can also be obtained by flight. The following figure illustrates the evolution of ADS-B avionics, where it can be seen how the DO-260B capacity grew significantly throughout 2019, due to the ADS-B mandate established by the FAA for January 1, 2020.




**Fig. 3.- Statistics of flights with ADS-B capacity and evolution of ADS-B capacity (MOPS)**




The following figures illustrate the statistics for the different figures of merit for ADS-B messages.

**Fig. 4.- Statistics of the main ADS-B figures of merit**



The system also allows an analysis of the main items of the messages formatted in CAT 21 and filtered by date and aircraft address.

**Fig. 5.- Data item statistics of ADS-B messages**



One of the main functions is to carry out analyzes filtered by dates and by the different identifiers of the aircraft, of the information obtained from the ADS-B messages.

This allows performance rules to be defined based on a selection of figures of merit and compliance thresholds according to the requirement of the airspace to be analyzed. An example is illustrated in the following figure to show the capabilities of such functionality.

**Fig. 6. Data filtering by performance rules formed by ADS-B figures of merit.**

Query stats

Start date:

Target address:

Target address country:

End date:

Target identification:

Target identification country:

Mode 3A:

ECAT:

	Id:	Code:	Description:	Threshold:	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	

	Id	Code	Description	Threshold	Status
<input type="button" value="Select"/>	1	PRFMFAA	PERFORMANCE FAA	50	<input type="button" value="Active"/>
<input type="button" value="Select"/>	2	260B_1	VUELOS CON TECNOLOGÍA 260B	90	<input type="button" value="Active"/>
<input type="button" value="Select"/>	3	VN_260B	260B	90	<input type="button" value="Active"/>

Filters

Query -

Details:

Code    FAA\_2

Description    PERFORMANCE FAA

Threshold    50

Filters:

Field	Operator	Values
NACP	>=	8 - EPU < 92,6 m (0,05 NM)
NUCpNIC	>=	7 - 7 (260 NUC 7, 260A NIC 8, 260B NIC 8)
NUCrNACv	>=	1 - < 10 m/s
SDA	>=	2 - 2ND
SIL	=	3 - <= 1 x 10 <sup>-7</sup> per flight hour or per sample
VN	=	2 - ED102A/DO-260B

Search

Search


Export to Excel

Export to Excel all the source messages of this query. This can take several minutes to complete. Data scope:

Summary

Msg date	Target address	Target identification	ECAT	Total messages	% compliance	Complies	Total compliance
2022-08-01	OAC138			425	100	Yes	425
2022-08-01	OAC138	NSE8807	2	499	100	Yes	499
2022-08-01	OAC138	NSE8815	2	456	100	Yes	456
2022-08-01	OAC138	NSE8808	2	404	100	Yes	404
2022-08-01	OAE093	GRA428A	1	16	100	Yes	16
2022-08-01	OAE056	POLI002	1	450	100	Yes	450
2022-08-01	OAE036	TIBGT	1	19	100	Yes	19
2022-08-01	OAC466	ULSS391	3	9	100	Yes	9
2022-08-01	OC2057	JOS0214	3	2226	100	Yes	2226
2022-08-01	OBA014	HRREM	1	2133	100	Yes	2133

Flight compliance analysis



Showing 1 to 10 of 32,979 entries

Previous 1 2 3 4 5 ... 3298 Next

% of messages that comply exactly with the filters

— END —