DGP/26-WP/22\* 18/8/17

منظمة الطيران المدني الدولي ورقة عمل



فريق خبراء البضائع الخطرة الاجتماع السادس والعشرون مونتريال، من 16 إلى 2017/10/27

البند رقم 6-3 من جدول الأعمال: التخفيف من المخاطر الناجمة عن نقل بطاريات الليثيوم عن طريق الجو (بطاقة الأعمال دقمDGP.003.01).

عدد بطاريات الليثيوم الاحتياطية المحمولة مع الأجهزة

(مقدمة من د. برينان)

الملخص تقترح ورقة العمل هذه تتقيح تعليمات التغليف 966 و969 لتوضيح عدد بطاريات اللينيوم الاحتياطية المسموح بحملها مع الأجهزة. الإجراء المطلوب من فريق الخبراء: يُرجى من فريق الخبراء النظر في تتقيح تعليمات التغليف 966 و969 على النحو المبين في مرفق هذه الورقة.

#### 1. **INTRODUCTION**

1.1 At the seventeenth working group meeting of the Dangerous Goods Panel (DGP-WG/17, Montréal, 24 to 28 April 2017), a paper was presented (DGP-WG/17-WP/41) that proposed revisions to Packing Instructions 966 and 969 to clarify the number of spares that may be packed with equipment (see paragraph 3.5.3.8 of the DGP-WG/17 report). These packing instructions in both Section I and Section II have the following condition: "The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two spares."

The working group agreed that the intent of the provisions in the packing instructions was 1.2 to allow for two spare "sets" of cells or batteries per piece of equipment and there was a need to modify the wording of the packing instructions to remove any ambiguity. However, the wording of the proposed changes in DGP-WG/17-WP/41 was not seen as sufficiently clear to achieve this.

\*تُر حم ملخص ورقة العمل فقط

1.3 Based on the feedback at DGP-WG/17 a revised proposal has been developed that specifically refers to "two spare sets" of cells or batteries and then what is meant by a "set".

### 2. ACTION BY THE DGP

2.1 The DGP is invited to revise Packing Instruction 966 and Packing Instruction 969 as shown in the appendix to this working paper.

\_\_\_\_\_

#### APPENDIX

### PROPOSED AMENDMENT TO PART 4 OF THE TECHNICAL INSTRUCTIONS

## Part 4

# PACKING INSTRUCTIONS

### Chapter 11

### CLASS 9 — MISCELLANEOUS DANGEROUS GOODS

Parts of this Chapter are affected by State Variation US 2; see Table A-1

#### 11.1 PACKING INSTRUCTIONS

• • •

. . .

## Packing Instruction 966

Passenger and cargo aircraft for UN 3481 (packed with equipment) only

•••

I. SECTION I

• • •

#### 1.2 Additional requirements

- Lithium ion cells and batteries must be protected against short circuits.
- Lithium ion cells or batteries must:
  - be placed in inner packagings that completely enclose the cell or battery then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group II performance requirements; or
  - be placed in inner packagings that completely enclose the cell or battery, then placed with equipment in a
    packaging that meets the Packing Group II performance requirements.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The number of cells or batteries in each package must not exceed the appropriate number for the
  equipment's operation, plus two-spares. spare sets. A "set" of cells or batteries is the number of individual
  cells or batteries that are required to power each piece of equipment.

• • •

#### II. SECTION II

• • •

#### II.2 Additional requirements

- Lithium ion cells and batteries must:
  - be placed in inner packagings that completely enclose the cell or battery, then placed in a strong rigid outer packaging; or
  - be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong rigid outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact

with conductive materials within the same packaging that could lead to a short circuit.
The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two-spares. spare sets. A "set" of cells or batteries is the number of individual cells or batteries that are required to power each piece of equipment.

• • •

Packing Instruction 969	
	Passenger and cargo aircraft for UN 3091 (packed with equipment) only
• • •	
l. <b>SE</b>	CTION I
•••	
I.2 <b>Ad</b>	ditional requirements
	Lithium metal cells and batteries must be protected against short circuits. Lithium metal cells or batteries must:
_	<ul> <li>be placed in inner packagings that completely enclose the cell or battery, then placed in an outer packaging. The completed package for the cells or batteries must meet the Packing Group performance requirements; or</li> </ul>
	<ul> <li>be placed in inner packagings that completely enclose the cell or battery, then placed with equipment i a packaging that meets the Packing Group II performance requirements.</li> </ul>
—	The equipment must be secured against movement within the outer packaging and must be equipped wit an effective means of preventing accidental activation.
—	The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two-spares, spare sets. A "set" of cells or batteries is the number of
	individual cells or batteries that are required to power each piece of equipment.
• • •	
II. SE	
•••	
II.2 <b>Ad</b>	ditional requirements
	Lithium metal cells or batteries must:
	<ul> <li>be placed in inner packagings that completely enclose the cell or battery, then placed in a strong rigid outer packaging; or</li> </ul>
	<ul> <li>be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong rigid outer packaging.</li> </ul>
—	Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
—	The equipment must be secured against movement within the outer packaging and must be equipped wit an effective means of preventing accidental activation.
	The number of cells or batteries in each package must not exceed the appropriate number for the equipment's operation, plus two-spares, spare sets. A "set" of cells or batteries is the number of individual cells or batteries that are required to power each piece of equipment.