DANGEROUS GOODS PANEL (DGP)

TWENTY-NINTH MEETING

Montréal, 13 to 17 November 2023

- Agenda Item 1: Harmonizing ICAO dangerous goods provisions with UN Recommendations on the Transport of Dangerous Goods (*Ref: REC-A-DGS-2025*)
 - 1.2: Develop proposals, if necessary, for amendments to the *Technical Instructions for* the Safe Transport of Dangerous Goods by Air (Doc 9284) for incorporation in the 2025-2026 Edition

AMENDMENTS TO PART 5 OF THE TECHNICAL INSTRUCTIONS DEVELOPED BY DGP-WG/22 AND DGP-WG/23

(Presented by the Secretary)

SUMMARY

This working paper contains consolidated draft amendments to Part 5 of the Technical Instructions developed by the Working Group of the DGP in 2022 (DGP-WG/2022) and 2023 (DGP-WG/2023) to:

- a) reflect the decisions taken by the UN Committee of Experts on the Transport of Dangerous Goods and on the Globally Harmonized System of Classification and Labelling of Chemicals at its eleventh session (Geneva, 9 December 2022);
- b) manage aviation specific risks;
- c) facilitate transport or state oversight; and
- d) address issues related to lithium batteries.

The DGP is invited to agree to the draft amendments in this working paper.

UN harmonization amendments

And

Amendments to battery provisions

Paragraph 4.1.2.1.6 of DGP-WG/23 report:

Part 5

SHIPPER'S RESPONSIBILITIES

. . .

Chapter 2

MARKING

. . .

2.4 MARKING SPECIFICATIONS AND REQUIREMENTS

• • •

UN Model Regulations, Chapter 5.2, 5.2.1.9 (see ST/SG/AC.10/50/Add.1)

2.4.16 Special marking requirements for lithium or sodium ion batteries

- 2.4.16.1 Packages containing lithium or sodium ion cells or batteries prepared in accordance with Section II of Packing Instructions 966, 967, 969—or, 970, 977 or 978 and Section IB of Packing Instructions 965 and 968 must be marked as shown in Figure 5-3.
 - 2.4.16.2 The mark must indicate the appropriate UN number preceded by the letters "UN" as follows:
 - a) "UN 3090" for lithium metal cells or batteries;
 - b) "UN 3480" for lithium ion cells or batteries;
 - c) "UN 3091" for lithium metal cells or batteries contained in, or packed with, equipment; or
 - d) "UN 3481" for lithium ion cells or batteries contained in, or packed with, equipment.;
 - e) "UN 3551" for sodium ion cells or batteries; or
 - f) "UN 3552" for sodium ion cells or batteries contained in, or packed with, equipment.

Where a package contains lithium cells or batteries assigned to different UN numbers, all applicable UN numbers must be indicated on one or more marks.

- 2.4.16.3 The mark must be in the form of a rectangle or a square with hatched edging. The symbol (group of batteries, one damaged and emitting flame, above the UN number for lithium ion—or_, lithium metal or sodium ion_ batteries or cells) must be black on white or suitable contrasting background. The hatching must be red. The mark must be a minimum dimension of 100 mm wide × 100 mm high and the minimum width of the hatching must be 5 mm. If the size of the package so requires, the dimensions may be reduced to not less than 100 mm wide × 70 mm high. Where dimensions are not specified, all features must be in approximate proportion to those shown on the full-size mark (Figure 5-3).
- [2.4.16.4 Packages containing lithium or sodium ion batteries batteries that meet the requirements of Section IB of Packing Instructions 965 or 968 must bear both the lithium or sodium ion battery mark (Figure 5-3) and the lithium or sodium ion battery Class 9 hazard label (Figure 5-26).]

. . .

UN Model Regulations, Chapter 5.2, Figure 5.2.5 (see ST/SG/AC.10/50/Add.1)



Minimum dimension 100 mm

* Place for UN number(s)

Figure 5-3. Lithium or sodium ion battery mark

. .

Chapter 3

LABELLING

• •

3.5 LABEL SPECIFICATIONS

3.5.1 Class hazard label specifications

3.5.1.1 Labels must satisfy the provisions of this section and conform, in terms of colour, symbols and general format, to the specimen labels shown in Figures 5-4 to 5-26.

Note.— Where appropriate, labels in Figures 5-4 to 5-26 are shown with a dotted outer boundary as provided for in 3.5.1.1 a). This is not required when the label is applied on a background of contrasting colour.

Class hazard labels must conform to the following specifications:

• •

UN Model Regulations, Chapter 3.2, dangerous goods list (see ST/SG/AC.10/50/Add.1):

- c) With the exception of labels for Divisions 1.4, 1.5 and 1.6 of Class 1, the upper half of the label must contain the pictorial symbol and the lower half must contain the class or, in the case of labels for Class 5, the division number, as appropriate. However for the Class 9 label for lithium or sodium ion batteries (Figure 5-26), the upper half of the label must only contain the seven vertical stripes of the symbol and the lower half must contain the group of batteries of the symbol and the class number. Except for the Class 9 label for lithium or sodium ion batteries (Figure 5-26), the label may include such text as the UN number, or words describing the hazard class (e.g. "flammable") in accordance with 3.5.1.1 e) provided that the text does not obscure or detract from the other required label elements.
- d) In addition, except for Divisions 1.4, 1.5 and 1.6, labels for Class 1 must show in the lower half, above the class number, the division number and compatibility group letter for the substance or article. Labels for Divisions 1.4, 1.5 and 1.6 must show in the upper half the division number and in the lower half the class number and the compatibility group letter.
- e) On labels other than those for material of Class 7, the insertion of any text (other than the class or division number or compatibility group) in the space below the symbol must be confined to particulars indicating the nature of the hazard and precautions to be taken in handling. In the case of the Class 9 label for lithium or sodium ion batteries (Figure 5-26), no text other than the class number must be included in the bottom part of the label.

. . .

(Miscellaneous — Lithium or sodium ion cells and batteries)



Symbol (seven vertical stripes in upper half); battery group, one broken and emitting flame in lower half: black Background: white

Figure "9" underlined in bottom corner

Figure 5-26. Miscellaneous dangerous goods — lithium or sodium ion batteries, Class 9

DGP/29-WP/15

Chapter 4

- 5 -

DOCUMENTATION

• • •

4.1.4 Information required on the dangerous goods transport document

4.1.4.1 Dangerous goods description

The dangerous goods transport document must contain the following information for each dangerous substance, material or article offered for transport:

- a) the UN or ID number preceded by the letters "UN" or "ID" as appropriate;
- b) the proper shipping name, as determined according to 3;1.2, including the technical name enclosed in parenthesis, as applicable (see 3;1.2.7);
- c) the primary hazard class or, when assigned, the division of the goods, including for Class 1 the compatibility group letter. The words "Class" or "Division" may be included preceding the primary hazard class or division numbers;
- d) subsidiary hazard class or division number(s) corresponding to the subsidiary hazard label(s) required to be applied, when assigned, must be entered following the primary hazard class or division and must be enclosed in parenthesis. The words "Class" or "Division" may be included preceding the subsidiary hazard class or division numbers;
- e) where assigned, the packing group for the substance or article which may be preceded by "PG" (e.g. "PG II").

Amendments to facilitate transport or State oversight

And

Amendments to battery provisions

Note.— Until 31 March 2025, shippers may identify vehicles powered by lithium batteries, UN 3171 — **Battery powered vehicle** as shown in the 2023-2024 Edition of these Instructions. The marks and labels applied, when required, must be consistent with the information shown on the dangerous goods transport document.

• •

Amendments to manage aviation specific risks

Paragraph 4.2.2.3 of DGP-WG/23 report:

4.4 RETENTION OF DANGEROUS GOODS TRANSPORT INFORMATION

- 4.4.1 The shipper must retain a copy of the dangerous goods transport document and additional information and documentation as specified in these Instructions, for a minimum period of three months and be made available to the appropriate national authority upon request.
- 4.4.2 When the documents are kept electronically or in a computer system, the shipper must be able to reproduce them in a printed form.

. . .

— END —